



### Electrical Characteristics

Nominal Impedance: 50 ohms
Frequency Range: DC to 11 GHz
VSWR 1.3:1 maximum
Insertion Loss 0.17 dB max

Operating Voltage (rms): 1500 V maximum at sea level
Dielectric Withstand Voltage (rms): 2500 V maximum at sea level
Contact Resistance: 1.0 milliohms maximum
Insulation Resistance: 5000 megohms minimum

### **Mechanical Characteristics**

Mating Cycles: 500 cycles minimum
Interface Dimensions: Conform to MIL-C-39012

### **Environmental Characteristics**

Temperature Range: -65 °C to +165 °C

	PART	DESCRIPTION		
1	Body	Brass, nickel plated		
2	Ferrule	Brass, nickel plated		
3	Contact	Brass, gold plated		
4	Dielectric	Teflon		

Dimensions / Material Update	MS	5	03 Jun 19
Contact Dimensions updated	MS	4	24 Apr 09
Crimp dimension was 3.3mm	PDC	3	04 Oct 02
CAD Issue	SN	2	29 Jan 02
First Issue	DW	1	15 Jun 99
DESCRIPTION OF REVISION	APPVD	ISS	DATE

## For stripping and assembly instuctions see Drawing Number: VAIN1101

+0.08



Ø2.9±0.1

Ø2,4±0,1

CINCH CONNECTORS LTD

SHIREOAKS ROAD, WORKSOP S80 3HA (01909) 474131

17.4±0.1

11 BILTON ROAD, CHELMSFORD CM1 2UP (01245) 342060

	SCALE: Not To Scale	DRAWN BY:	P D Couzens
	DIMENSIONS: mm	CHECKED BY:	
	TOLERANCES: ± 0.2mm unless	APPROVED BY:	
	otherwise stated	DATE:	04 Oct 02

TITLE:

N Crimp Plug for RG214

PART NUMBER:

VN10-2019

PAGE: 1 of 1

COPYRIGHT © 2019 VITELEC ELECTRONICS LIMITED

THIS DRAWING MAY NOT BE REPRODUCED IN WHOLE OR IN PART WITHOUT OUR WRITTEN PERMISSION

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Connectors / Coaxial Connectors category:

Click to view products by Bel Fuse manufacturer:

Other Similar products are found below:

8915-1511-000 89674-0827 6001-7071-019 6002-7051-003 6002-7551-202 6059674-1 619550-1 630059-000 M39030/3-01N 6500-7071-046 6769 CX050L2AQ 7002-1541-010 7002-1542-011 7004-1512-000 7009-1511-004 7010-1511-000 7029-1511-060 7101-1541-010 7101-1571-002 7145-1521-002 7203-1571-003 7209-1511-011 7210-1511-015 7210-1511-019 73137-5015 73216-2241 73404-2300 7405-1521-005 7405-1521-802 8527 8547 FS11V 877931 8808-1511-001 9049-9513-000 9074-9513-000 9101-9573-002 910A205F 9130-9573-002 PL11SC-026 PL375-33 PL40-5 PL74C-221 PL75MC-217 PL803-7 1200690078 1-201144-1 R107003010W R110A172100