


RF Series


- Lower impedance at high frequency range
- Endurance with ripple current: 105°C 4,000 to 8,000hours
- RoHS Compliant



■ 规格表 SPECIFICATIONS

项目 Items	特性参数 Characteristics																																							
使用温度范围 Category Temperture Range	-55~+105°C																																							
额定工作电压范围 Rated Voltage Range	6.3 ~ 100 V																																							
静电容量允许偏差 Capacitance Tolerance	±20% (M) (at 20°C, 120Hz)																																							
漏电流 Leakage Current	<p>$I \leq 0.01CV$ or $3\mu A$, which is greater after application of rated Voltage for 2 minutes .施加额定工作电压2分钟后读数,二者取大值</p> <p>Note: I=Max. leakage current (uA), C=Nominal capacitance(uF), V=Rated voltage(V) (at 20°C)</p>																																							
损耗角正切值tan δ Dissipation Factor	Rated voltage(V)	6.3	10	16	25	35	50	63	80	100																														
	$\tan \delta$ (Max.)	0.22	0.19	0.16	0.14	0.12	0.10	0.09	0.08	0.08																														
	(at 20°C, 120Hz)																																							
	<p>标称容量超过1000 μF,则每增加1000 μF,损耗角正切值增加0.02</p> <p>When nominal capacitance exceeds 1000 μF, add 0.02 to the value above for each 1000 μF increase.(at 20°C, 120Hz)</p>																																							
低温特性 Low temperature Characteristics (Max.Impedance Ratio)	<p>电容器低温的阻抗比值, 不应超过下表所列出的值 Impedance ratio values must not exceed values listed in below table.</p> <table border="1"> <tr> <td>Rated voltage(V)</td><td>6.3</td><td>10</td><td>16</td><td>25</td><td>35</td><td>50</td><td>63</td><td>80</td><td>100</td></tr> <tr> <td>Z(-25°C)/Z(+20°C)</td><td>4</td><td>3</td><td>2</td><td>2</td><td>2</td><td>2</td><td>2</td><td>2</td><td>2</td></tr> <tr> <td>Z(-55°C)/Z(+20°C)</td><td>8</td><td>6</td><td>4</td><td>3</td><td>3</td><td>3</td><td>3</td><td>3</td><td>3</td></tr> </table> <p style="text-align: right;">(at 120Hz)</p>									Rated voltage(V)	6.3	10	16	25	35	50	63	80	100	Z(-25°C)/Z(+20°C)	4	3	2	2	2	2	2	2	2	Z(-55°C)/Z(+20°C)	8	6	4	3	3	3	3	3	3	
Rated voltage(V)	6.3	10	16	25	35	50	63	80	100																															
Z(-25°C)/Z(+20°C)	4	3	2	2	2	2	2	2	2																															
Z(-55°C)/Z(+20°C)	8	6	4	3	3	3	3	3	3																															
耐久性 Endurance	<p>施加额定工作电压和额定纹波电流经下表规定时间, 恢复到20°C后, 产品性能应满足以下要求</p> <p>The following specifications shall be satisfied when the capacitors are restored to 20°C after application of rated voltage with rated ripple current for the specified period of time.</p> <table border="1"> <tr> <td>Time</td><td>Φ5 & Φ6.3:4000hrs, Φ8~Φ10:5000 hrs, Φ13:7000 hrs, Φ16 & Φ18:8000 hrs</td></tr> <tr> <td>Capacitance change</td><td>≤±20% of the initial value</td></tr> <tr> <td>D.F. ($\tan \delta$)</td><td>≤200% of the specified value</td></tr> <tr> <td>Leakage current</td><td>≤The specified value</td></tr> </table>									Time	Φ5 & Φ6.3:4000hrs, Φ8~Φ10:5000 hrs, Φ13:7000 hrs, Φ16 & Φ18:8000 hrs	Capacitance change	≤±20% of the initial value	D.F. ($\tan \delta$)	≤200% of the specified value	Leakage current	≤The specified value																							
Time	Φ5 & Φ6.3:4000hrs, Φ8~Φ10:5000 hrs, Φ13:7000 hrs, Φ16 & Φ18:8000 hrs																																							
Capacitance change	≤±20% of the initial value																																							
D.F. ($\tan \delta$)	≤200% of the specified value																																							
Leakage current	≤The specified value																																							
高温储存特性 Shelf Life	<p>105°C 放置1000小时, 恢复到20°C后, 产品性能应满足以下要求</p> <p>The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 1000 hours at 105°C without voltage applied.</p> <table border="1"> <tr> <td>Capacitance change</td><td>≤±20% of the initial value</td></tr> <tr> <td>D.F. ($\tan \delta$)</td><td>≤200% of the specified value</td></tr> <tr> <td>Leakage current</td><td>≤The specified value</td></tr> </table>									Capacitance change	≤±20% of the initial value	D.F. ($\tan \delta$)	≤200% of the specified value	Leakage current	≤The specified value																									
Capacitance change	≤±20% of the initial value																																							
D.F. ($\tan \delta$)	≤200% of the specified value																																							
Leakage current	≤The specified value																																							

■ 外形图 DIMENSIONS (mm)



ΦD	5	6.3	8	10	13	16	18
P	2.0	2.5	3.5	5.0	5.0	7.5	7.5
Φd	0.5	0.5	0.5	0.6	0.6	0.8	0.8

a	(L<20) 1.5
	(L≥20) 2.0

■ 纹波电流补正系数 RATED RIPPLE CURRENT COEFFICIENT

- 频率系数 Frequency Coefficient

Capacitance(μF)	Frequency(Hz)	120	1k	10k	100k
0.47 ~ 180		0.40	0.75	0.90	1.00
220 ~ 560		0.50	0.85	0.94	1.00
680 ~ 1,800		0.60	0.87	0.95	1.00
2,200 ~ 3,900		0.75	0.90	0.95	1.00
4,700 ~		0.85	0.95	0.98	1.00

RF Series

■ 尺寸与最大纹波电流一览表 STANDARD RATINGS

WV(V)	6.3(0J)				10(1A)				16(1C)				25(1E)			
	Case size ΦD×L (mm)	Capaci- tance (μ F)	Impedance (Ω max)100kHz		Capaci- tance (μ F)	Impedance (Ω max)100kHz		Rated ripple current (mA rms) at 105°C 100kHz	Capaci- tance (μ F)	Impedance (Ω max)100kHz		Rated ripple current (mA rms) at 105°C 100kHz	Capaci- tance (μ F)	Impedance (Ω max)100kHz		Rated ripple current (mA rms) at 105°C 100kHz
			20°C	-10°C		20°C	-10°C			20°C	-10°C			20°C	-10°C	
5×11	150	0.50	1.0	179	100	0.50	1.0	150	47	0.50	1.0	142	47	0.50	1.0	142
6.3×11	330	0.25	0.5	294	220	0.25	0.5	279	100	0.25	0.5	265	100	0.25	0.5	265
6.3×15	470	0.18	0.36	405	330	0.18	0.36	388	220	0.18	0.36	369	150	0.18	0.36	354
8×12	680	0.12	0.24	558	470	0.12	0.24	535	330	0.12	0.24	508	220	0.12	0.24	487
8×16	1,000	0.09	0.18	732	680	0.09	0.18	695	470	0.09	0.18	667	330	0.09	0.18	640
8×20	1,200	0.08	0.16	814	1,000	0.08	0.16	773	560	0.08	0.16	726	390	0.08	0.16	697
10×13	820	0.09	0.18	964	680	0.09	0.18	915	470	0.09	0.18	878	330	0.09	0.18	843
10×16	1,200	0.068	0.106	1,054	1,000	0.068	0.136	1,011	680	0.068	0.136	951	470	0.068	0.136	913
10×20	1,500	0.052	0.104	1,224	1,200	0.052	0.104	1,162	1,000	0.052	0.104	1,116	680	0.052	0.104	1,038
10×25	2,200	0.045	0.09	1,446	1,500	0.045	0.09	1,344	1,200	0.045	0.09	1,277	820	0.045	0.09	1,200
10×30	2,700	0.037	0.074	1,698	1,800	0.037	0.074	1,579	1,500	0.037	0.074	1,500	1,000	0.037	0.074	1,395
13×20	3,300	0.038	0.076	1,668	2,200	0.038	0.076	1,551	1,500	0.038	0.076	1,489	1,000	0.038	0.076	1,414
13×25	3,900	0.03	0.06	1,954	3,300	0.03	0.06	1,875	2,200	0.03	0.06	1,744	1,500	0.03	0.06	1,657
13×30	4,700	0.025	0.05	2,314	3,900	0.025	0.05	2,152	2,700	0.025	0.05	2,001	1,800	0.025	0.05	1,901
13×35	5,600	0.022	0.044	2,516	4,700	0.022	0.044	2,390	3,300	0.022	0.044	2,270	2,200	0.022	0.044	2,157
13×40	6,800	0.017	0.034	2,874	5,600	0.017	0.034	2,701	3,900	0.017	0.034	2,539	2,700	0.017	0.034	2,412
16×21	5,600	0.029	0.058	2,906	3,900	0.029	0.058	2,702	2,700	0.029	0.058	2,594	1,800	0.029	0.058	2,490
16×26	6,800	0.022	0.044	2,930	5,600	0.022	0.044	2,783	3,900	0.022	0.044	2,644	2,700	0.022	0.044	2,512
16×30	8,200	0.019	0.038	3,270	6,800	0.019	0.038	3,041	4,700	0.019	0.038	2,889	3,300	0.019	0.038	2,715
16×35	10,000	0.017	0.034	3,610	8,200	0.017	0.034	3,357	5,600	0.017	0.034	3,122	3,900	0.017	0.034	2,934
16×40	12,000	0.015	0.03	3,716	10,000	0.015	0.03	3,455	6,800	0.015	0.03	3,178	4,700	0.015	0.03	2,987
18×21	6,800	0.028	0.056	3,892	5,600	0.028	0.056	3,736	3,900	0.028	0.056	3,512	2,200	0.028	0.056	3,266
18×26	10,000	0.02	0.04	3,945	6,800	0.02	0.04	3,747	4,700	0.02	0.04	3,560	3,300	0.02	0.04	3,417
18×30	12,000	0.018	0.036	4,036	8,200	0.018	0.036	3,834	5,600	0.018	0.036	3,604	3,900	0.018	0.036	3,423
18×35	15,000	0.016	0.032	4,184	10,000	0.016	0.032	3,891	8,200	0.016	0.032	3,696	4,700	0.016	0.032	3,437
18×40	18,000	0.015	0.03	4,209	1,200	0.015	0.03	3,914	10,000	0.015	0.03	3,718	5,600	0.015	0.03	3,495

RF Series

■ 尺寸與最大紋波電流一覽表 STANDARD RATINGS

WV(V) Case size ΦD×L (mm)	35(1V)			50(1H)			63(1J)			100(2A)						
	Capaci- tance (μ F)	Impedance (Ω max)100kHz		Capaci- tance (μ F)	Impedance (Ω max)100kHz		Capaci- tance (μ F)	Impedance (Ω max)100kHz		Capaci- tance (μ F)	Impedance (Ω max)100kHz					
		20°C	-10°C													
5×11	33	0.50	1.0	179	22	0.90	1.8	156	12	1.90	4.0	149	6.8	2.16	8.63	81
6.3×11	56	0.25	0.5	295	47	0.45	0.9	268	22	1.00	2.0	245	10	1.70	6.81	182
6.3×15	100	0.18	0.36	408	68	0.31	0.62	364	39	0.61	1.400	334				
8×12	150	0.12	0.24	559	100	0.22	0.44	489	68	0.34	0.750	406	22	1.43	3.97	236
8×16	220	0.09	0.18	734	150	0.16	0.32	638	100	0.27	0.650	538	39	0.74	1.93	315
8×20	270	0.08	0.16	749	180	0.12	0.24	734	150	0.21	0.520	694	56	0.39	1.32	500
10×13	220	0.09	0.18	894	120	0.16	0.32	831	100	0.26	0.510	793	47	0.48	1.43	430
10×16	330	0.063	0.136	1,054	220	0.21	0.380	950	180	0.13	0.26	856	68	0.240	0.99	537
10×20	470	0.052	0.104	1,226	220	0.088	0.18	1,056	180	0.15	0.290	895	82	0.23	0.56	580
	680	0.055	0.1	1,360	470	0.065	0.11	1,062					100	0.25	0.62	690
10×25	560	0.045	0.09	1,445	330	0.073	0.15	1,254	220	0.13	0.260	1,056				
					470	0.078	0.14	1,256								
10×30	680	0.037	0.074	1,694	390	0.054	0.11	1,504	330	0.09	0.180	1,304				
10×40					1,000	0.064	0.13	1,668	560	0.10	0.200	1,551	220	0.79	1.48	920
13×16													100	0.15	0.62	859
13×20	680	0.038	0.076	1,764	390	0.059	0.12	1,693	330	0.09	0.170	1,625	150	0.11	0.48	972
					680	0.067	0.13	1,721	470	0.13	0.210	1,650	220	0.08	0.15	1,290
13×25	1,000	0.03	0.06	1,956	560	0.044	0.088	1,842	390	0.07	0.140	1,725	220	0.09	0.38	1,003
					1,000	0.05	0.100	2080	560	0.052	0.110	1,823				
13×30	1,200	0.025	0.05	2,314	680	0.039	0.078	2,222	470	0.055	0.110	2,094	270	0.081	0.38	1,205
13×35	1,500	0.022	0.044	2,514	820	0.033	0.066	2,295	680	0.047	0.094	2,278	330	0.054	0.21	1,484
13×40	1,800	0.017	0.034	2875	1000	0.029	0.058	2504	820	0.042	0.084	2378	390	0.055	0.20	1,526
16×21	1,200	0.029	0.058	2914	680	0.048	0.096	2545	470	0.059	0.120	2475	220	0.100	0.44	763
16×25					1000	0.051	0.103	2623								
					1500	0.032	0.066	2720					330	0.073	0.28	1282
16×26	1,800	0.022	0.044	3064	1000	0.034	0.068	2849	680	0.050	0.100	2650				
16×30	2,200	0.019	0.038	3095	1200	0.028	0.056	2904	820	0.043	0.086	2,675				
16×32													470	0.041	0.15	1,724
16×35	2,700	0.017	0.034	3,156	1,500	0.025	0.05	2,935	1,000	0.036	0.072	2,778	560	0.036	0.13	1,763
16×40	3,300	0.015	0.03	3,212	1,800	0.021	0.042	3,206	1,200	0.030	0.060	2,854	680	0.034	0.10	1,845
18×21	1,800	0.028	0.056	3,495	820	0.042	0.084	3,286	680	0.055	0.110	2,995	330	0.056	0.18	1,207
					1,500	0.025	0.057	3,341								
18×25	2,200	0.02	0.04	3,545	1,200	0.029	0.058	3,416	820	0.043	0.086	3,176				
18×26													470	0.048	0.16	1,763
18×30	2,700	0.018	0.036	3,634	1,800	0.025	0.05	3,501	1,200	0.032	0.064	3,290				
18×32													560	0.039	0.14	1,846
18×35	3,300	0.016	0.032	3,784	2,700	0.023	0.046	3,594	1,500	0.030	0.060	3,343				
18×36													680	0.04	0.11	2,082
18×40	3,900	0.015	0.03	3,804	2,700	0.02	0.04	3,651	1,800	0.025	0.050	3,468	820	0.033	0.10	2,327

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Aluminium Electrolytic Capacitors - Radial Leaded category:

Click to view products by BERYL manufacturer:

Other Similar products are found below :

[NRELS102M35V16X16C.140LLF](#) [ESRG160ETC100MD07D](#) [227RZS050M](#) [335CKR250M](#) [476CKH100MSA](#) [477CKR100M](#)
[107CKR010M](#) [107CKH063MSA](#) [RJH-25V222MI9#](#) [RJH-35V221MG5#](#) [B43827A1106M8](#) [RJH-50V221MH6#](#) [EKYA500ELL470MF11D](#)
[B41022A5686M6](#) [ESRG250ELL101MH09D](#) [EKMA160EC3101MF07D](#) [RJB-10V471MG3#](#) [ESMG160ETD221MF11D](#)
[EKZH160ETD152MJ20S](#) [RJH-35V122MJ6#](#) [EGXF630ELL621ML20S](#) [RBD-25V100KE3#N](#) [EKMA350ELL100ME07D](#)
[ESMG160ETD101ME11D](#) [ELXY100ETD102MJ20S](#) [EGXF500ELL561ML15S](#) [EKGMG350ETD471MJ16S](#) [35YXA330MEFC10X12.5](#)
[RXW471M1ESA-0815](#) [ELXZ630ELL221MJ25S](#) [ERR1HM1R0D11OT](#) [LPE681M30060FVA](#) [LPL471M22030FVA](#) [HFE221M25030FVA](#)
[LKMD1401H221MF](#) [B41888G6108M000](#) [EKMA160ETD470MF07D](#) [UHW1J102MHD6](#) [EKGMG500ETD221MJC5S](#) [LKMK2502W101MF](#)
[LKMD1401H181MF](#) [LKMI2502G820MF](#) [LKMJ2001J122MF](#) [LKML2501C472MF](#) [LKMJ4002C681MF](#) [450MXH330MEFCSN25X45](#)
[450MXK330MA2RFC22X50](#) [63ZLH560MEFCG412.5X30](#) [ELH2DM331O25KT](#) [ELH2DM471P30KT](#)