


**666N**
**Click-type torque wrenches with reversible ratchets, for right-hand tightening, torque accuracy:  $\pm 3\%$** 

**UNI EN ISO 6789**

- Scale increased by 60% for improved visibility and setting accuracy
- Torque adjusting speed increased by 40%
- Handle and lens materials resistant to all chemical substances used in automotive sector, industry and aviation
- Red colour of o-ring indicates that wrench is unlocked and torque can be adjusted
- When not in use, set torque to lowest value of torque wrench range



	art.	Nm	Kgfm	lbf.ft	■	D mm	A mm	L mm	g	Incremento
006660002	666N/2	5÷25	0,5÷2,5	4÷18	1/4	25	29	220	300	2,0 Nm
006660003	666N/2X	5÷25	0,5÷2,5	4÷18	3/8	25	29	220	300	2,0 Nm
006660005	666N/5	10÷50	1÷5	7÷37	3/8	30	33	325	660	0,2 Nm
006660010	666N/10	20÷100	2÷10	15÷75	3/8	30	33	367	730	0,2 Nm
006660011	666N/10X	20÷100	2÷10	15÷75	1/2	30	37	367	800	0,5 Nm
006660020	666N/20	40÷200	4÷20	30÷150	1/2	40	43	465	1010	1,0 Nm
006660030	666N/30	60÷300	6÷30	50÷220	1/2	40	43	581	1380	1,0 Nm

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Spanners](#) category:*

*Click to view products by [Beta](#) manufacturer:*

Other Similar products are found below :

[74008](#) [1406504-3](#) [1406504-4](#) [1406504-5](#) [1725859-2](#) [9965](#) [1055267-1](#) [1-1406504-0](#) [TG70-24](#) [TG70-18](#) [R282320031](#) [1055512-1](#) [1055276-1](#)  
[R282303020](#) [TOL-222901](#) [523200-4](#) [TOL-171801](#) [1490262-2](#) [9968](#) [1302340394](#) [AC24VS](#) [R282340000](#) [BT-BS-609WT](#) [BT-BS-610R](#) [BT-](#)  
[BS-610RT](#) [R282320030](#) [BT-ST-302D](#) [1031-27R](#) [1031-34R](#) [1060-29](#) [1067-10](#) [1067-27](#) [1067-32](#) [1071-48](#) [10F0-26P](#) [10F0-32P](#) [10F0-55P](#) [0-](#)  
[90-947](#) [0-90-949](#) [40080606](#) [40082626](#) [40093232](#) [50184065](#) [58211008](#) [58211011](#) [58211013](#) [58211014](#) [58211015](#) [58211016](#) [58211019](#)