



Reliable

Efficient

Intelligent

**Universal, Reliable and Long Lasting. The Power for Wireless, Intelligence, and the Future.**

The Cita Technologies CPWLD 14 is a conservatively rated, highly reliable, all-weather LED driver specifically suited for the modern demands of commercial solid state lighting. A universal input / output design adapts to a wide range of line and string voltages, allowing for worldwide implementation from a single SKU. Fully variable Multiple Dimming Control delivers analog-like smoothness with zero flicker. The additional 12V auxiliary output provides a separate power source for wireless and/or control interfaces. Cita is proud to design and manufacture all of its own LED drivers, and stands behind them with a 5 year limited warranty.

### KEY FEATURES:

- **Universal Input and Output (100VAC - 305VAC)**
- **12V auxiliary output available for secondary interface**
- **Excellent 0-10V dimming performance with no flicker**
- **Compatible with IEC 60929:2006 - 0-10V ballast controls**
- **Ultra compact design**
- **Product Assurance: 5 Year Limited Warranty**  
(see warranty terms for more information)
- Smooth light output promotes longer LED life
- Fully optimized design produces clean waveforms, reducing noise and stress on components.
- Multiple Dimming control interface and wireless ready
- Fully potted design meets UL IP67
- Highly reliable in wet locations
- Excellent protection features with auto recovery for all conditions
- Long Lifetime Expectancy: >100K hours @ 50°C ambient / full load
- Low standby (Off) power: 0.2W @ 120VAC; 0.4W @ 230VAC

### APPLICATIONS:

Wide Variety of LED lighting fixtures:

- Indoor and outdoor
- Dimming and non dimming
- Industrial, commercial, and residential
- Remotely power wireless controllers, including Bluetooth™
- Worldwide acceptance
- Wireless mesh network ready



### UL INFORMATION:

- 14W LED Driver  
CC up to 1050mA, 60VDC  
CV up to 1050mA, 12V-60VDC
- EN60950-1, 2nd Edition, Class 2, IP67
- UL File: E354816

### ORDERING INFORMATION:

- **CPWLD 14-18U-070:**  
12-22VDC @ 700mA, Dimming, no AUX
- **CPWLD 14-18U-070A:**  
15-22VDC @ 700mA, Dimming + 100mA AUX
- **CPWLD 14-36U-035:**  
12-42VDC @ 350mA, Dimming, no AUX
- **CPWLD 14-36U-035B:**  
15-42VDC @ 350mA, Dimming + 200mA AUX
- **CPWLD 14-xxU-yyy(A/B):**  
Custom CC models
- **CPWLD 14-zz-00:**  
Custom CV Models  
zz = 12, 24, 36, 48, 60 or upon request

**CITA Technologies, L.L.C.**

975 Deerfield Pkwy, Buffalo Grove, Illinois 60089, USA

T: 1-800-503-9180 or 1-847-419-9118 F: 1-847-419-1515


citapower.com

**Operating Specifications**

Electrical		Environmental	
<b>Input Voltage Range</b>	100 - 305VAC (47-63Hz)	<b>Operating Temperature</b>	-30°C to +70°C
<b>Input Power</b>	Max 16W	<b>Case Temperature</b>	+90°C maximum
<b>Isolation</b>	3000VAC / 1 minute	<b>Storage Temperature</b>	-40°C to +105°C
<b>Inrush Current</b>	60A at 230VAC, 25°C cold start	<b>Ingress Protection</b>	IP67
<b>Power Factor</b>	60% Typical	<b>Case Material</b>	UL94V-0 Plastic (F1)
<b>Output Power</b>	Max 14W	<b>Safety Agency Approvals</b>	
<b>Output Voltage Range</b>	-035 version: 350mA +/-2%, 12-42VDC, 4-12 LED string -070 version: 700mA +/-2%, 12-22VDC, 4-5 LED string -035B version: 350mA +/-2%, 15-42VDC, 5-12 LED string -070A version: 700mA +/-2%, 15-22VDC, 5 LED string All models with turn off capability (DIM <1V)	EN60950-1, 2nd edition, Class 2, IP67, for wet location use	CB Certificate No: E354816-A1-CB-1
<b>Auxiliary Output</b>	-035B version: 12VDC, 200mA maximum -070A version: 12VDC, 100mA maximum (-035 and -070 versions: no auxiliary output)	UL file number: E354816, standards: UL 60950-1, 2nd Edition	Standards: IEC 60950-1(ed.2), IEC 60950 1(ed.2);am1 EN 60950-1:2006/ A11:2009/ A1:2010/ A12:2011
<b>Efficiency</b>	Typical, full load, 14W = 83% Typical, min. LED string, or at -30°C = 70%	CSA C22.2 No. 60950-1-07, 2nd Edition	EMI Standards: CE, EN 55022, Class B; FCC Part 15, Class B
<b>MTBF Lifetime</b>	>500,000 hours @ 50°C ambient, full load >100,000 hours @ 60°C ambient, full load >27,000 hours @ 70°C ambient, full load		
<b>Dimming Control</b>	Wireless dimming interface with 12VDC power output 0-10VDC (10% to 100% dimming) 0-10VDC dimming compatible with IEC60929:2006 controllable ballasts Potentiometer PWM dimming (1KHz/10VDC)		
<b>Robust Protection</b>	OVP, OCP, SCP, OTP		
Mechanical			
<b>Main Body Size</b>	L x W x H: 2.70" x 2.30" x 0.98" Weight: 0.30 lb See drawing below for details		

**Notes:**

1. This product is not intended to function with TRIAC dimmer
2. Wire Leads: Input: 18AWG, 105°C, 600V; Output: 22AWG, 105°C, 600V
3. Red (AUX+) wire only for models with auxiliary output.



L1 **CITA** CE C **UL** **US** AUX+ GND(-) CTRL+  
 L2 UL 60950-1  
 14W UNIVERSAL LED DRIVER IP67  
 100-305 VAC 50/60 Hz  
**CPWLD 14-xxU-yyzd**  
 DC OUTPUT: mm-aaVDC @ bbbmA Tc: 90°C  
 CTRL= 0-10 VDC RoHS  
 AUX OUTPUT: 12VDC @ 100 or 200 mA  
 yywwC 000000000 REV: z DC- DC+

xx: Nominal voltage: 12-56VDC  
 yy: Nominal constant current (mA)  
 d: Auxiliary designation  
 mm: Minimum Voltage  
 aa: Open circuit or maximum voltage: 15-60VDC  
 bbb: Nominal constant current  
 yywwC: Date code yyww, followed by letter "C" for mfg location  
 z: Product revision

**CITA Technologies, LLC**  
 975 Deerfield Pkwy, Buffalo Grove, Illinois 60089, USA  
 T: 1-800-503-9180 or 1-847-419-9118 F: 1-847-419-1515  
 www.citatechllc.com

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [LED Power Supplies](#) category:*

*Click to view products by [BIAS Power](#) manufacturer:*

Other Similar products are found below :

[ESS015W-1000-12](#) [PDA-WIFI](#) [PIFC-K250F](#) [PITB-K222A](#) [ALD-514012PJ134](#) [LB240S24KH](#) [LMH020-SPLC-0000-0000001](#) [79534](#) [79535](#)  
[EUG-200S210DT](#) [ESS030W-1050-21](#) [ESS030W-0900-32](#) [BPOXL 4-12-035](#) [ESS010W-0350-24](#) [ESS010W-0200-42](#) [ESM060W-1400-42](#)  
[PDA080B-1A0G](#) [ESS010W-0500-12](#) [PDA150B-S1A5G](#) [SLM140W-1.05-130-ZA](#) [ESS015W-0700-18](#) [EUD-150S350DVA](#) [LWA320-C420-](#)  
[ARK-B](#) [HVG-240-48AB](#) [HVG-320-36AB](#) [HVG-320-54AB](#) [ELG-240-C1400AB](#) [EUK-150S105DV](#) [BXCS-12Z-N2P-B1-A](#) [BXPR-WN-01-A](#)  
[LN1224CV](#) [BXCS-12D-N2P-01-A](#) [BXCS-12W-N2P-01-A](#) [HBG-160-24AB](#) [980100001200394](#) [980060001200376](#) [LC 14W 250-350MA](#)  
[FLEXC R ADV2](#) [LC 24W 500-600MA FLEXC R ADV2](#) [LC 36W 850-900MA FLEXC R ADV2](#) [LC 50W 200-350ML 170V FLEXC LP](#)  
[SNC4](#) [LC 25W 200-350ML 70V FLEXC LP SNC4](#) [LC 35W 200-350ML 121V FLEXC LP SNC4](#) [LCBI 10W 350MA PHASE-CUT/1-10V LP](#)  
[LC 13W 300MA FIXC C SNC](#) [LC 10W 250MA FIXC SC SNC2](#) [LC 35W 800MA FIXC SR ADV2](#) [LC 38W 900MA FIXC SR ADV2](#) [LC](#)  
[34W 800MA FIXC SC ADV2](#) [LC 44W 1050MA FIXC SC ADV2](#) [LC 38W 900MA 42V FIXC SRL ADV2](#)