

BiTsensor® PE(St)CH B2ca

Halogen-free cable for RS 485 transmission



Technical data:

Thermal parameters:

Operating temperature: -40 °C to 80 °C
Min. installation temperature: -20 °C

Electrical parameters:

Operating voltage: 300V
Test voltage: 2500V
Wave impedance: 120 Ω ±10%
Max. capacitance in pair: 42 nF/km

Mechanical parameters:

Min. bending radius: 30mm

Design:

Conductors: stranded tinned copper conductors class 2 acc. to EN 60228, IEC 60228
Insulation: foamed polyethylene with a thin external layer of solid polyethylene
Conductor colours: acc. to the table
Screens: aluminium backed polyester tape on every pair and tinned copper drain wire
Outer sheath: special halogen-free, self-extinguishing and flame retardant compound (acc. to EN 60332-1-2, IEC 60332-1, EN 60332-3-24, IEC 60332-3-24 cat. C), colour: green

Application:

Cable BiTsensor®PE(St)CH B2ca is dedicated for EIA/RS-485 transmission. The cable has a low capacity, thus ensuring high transmission speed for long connections. Used in protocol-based networks BACnet MS/TP, Linknet, MODbus RTU, etc. Cables may be used in dry and damp rooms, and are suitable for fixed installations. Cables classified according to **PN-EN 50575 (CPR)**.

Cat. no.	Cable type	n x mm ²	Outer diameter* [mm]	Approximate cable weight [kg/km]	Conductor colours
EB0250	BiTsensor®PE(St)CH 1x2x0,22 mm ² B2ca	1x2x0,22	5,6	41	white, blue
EB0251	BiTsensor®PE(St)CH 2x2x0,22 mm ² B2ca	2x2x0,22	7,1	62	Pair 1: white, blue Pair 2: red, black

*Outer diameter tolerance: +/-5%
 Cable Factory BITNER reserves the right to modify specifications without prior notification

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Multi-Conductor Cables](#) category:

Click to view products by [BITNER](#) manufacturer:

Other Similar products are found below :

[01342.35T.01](#) [CS2885-000](#) [CTC-0062-20-9/5-9](#) [644833-000](#) [6500FE-877-1000](#) [CW9530-000](#) [CX6543-000](#) [CXA-0066-20-4-9CS2973](#) [CXA-0078-16-1-9CS2405](#) [CY0660-000](#) [730859-000](#) [MCC-USB-4-250](#) [768146-000](#) [773159-000](#) [820457-000](#) [82907-NAT-500](#) [83005-WHT-500](#) [83023-YEL-500](#) [83027-RED-100](#) [83029-GRN-100](#) [8302-CHR-500](#) [83046-RED-100](#) [8305-CHR-100](#) [83306E-WHT-100](#) [83333-WHT-100](#) [8334-060-1000](#) [83349E-WHT-100](#) [83652-RED-100](#) [8404-060-500](#) [8441-BLK-1000](#) [8450-BLK-1000](#) [8451-GRY-U500](#) [8459-CHR-500](#) [8465-CHR-1000](#) [8466-CHR-1000](#) [8467-CHR-1000](#) [8469 060100](#) [8469-CHR-1000](#) [8471-CHR-1000](#) [8472-BLK-250](#) [8501-ORG-100](#) [8501-RED-100](#) [8503-WHT/BLU-100](#) [8520-BRN-100](#) [8520-GRY-100](#) [8523-GRY-100](#) [8523-GRY-1000](#) [8523-LT-BLU-25](#) [8523-ORG-1000](#) [8524-DK-BLU-100](#)