

BiTsensor PE(St)CH

Halogen-free, data transmission cable, RS 485



RoHS 2002/95/WE



LVD 2014/35/WE

CPR 305/2011



Technical data:

Operating temperature: -40°C to 80°C

Min. laying temperature: -20°C

Operating voltage: 300V

Test voltage: 2500V

Min. bending radius: 30mm

Construction:

Conductors: bare, annealed copper conductors, stranded class 2 acc. to EN 60228

Insulation: foam-skin PE

Cores identification: see table below

Screen: aluminium backed polyester tape over every pair, tinned copper wire braid over twisted pairs

Outer sheath: special halogen-free compound, self-extinguishing and flame retardant (acc. to EN 60332-1, EN 50265, IEC 60332-1)

Outer sheath color: green

Application:

BiTsensor PE(St)CH cable is intended to use in serial bus EIA/RS-485. Low capacity of the cable gives high frequency transmission in long connections. Used in transmission networks based on BACnet MS/TP, Linknet, MODbus RTU protocols etc. They are suitable for installation in operating in dry and damp rooms. The cable is classified acc. PN-EN 50575 (CPR)



industrial applications



internal application



PN-EN 60332-1



halogen-free
EN 50267



low smoke emission



data transmission

Cat.No.	n x mm ²	Diameter [mm]	cable weight [kg/km]	Cu [kg/km]	Cores identification
LP0178	1x2x0,22	5,6	41	17,0	white, blue
LP0185	1x2x0,22	7,1	62	24,0	1st pair: white, blue 2nd pair: red, black

Note: The cross-section (mm²) is approximate

Cable Factory BITNER reserve the right to modify the specifications without prior notice

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Multi-Conductor Cables](#) category:

Click to view products by [BITNER](#) manufacturer:

Other Similar products are found below :

[01342.35T.01](#) [CS2885-000](#) [CTC-0062-20-9/5-9](#) [644833-000](#) [6500FE-877-1000](#) [CW9530-000](#) [CX6543-000](#) [CXA-0066-20-4-9CS2973](#) [CXA-0078-16-1-9CS2405](#) [CY0660-000](#) [730859-000](#) [MCC-USB-4-250](#) [768146-000](#) [773159-000](#) [820457-000](#) [82907-NAT-500](#) [83005-WHT-500](#) [83023-YEL-500](#) [83027-RED-100](#) [83029-GRN-100](#) [8302-CHR-500](#) [83046-RED-100](#) [8305-CHR-100](#) [83306E-WHT-100](#) [83333-WHT-100](#) [8334-060-1000](#) [83349E-WHT-100](#) [83652-RED-100](#) [8404-060-500](#) [8441-BLK-1000](#) [8450-BLK-1000](#) [8451-GRY-U500](#) [8459-CHR-500](#) [8465-CHR-1000](#) [8466-CHR-1000](#) [8467-CHR-1000](#) [8469 060100](#) [8469-CHR-1000](#) [8471-CHR-1000](#) [8472-BLK-250](#) [8501-ORG-100](#) [8501-RED-100](#) [8503-WHT/BLU-100](#) [8520-BRN-100](#) [8520-GRY-100](#) [8523-GRY-100](#) [8523-GRY-1000](#) [8523-LT-BLU-25](#) [8523-ORG-1000](#) [8524-DK-BLU-100](#)