# BiTsound<sup>®</sup>Speaker Cable OFC

### Highly flexible speaker cable













indoor application

outdoor application

EN 60332-1

low operating temperature







## **Technical data:**

Operating temperature: -30°C to 80°C

Min. ambient temperature for fixed installations: -40°C

Min. installation temperature: -5°C

Test voltage 50Hz: 2000V

Min. insulation resistance: 20MΩxkm Min. bending radius: 5xØ (Ø - cable diameter)

#### **Construction:**

Conductors: bare copper conductors, highly flexible class 6 acc. to EN 60228

**Insulation:** special PVC

Core identification: 2 cores: black, red

4 cores: black, red, white, green

8 cores: black, red, white, green, yellow, grey, violet, blue

**Core arrangement:** cores twisted together

Outer sheath: special PVC, self-extinguishing and flame retardant acc. to EN 60332-1, UV resistant

Outer sheath colour: black matt

#### **Application:**

BiTsound®Speaker Cables OFC are characterized by high flexibility and increased transmission parameters. They can be installed in channels, cable trays or in plaster. Special black, matt, UV and weather-resistant outer sheath enables outdoor installation and eliminates the light reflection effect. Cables are also designed for internal, external and on-stage applications.

BiTsound®Speaker Cables OFC are classified in accordance with EN 50575 (CPR).

#### **Cable properties:**

- high impact strength and flexibility at both room and low temperatures
- thermal stability

BiTsound" Speaker Cable OFC

- special black, matt outer sheath eliminating the light reflection effect

Cat. no.	nxmm <sup>2</sup>	Outer diameter [mm]	Approximate cable weight [kg/km]	Cu [kg/km]	Max. resistance of power conductors DC at 20°C [Ω/km]
LP0199	2x1,5	7,0	75	28,8	12,80
LP0274	4x1,5	9,3	138	57,6	12,80
LP0200	2x2,5	8,0	108	48,0	7,20
LP0201	4x2,5	10,5	194	96,0	7,20
LP0296	8x2,5	13,8	369	192,0	7,20
LP0202	2x4,0	10,0	172	76,8	4,35
LP0203	4x4,0	11,7	272	153,6	4,35
LP0277	8x4,0	16,6	570	307,2	4,35

Cable Factory BITNER reserves the right to modify the specifications without prior notice Note: On customer's request other cross sections or number of cores can be produced



# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for BITNER manufacturer:

Other Similar products are found below:

EB0003 EB0005 EB0010 EB0016 EB0017 EB0030 EB0050 EB0080 H50050 H50052 H50054 H50074 H60776 H60777 H60778

H60779 H60781 H60784 H60789 H60790 H60791 H60792 H60794 H60797 H60800 H60802 H60803 H60804 H60805 H63105

H63108 H63110 H63114 H63119 H63134 H63135 H63137 H63139 H63143 H63148 H63167 H63171 IG2000.03 IG2000.05 IG2000.06

IG2000.09 IG2000.13 IG2001.03 IG2001.05 IG2001.06