1 1 FLP-94F LENS CAP, FLEXIBLE UIGHT-PIPE, FLAT FACE 99/14/09 T. Y. 2 1 FLPS2031.XXXX 2mm LIGHT PIPE CABLE, CUT LENGTH IN INCHES A Degree Flore In BOOM 11/16/12 T. Y. 3 Degree Flore In BOOM 11/16/12 T. Y. 4 Degree Flore In BOOM 11/16/12 T. Y. 5 Degree Flore In BOOM 11/16/12 T. Y. 6 Degree Flore In BOOM 11/16/12 T. Y. 7 Degree Flore In BOOM 11/16/12 T. Y. 8 Degree Flore In BOOM 11/16/12 T. Y. 9 Degree Flore In BOOM 11/16/12 T. Y. 9 Degree Flore In BOOM 11/16/12 T. Y. 1 Degree Flore In BOOM 11/16/12 T. Y. 2 Degree Flore In BOOM 11/16/12 T. Y. 2 Degree Flore In BOOM 11/16/12 T. Y. 2 Degree Flore In BOOM 11/16/12 T. Y. 3 Degree Flore In BOOM 11/16/12 T. Y. 4 Thomas Flore In Boom 11/16/12 T. Y. 4 Thomas Flore In Boom 11/16/12 T. Y. 5 Degree Flore In BOOM 11/16/12 T. Y. 5 Degree Flore In BOOM 11/16/12 T. Y. 6 Degree Flore In BOOM 11/16/12 T. Y. 6 Degree Flore In B	ITEM Q'TY	PART NUMBER	PART DESCRIPTION		DECORPORATE OF THE PROPERTY OF	TION	- ADDDOVED
### PLPS2031-XXXX 2mm LIGHT PIPE CABLE CUT LENGTH IN INCHES B Upcated Fiber in SQM 11/16/12 T.V. ###	1 1						
Ø.200 [Ø5.1mm] 0.049 [1.2mm] 0.166 [Ø4.2mm] 0.166 [4.2mm] 0.391 [9.9mm] " L " Tolerance 0.750" ~ 16.000" ±0.050" 16.100" ~ 40.000" ±0.150" 40.150" 40.100" ~ 80.000" ±0.300" 80.100" ~ 3,940.0" ±0.5% Recommended Mounting Holes	2 1						
## 0.090 [2.3mm] ## 0.039 [1.0mm] 0.049 [1.2mm]	·		,				
#NOTE: Tolerance		[Ø4.2mm]	0.049 [1.2mm] — 0.166 [4.2mm] —		2		
#NOTE: 16.100" ~ 40.000"				l e	" L "	Tolerance	
#NOTE: 16.100" ~ 40.000"					0.750" ~ 16.00 0 "	±0.050"	
#NOTE: 40.100" ~ 80.000" ±0.300" ±0.5% 40.100" ~ 3,940.0" ±0.5% *NOTE: 40.100" ~ 80.000" ±0.300" ±0.5% *DECIMALS ANGULAR X° ±1°							
Recommended Mounting Holes STANDARD TOLERANCE (UNLESS OTHERWISE SPECIFIED) DECEMBALS X ± .1 X° ± 1° TITLE: LENS CAP / FLP ASSEMBLE LENS CAP / FLP ASSEMBLE LENS CAP / FLP FLAT FAC *NOTE: **NOTE: **DATE: **DAT							
*NOTE: STANDARD TOLERANCE (UNLESS OTHERWISE SPECIFIED) DECIMALS (UNLESS OTHERWISE SPECIFIED) A THOMAS, IRVINE, CA. 92618 TEL: (949) 951-8808 FAX: (949) 951-3974 **NOTE: STANDARD TOLERANCE (UNLESS OTHERWISE SPECIFIED) A THOMAS, IRVINE, CA. 92618 TEL: (949) 951-8808 FAX: (949) 951-3974 **TITLE: LENS CAP / FLP ASSEMBLE FLAT FACE Brian Oliver O9/14/09 PART NO: FLPF-XX.X B			Ø 160 ⁺ .003 →				
*NOTE: *NOTE: **NOTE: **Recommended Mounting Holes **Recommended Mounting Holes **NOTE: **NOTE: **Recommended Mounting Holes **NOTE: **NOTE: **NOTE: **Recommended Mounting Holes **NOTE: **			9.109002	80	STANDARD TOLERANCE		®
*NOTE: *NOTE: **NOTE: **NOT			Recommended Mounting Holes		DECIMALS ANGULAR	4 THOMAS, IRVINE, O	CA, 92618
ALLOWABLE CUT LENGTH IS UP TO 3 DECIMAL PLACES. CHECKED: Fred Jensen O9/14/09 CAGE CODE: 32559 SHEET # 1 OF CAGE CODE: 32559 CAGE CODE: 32559 CAGE CODE: 32559 SHEET # 1 OF CAGE CODE: 32559 CAGE CODE: 32		E CUT LENGTH IS UF		.	.XX ± .02 .XXX ± .010 DESIGNED: Brian Oliver CHECKED: DATE: 09/14/09	TEL: (949) 951-8808 FAX: (5 TITLE: LENS CAP / FLF PART NO: FLPF-XX.X CAGE CODE: 32559 SHE	P ASSEMBLY, FLAT FACE REVISION: B ET # 1 OF 1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for LED Light Pipes category:

Click to view products by Bivar manufacturer:

Other Similar products are found below:

1367627-1 SLP3-300-450-F SLP3-400-450-R LPA-C011301S-6 LPF-C011306S FLP25-1.95 VLP-640-F LPA-C011301S-5.4 LPA-R051171S-12 LPA-S011331S 515-1027-803F 515-1217F SLP3-150-300-R SLP3-500-450-R 515-1064-810F FLPV-SG BDL-1187

7511A41 7511A87-500 FLPV-SBC 5151064802F 5151-192-0055-0DF LPF-R011340S 515-1166-801F FLPF-6.0 PM4-C1522-3.70 LC-11.25 CLP-1214 515-1064-808F FLX3_05 515-1192-0025-0DF HS LC-H-D2/ R2XC1-2 54 515-1192-80-3DF 1282.2600 1296.2004

PBLP-1001-1 SZ1-10.00-A220-F4P54 SZ1-10.00-A220-F4P LC2-4.1 1296.7042 SF4-2.5-F5P PLP5-2-625-54 FLP25-13.5 1271.2002

1272.0030 1276.2004 1281.1001-8MM 1282.1300 1296.1034 1296.2022