



SOJ/P/F Series—Half Pitch DIP Switch

Features


- ◆ Half Pitch(0.05 inch/ 1.27mm) terminal
- ◆ Standard gold-plated electrical contacts
- ◆ Tape sealed version available to ensure washability
- ◆ Singular pole: 1, 3 and 5 available
- ◆ Gull Wing Lead, J Lead and Flat Lead




SOJ (J Lead)



SOP (Gull Wing Lead)



SOF (Flat Lead)




Specifications

- ◆ Contact Rating
 - Switching 25mA, 24VDC
 - Non-Switching..... 100mA, 50VDC
- ◆ Contact Resistance
 - Initial 50mΩ Max.
 - After Life Test 100mΩ Max.
- ◆ Insulation Resistance 100MΩ min at 500VDC
- ◆ Dielectric Strength 300VAC/ 1 minute
- ◆ Operating Force..... 500g Max.
- ◆ Mechanical Life 2,000 cycles
- ◆ Electrical Life 1,000 cycles

Materials

- ◆ **Cove & Base:** Thermoplastic 94V-0, Black
- ◆ **Actuator:** Thermoplastic UL 94-HB, White
- ◆ **Movable Contact:** Copper Alloy, Gold- or Pure-Tin-plated
- ◆ **Terminal Contact & Terminal:** Copper Alloy, Gold- or Pure-Tin-Plated
- ◆ **Tape Sealed:** Polyimide Film

Wiring Diagram



Packaging Information

- ◆ Tube: SOJ/ SOP
- ◆ Tape & Reel: SOJ/ SOP/ SOF
- ◆ Actuators all in "OFF" position


Soldering Information

- ◆ Hand Soldering
 - Soldering Iron of 30W or under at 300°C for 4±1 sec. max.
- ◆ Reflow Soldering
 - Peak temperature: 260°C max. The time above 255°C must be 30 sec. max.
- ◆ Keep all actuators in "OFF" position during soldering and cleaning process

Package

P/N	No. Of Pole	Dim. A	Quantity per Tube
SOP01	1	2.31mm	93 (Half)
SOP02	2	3.58mm	125
SOP03	3	4.85mm	90
SOP04	4	6.12mm	70
SOP05	5	7.39mm	60
SOP06	6	8.66mm	50
SOP08	8	11.20mm	40
SOP10	10	13.74mm	30
SOP12	12	16.28mm	25

Order Information



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [DIP Switches/SIP Switches](#) category:

Click to view products by [BIWIN](#) manufacturer:

Other Similar products are found below :

[79B10T](#) [8136-475G4T](#) [G7G-1A2-CB-DC12](#) [DRS4016](#) [1825444-1](#) [193005MS](#) [195010MS](#) [200183](#) [206002](#) [208004](#) [208007ST](#) [208008](#)
[25.350.0653.0](#) [SDA10H1BDA](#) [97R06ST](#) [A2C-2A5](#) [1825444-7](#) [ADE12S04](#) [192960010](#) [206005RAS](#) [209005LPST](#) [2-1825058-8](#)
[219002LPST](#) [219002MSTJRF](#) [219012MST](#) [25.352.0353.0](#) [CXDRIVEV2X](#) [LA2-002-DC24](#) [DSR02T](#) [193004MS](#) [E2FMX2D1M1TGJ03M](#)
[NDI10H](#) [219-9MSTP](#) [219008LPSTR](#) [EPM02FV](#) [206010RAST](#) [76SB05](#) [TD06H0SK1](#) [Z7.255.9027.0](#) [1-1825058-3](#) [1825428-4](#) [219-](#)
[10LPSTF](#) [E3ZG6111D03M](#) [G4D212PUSTV2DC5](#) [HARW0002](#) [EPG301BT06](#) [1-1825058-6](#) [E3TSL23M5J03M](#) [Y5795](#) [7R0060](#)