#### **Data Sheet**

# Switching DC Power Supply with USB Charger Output 1-36 V, 0-3 A

### **Model 1550**



The model 1550 is a compact 108 watt power supply delivering  $1\text{-}36\ V$  and 0-3 A from its main isolated output. A unique feature of the 1550 supply is the USB charging port located on the front panel allowing the user to charge a cell phone or MP3 player. Clean power and quiet operation make this power supply ideal for any bench in laboratories, work shops and schools where bench space is limited.

#### Features:

- USB charging port on front panel
- Rear panel security loop
- Compact design
- Output On/Off control
- Large bright easy to read LCD display
- Constant voltage and constant current operation
- Overvoltage protection
- 230 VAC version with banana style outputs (model 1550-220V)



| Charge your cell phone       | USB Charging Port |  |
|------------------------------|-------------------|--|
| or MP3 player while you work |                   | F50 V COUNTY OF THE PARTY OF TH |

| Specifications                     | 1550   |  |  |
|------------------------------------|--|--|--|
| MAIN OUTPUT                        |  |  |  |
| Output Voltage Adjustable Range    | 1.0 – 36 VDC   |  |  |
| Output Current Adjustable Range    | 0 – 3 A  |  |  |
| Voltage Regulation                 |  |  |  |
| Load (10 % to 100 %)               | ±50 mV   |  |  |
| Line (min to max)                  | ±20 mV   |  |  |
| Ripple                             | ±5 mV rms  |  |  |
| Noise (Peak to Peak)               | ±50 mV   |  |  |
| Current Regulation                 |  |  |  |
| Load (10 % to 100 %)               | ±20 mA   |  |  |
| Line (min to max)                  | ±20 mA   |  |  |
| USB OUTPUT                         |  |  |  |
| Output Voltage                     | 5 V (±10 %)  |  |  |
| Output Current                     | 400 mA (±10 %)   |  |  |
| Load Voltage Regulation            | 80 mV (±10 %)  |  |  |
| Ripple & Noise (no load rms)       | 8 mV (±10 %)   |  |  |
| OTHER                              |  |  |  |
| AC Input                           | 100 − 120 Vac (50~60 Hz)*                                  |  |  |
| Efficiency at Max Power            | 83 % (±10 %)   |  |  |
| Voltmeter and Ammeter Display      | 3 Digit  |  |  |
| Voltmeter Accuracy                 | $\pm$ 1 % of rdg. $\pm$ 5 digits                           |  |  |
| Switching Operation Frequency      | 80 kHz to 120 kHz  |  |  |
| Ammeter Accuracy                   | $\pm$ 1 % of rdg. $\pm$ 5 digits                           |  |  |
| Full Load Input Current at 120 Vac | 1.8 A (±10 %)  |  |  |
| LCD Indication                     | CC, CV, Amp, Volt, Output ON-OFF                           |  |  |
| GENERAL                            |  |  |  |
| Protection                         | Short Circuit, Overload, Over Temperature,<br>Over Voltage |  |  |
| Dimensions (W x H x D)             | 2.8" x 6.0" x 9.8" (70 x 150 x 250 mm)                     |  |  |
| Weight                             | 4.4 Lbs. (2 kgs)   |  |  |
|                                    | One-Year Warranty  |  |  |
| Supplied Accessories               | User manual and power cord                                 |  |  |
|                                    |  |  |  |

<sup>\*</sup>For 230V input, order model number 1550-220V.





## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Benchtop Power Supplies category:

Click to view products by B&K Precision manufacturer:

Other Similar products are found below:

NL200 PR20 ZUPNC403 ZUP/W ZUPNC402 TL89F2 TL89K1 TL89T1 1332A-NIST ACC-GENH/RM CPX200DP AX-3003P AX-6003P AX-8450A TPM-3003 HMP2020 HMP2030 HMP4040 1350 UT804 1410 XLNRC 1513 1514 1550 1651A 1665 1666 1667
1693 1694 1698 1739 1788 TPM-3005 9174B GDM-8245 GDM-8255A GDM-8341 PSP-603 PSW 160-7.2 QL355P SII HCS-3400-USB MX180T MX180TP 382276 1403 RK153 ENP-120-48 ENP-120-24