



## Technical sheet

No. **11FA11D**

Issue  
**V01.0**

**Product family:** Cable-ties - Nylon accessories  
**Item code:** N0901, N0902, N0903  
**Description:** ACCESSORIES FOR NYLON CABLE-TIES · 2-WAY CABLE TIE MOUNTS · UV RESISTANT

Image



### Specifications

**MATERIAL:** polyamide (PA 6.6) + adhesive  
**COLOR:** black  
**INSULATION SELF-EXTINGUISHING:** UL 94 V2  
**OPERATING TEMPERATURE:** from -40 °C to +85 °C  
**MINIMUM INSTALLATION TEMPERATURE:** -10 °C  
**CHEMICAL RESISTANCE:** good resistance to bases, oils, grease, chloride solvents. Limited resistance to acids. Not resistant to phenols.

Code	For cable ties with max width (mm)	Dimensions (mm)	Height (mm)	Fixing hole Ø (mm)	Fixing screw Ø (mm)	Type of mount	
N0901	3,6	19 x 19	5,4	3,3	3	adhesive	100/1500
N0902*	4,8	28 x 28	7	5,5	5	adhesive	100/1000
N0903*	4,8	28 x 28	5,8	5,5	5	screw	



\* file n° E 223175

**HALOGEN  
FREE**

**UV  
RESISTANT**

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Cable Tie Mounts](#) category:*

*Click to view products by [BM Group](#) manufacturer:*

Other Similar products are found below :

[3-350087-0](#) [CTB75X75BKA-C](#) [561-EZS375B40](#) [08443-0](#) [10035-0](#) [1689174-1](#) [10351-0](#) [10029-0](#) [08484-0](#) [08318-0](#) [PAM075NY-A-C](#)  
[BMB0901](#) [BMB0902](#) [BMB0903](#) [151-02258](#) [151-28459](#) [151-25619](#) [151-11310](#) [70685](#) [70681](#) [61724510](#) [64685](#) [70406](#) [64678](#) [64684](#) [70683](#)  
[70362](#) [64682](#) [64677](#) [64681](#) [70684](#) [70373](#) [70433](#) [70364](#) [64686](#) [95183](#) [17104](#) [64679](#) [70431](#) [06290](#) [10044](#) [151-01594](#) [151-01802](#) [151-](#)  
[02259](#) [151-11319](#) [151-11810](#) [151-11819](#) [151-30300](#) [151-30400](#) [10046-0](#)