




## Technical sheet

No. **11FA10A**

Issue  
**V01.0**

**Product family:** Cable-ties - Nylon cable-ties UV resistant  
**Item code:** N1890, N2690, N3690  
**Description:** NYLON CABLE TIES UV RESISTANT - IMPACT RESISTANT

### Image



### Specifications

**MATERIAL:** polyamide (PA 6.6) + carbon black  
**COLOR:** black  
**INSULATION SELF-EXTINGUISHING:** UL 94 V2  
**OPERATING TEMPERATURE:** from -40 °C to +85 °C  
**MINIMUM INSTALLATION TEMPERATURE:** -10 °C  
**CHEMICAL RESISTANCE:** good resistance to bases, oils, grease, chloride solvents. Limited resistance to acids. Not resistant to phenols.  
**ACCORDING TO STD.:** EN 62275:2015-02  
**CLASSIFICATION:** type 1 (EN)  
**ASSEMBLY:** open the package just before use

Code	Width (mm)	Length (mm)	Max bundle Ø (mm)	Min bundle Ø (mm)	Tensile minimum resistance (N)	
N1890	9	180	40	20	400	100/1500
N2690	9	265	62	20	540	100/1400
N3690	9	360	93	20	540	100/500



**HALOGEN  
FREE**

**UV  
RESISTANT**

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Cable Ties](#) category:*

*Click to view products by [BM Group](#) manufacturer:*

Other Similar products are found below :

[65034-C](#) [65037-C](#) [770-1751-10](#) [20093-0](#) [SF600-120X](#) [SJ3518FR-1x50](#) [SJ3526N BLACK 58" X 50YD](#) [SJ3571](#) [SJ-3571-1"x50yd-Black](#) [34-455-C](#) [TYZ528M](#) [34-463-C](#) [URT20S-M](#) [06226](#) [08600-0](#) [08913-0](#) [08376-0](#) [10036-0](#) [10037-0](#) [10325-0](#) [10362-0](#) [561-EZ250](#) [SJ3519FR](#) [BLACK 1X50](#) [SJ3527N-Beige-2"x50yd](#) [SJ3527N-LOOP-BLACK-1](#) [SJ3572-2"x50yd-Black](#) [CF5625-000](#) [65004-C](#) [65005-C](#) [65036-C](#) [157-00039](#) [770-1708](#) [770-1753-10](#) [65035-C](#) [770-1752](#) [08386-0](#) [10431-0](#) [10620-0](#) [10345-0](#) [08416-0](#) [08384-0](#) [08401-0](#) [08664-0](#) [10425-0](#) [08470-0](#) [13120B](#) [561-EZ1750](#) [08471-0](#) [10001-0](#) [10327-0](#)