



- 一. 电气性能:
  - 1-1. 额定电流: 3A AC DC.
  - 1-2. 接触电阻:  $\leq 20m\Omega$
  - 1-3. 绝缘电阻:  $\geq 1000M\Omega$
  - 1-4. 耐压: 550V AC/Minute
- 二. 物理特性:
  - 2-1. 操作温度:  $-55^{\circ}C \sim 105^{\circ}C$
  - 2-2. 焊接温度:  $+220^{\circ}C$ , 10s max
- 三. 材质:
  - 3-1. 塑胶: PBT (Black) UL94V-0
  - 3-2. 插针: Brass/Gold plated

| Pin | A      | B     |
|-----|--------|-------|
| 1   | 2.54   | 0.00  |
| 2   | 5.08   | 2.54  |
| 3   | 7.62   | 5.08  |
| 4   | 10.16  | 7.62  |
| 5   | 12.70  | 10.16 |
| 6   | 15.24  | 12.70 |
| 7   | 17.78  | 15.24 |
| 8   | 20.32  | 17.78 |
| 9   | 22.86  | 20.32 |
| 10  | 25.40  | 22.86 |
| 11  | 27.94  | 25.40 |
| 12  | 30.48  | 27.94 |
| 13  | 33.02  | 30.48 |
| 14  | 35.56  | 33.02 |
| 15  | 38.10  | 35.56 |
| 16  | 40.64  | 38.10 |
| 17  | 43.18  | 40.64 |
| 18  | 45.72  | 43.18 |
| 19  | 48.26  | 45.72 |
| 20  | 50.80  | 48.26 |
| 21  | 53.34  | 50.80 |
| 22  | 55.88  | 53.34 |
| 23  | 58.42  | 55.88 |
| 24  | 60.96  | 58.42 |
| 25  | 63.50  | 60.96 |
| 26  | 66.04  | 63.50 |
| 27  | 68.58  | 66.04 |
| 28  | 71.12  | 68.58 |
| 29  | 73.66  | 71.12 |
| 30  | 76.20  | 73.66 |
| 31  | 78.74  | 76.20 |
| 32  | 81.28  | 78.74 |
| 33  | 83.82  | 81.28 |
| 34  | 86.36  | 83.82 |
| 35  | 88.90  | 86.36 |
| 36  | 91.44  | 88.90 |
| 37  | 93.98  | 91.44 |
| 38  | 96.52  | 93.98 |
| 39  | 99.06  | 96.52 |
| 40  | 101.60 | 99.06 |

P.C.B Layout

博穆电子

|       |                 |       |      |                        |     |
|-------|-----------------|-------|------|------------------------|-----|
| 图名:   | PZ2.54-1xNAW-ZW |       | 图号:  | XXXXXXXXXXXXXXXXXXXXXX |     |
|       | XX.             | ±0.40 |      | XX.                    | ±2° |
| 未标注公差 | X.              | ±0.30 | .XX° | ±1°                    |     |
|       | .XX             | ±0.20 |      |                        |     |
|       |                 | ±0.15 |      |                        |     |
| 绘制:   | 韩金锋             |       | 单位:  | MM                     |     |
| 签发:   |                 |       | 比例:  | 1:1                    |     |
| 审核:   |                 |       | 视图:  |                        |     |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Boom](#) manufacturer:*

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [0009485154](#) [009176003701906](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#)  
[63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#) [65817-010LF](#)  
[65817-015LF](#) [66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#)  
[70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [FCN-367T-T012/H](#) [80.063.4001.1](#)  
[800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-014-20-](#)  
[001000](#)