



P. C. B Layout

一. 电气性能:

- 1-1. 额定电流: 3A AC DC.
- 1-2. 接触电阻:  $\leq 20m\Omega$
- 1-3. 绝缘电阻:  $\geq 1000M\Omega$
- 1-4. 耐压: 550V AC/Minute

二. 物理特性:

- 2-1. 操作温度:  $-55^{\circ}C \sim 105^{\circ}C$
- 2-2. 焊接温度:  $+220^{\circ}C$ , 10s max

三. 材质:

- 3-1. 塑胶: PBT (Black) UL94V-0
- 3-2. 插针: Brass/Gold plated

| PIN | A      | B     |
|-----|--------|-------|
| 1   | 2.54   | 0.00  |
| 2   | 5.08   | 2.54  |
| 3   | 7.62   | 5.08  |
| 4   | 10.16  | 7.62  |
| 5   | 12.70  | 10.16 |
| 6   | 15.24  | 12.70 |
| 7   | 17.78  | 15.24 |
| 8   | 20.32  | 17.78 |
| 9   | 22.86  | 20.32 |
| 10  | 25.40  | 22.86 |
| 11  | 27.94  | 25.40 |
| 12  | 30.48  | 27.94 |
| 13  | 33.02  | 30.48 |
| 14  | 35.56  | 33.02 |
| 15  | 38.10  | 35.56 |
| 16  | 40.64  | 38.10 |
| 17  | 43.18  | 40.64 |
| 18  | 45.72  | 43.18 |
| 19  | 48.26  | 45.72 |
| 20  | 50.80  | 48.26 |
| 21  | 53.34  | 50.80 |
| 22  | 55.88  | 53.34 |
| 23  | 58.42  | 55.88 |
| 24  | 60.96  | 58.42 |
| 25  | 63.50  | 60.96 |
| 26  | 66.04  | 63.50 |
| 27  | 68.58  | 66.04 |
| 28  | 71.12  | 68.58 |
| 29  | 73.66  | 71.12 |
| 30  | 76.20  | 73.66 |
| 31  | 78.74  | 76.20 |
| 32  | 81.28  | 78.74 |
| 33  | 83.82  | 81.28 |
| 34  | 86.36  | 83.82 |
| 35  | 88.90  | 86.36 |
| 36  | 91.44  | 88.90 |
| 37  | 93.98  | 91.44 |
| 38  | 96.52  | 93.98 |
| 39  | 99.06  | 96.52 |
| 40  | 101.60 | 99.06 |

|     |                              |       |      |       |       |      |     |     |     |
|-----|------------------------------|-------|------|-------|-------|------|-----|-----|-----|
| 图名: | PZ2. 54-1xNAW-FW             |       |      | 未标注公差 |       | 绘制:  | 韩金锋 | 单位: | MM  |
|     | XX.                          | ±0.40 | XX.° | ±2°   |       |      |     |     |     |
| 图号: | XXXXXXXXXXXXXXXXXXXXXXXXXXXX |       |      | X.    | ±0.30 | XX.° | ±1° | 签发: |     |
|     | XX                           | ±0.20 |      |       |       |      |     |     |     |
|     |                              |       |      | .XX   | ±0.15 |      | 审核: |     | 视图: |
|     |                              |       |      |       |       |      |     |     |     |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Boom](#) manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)