





A	1	2	3	4
				产品编号
				HAY420A
				产品名称
				5557-nA/nAW

5557-NA



5557-NAW



Dimensional & Ordering Information

poles	2-24 poles
Pitch between ploes	4.20mm
Rated Voltage	300V AC,DC
Rated current	9.0A
Withstand Voltage	1500V.AC/minute
Insulation Resistance	≥1000MΩ
Temperaure Range	-25℃~+85℃
Applicable Wire	AWG#28~#20

24	HAA300A-24A	46.20	51.80
22	HAA420A-22A	42.00	47.60
20	HAA420A-20A	37.80	43.40
18	HAA420A-18A	33.60	39.20
16	HAA420A-16A	29.40	35.00
14	HAA420A-14A	25.20	30.80
12	HAA420A-12A	21.00	26.60
10	HAA420A-10A	16.80	22.40
8	HAA420A-8A	12.30	18.20
6	HAA420A-6A	8.40	14.00
4	HAA420A-4A	4.20	9.80
2	HAA420A-2A	—	5.60
Circuits	180°	A	B
	Part No.	Dimension(mm)	

F	ECN NO.	UNIT	TOLERANCE	PROJECTION	DRAWING	CHECK	APPROVAL
	NEW DRAWING	mm	.*** ±0.08 .** ±0.15 .* ±0.25		张建斌	程海洋	周顺招

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Boom](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)