



Specification

Power Pins: 1AMP
 Dielectric Withstanding Voltage:
 AC 1000V/60 sec.r.m.s
 Insulation Resistance:
 1000M Min at DC500V
 Contact Resistance: 20m Max
 Durability: 100gf cycles Min
 Terminal Retention Force:
 2.27kg fper contact Min

Material

Contacts: Brass
 Insulator: P.B.T UL 94V-0 Rate
 Planted: Gold over
 Operating Temperature:
 -40°C to 105°C

未注公差 (TOLERANCE)		绘图 (DRAWN)	change	单位(SCALE)	mm	料号 (PART NO.)	
X	±2°	X		投影(PROJECT)	第一角投影	料号(DRAW NO.)	
X	±1°	X	校对 (CHECKED)	比例(ACALE)	5:1	品名	Female Header
.XX	±0.5°	.XX	核准 (APPROVED)	版本(EDITION)	2009-03-18	(NAME)	2.54mm
.XXX		.XXX		日期 (DATE)			
						175-9F04V021-E	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Boom](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)