



Number	A	B	Dimension(mm)	Number	A	B	Dimension(mm)
2*2P	2.54	5.28	2*22P	53.34	56.08	56.08	53.54
2*3P	5.08	7.82	2*23P	55.88	58.62	58.62	56.16
2*4P	7.62	10.36	2*24P	58.42	61.16	61.16	63.70
2*5P	10.16	12.90	2*25P	60.96	63.70	63.70	66.24
2*6P	12.70	15.44	2*26P	63.50	66.24	66.24	68.78
2*7P	15.24	17.98	2*27P	66.04	68.78	68.78	71.32
2*8P	17.78	20.56	2*28P	68.58	71.32	71.32	73.86
2*9P	20.32	23.06	2*29P	71.12	73.86	73.86	76.40
2*10P	22.86	25.60	2*30P	73.66	76.40	76.40	78.94
2*11P	25.40	28.14	2*31P	76.20	78.94	78.94	81.48
2*12P	27.94	30.68	2*32P	78.74	81.48	81.48	84.02
2*13P	30.48	33.22	2*33P	81.28	84.02	84.02	86.56
2*14P	33.02	35.76	2*34P	83.82	86.56	86.56	89.10
2*15P	35.56	38.30	2*35P	86.36	89.10	89.10	91.64
2*16P	38.10	40.84	2*36P	88.90	91.64	91.64	94.18
2*17P	40.64	43.38	2*37P	91.44	94.18	94.18	96.72
2*18P	43.18	45.92	2*38P	93.98	96.72	96.72	99.26
2*19P	45.72	48.46	2*39P	96.52	99.26	99.26	101.80
2*20P	48.26	51.00	2*40P	99.06			

MATERIAL
 Insulator: PA6T+30%G.F(UL94V-0)
 Contact Plating: Phosphor Bronze
 Contact Plating: Gold over 50u" Nickel
 Color : Black
 Plating : 1.0u" Au

SPECIFICATION
 Current Rate : 3Amp
 Operation Temperature: -40°C to +105°C
 Contact Resistance: 20mΩ MAX.at DC 1A
 Insulation Resistance: 1000MΩ MIN.at DC 500V
 Dielectric Strength: AC 500V Per minute

SCALE: 1:1	SIZE: M4	版本	B/0	日期	2010-9-9	核 准
UNIT: MM	制图	曹忠燕	审核			
X:±0.25 X:±0.05 X:±0.01	X:±0.05 X:±0.01	客户册号	F792101314101		核 准	
X:±0.15	品号/规格	PH2.54*8.5 2*40P SMT				

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Boom](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)