



1) Tapered thread end max. 4P
2) Trilobular cross-section

BN 84402

Hexalobular (6 Lobe) socket pan head thread forming screws

with uncontinuous slot, metric thread

Steel case-hardened 450-560 HV

zinc plated blue, added lubricant



ISO 4042

Quenched and tempered fasteners ≥ 360 HV and tempered case-hardened fasteners with electroplated coatings: Susceptible to hydrogen embrittlement!
Further notice to residual risks can be found in the introduction section.

[3D Cadenas](#)

Article#	d ₁	d ₂ max.	k max.	n min.		t max.	L
8280495	M2,5	5	2,1	0,66	X8	1,13	4
8280282							6
8280290							8
8280304							10
8280312	M3	5,6	2,4	0,86	x10	1,26	6
8280320							8
8280339							10
8280347							12
8280355							16
8280363	M4	8	3,1	1,26	x20	1,6	6
8280371							8
8280398							10
8280401							12
8280428							16
8280436	M5	9,5	3,7	1,26	x25	1,9	10
8280444							12
8280452							16
8280460	M6	12	4,6	1,66	x30	2,3	10
8280479							12
8280487							16

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Screws & Fasteners](#) category:

Click to view products by [Bossard](#) manufacturer:

Other Similar products are found below :

[5721-1440-1/4-SS](#) [0098.0094](#) [0098.9206](#) [59781-6](#) [0098.9212](#) [6292-1](#) [690432-1](#) [699161-000](#) [700989](#) [7230-3](#) [72609-02](#) [CAPTIVE JACK](#)
[SCREW](#) [73542-02](#) [CAPTIVE SHORT THUMBSCREW](#) [745564-1](#) [7680](#) [809704-1](#) [8700](#) [8860220](#) [9521](#) [992763-3](#) [1-18024-0](#) [A168P1](#) [1-](#)
[24921-1](#) [125416-1](#) [1301810313](#) [1-306131-6](#) [1301830042](#) [1458](#) [1-59781-3](#) [18029-4](#) [NBX-10953](#) [NUT-16-3P-HEX-NICKEL](#) [20993.45098](#)
[21004-1](#) [21009-4](#) [21014-5](#) [21021-2](#) [CA24037A01](#) [22987-4](#) [240632-1](#) [240632-2](#) [89506-9801](#) [2504](#) [9031](#) [9-1393249-2](#) [2.5NZPNBU](#) [26-](#)
[0048PP](#) [27210-1](#) [27210-8](#) [9318](#) [9520](#)