


### »Features

- Low reverse leakage
- High forward surge capability
- High current capability
- High reliability
- High surge current capability
- Epitaxial construction



**SMB(DO-214AA)**

### »General Description

- Case: SMB molded plastic
- Polarity: Color band denotes cathode
- Epoxy: UL 94V-0 rate flame retardant
- Lead: Pure tin plated, lead free
- High temperature soldering guaranteed:260°C/10seconds


### » Maximum Ratings and Characteristics @ TA = 25°C unless otherwise noted

Parameter	SYMBOLS	ES3A	ES3B	ES3D	ES3G	ES3J	ES3K	ES3M	UNIT
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	$V_{RMS}$	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	$V_{DC}$	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current	$I_{(AV)}$	3.0							A
Non-repetitive peak forward surge current 8.3 ms singlehalf sine-wave	$I_{FSM}$	80					60		A
Maximum forward voltage @ $I_F=3.0A$	$V_F$	0.95		1.25	1.7	3.2		V	
Maximum reverse current @VDC	$I_R$	5.0							μA
	$T_A=125^{\circ}C$	100							
Maximum Reverse Recovery Time @ $I_F=0.5A, I_R=1.0A, I_{RR}=0.25A$	$t_{rr}$	35							nS
Type junction capacitance @VR=4.0V,f=1MHz	$C_J$	60							pF
Typical Thermal Resistance (Note 1)	$R_{\theta JA}$	85							°C/W
Operating Junction Temperature Range	$T_J$	-55 to +150							°C
Storage Temperature Rang	$T_{stg}$	-55 to +150							°C


Note: (1)Thermal resistance from junction to ambient, PCB mounted.

»Typical Performance Characteristics ((T<sub>J</sub> = 25 °C, unless otherwise noted))


TYPICAL FORWARD CHARACTERISTIC




FORWARD CURRENT DERATING CURVE




MAXIMUM NON REPETITIVE PEAK FORWARD SURGE CURRENT



TYPICAL REVERSE CHARACTERISTICS



»Package Information - SMB



SMB						
Dimension	Inches			Millimeters		
	MIN	NOM	MAX	MIN	NOM	MAX
A	0.134	0.144	0.155	3.4	3.67	3.94
B	0.205	0.213	0.22	5.21	5.4	5.59
C	0.075	0.079	0.083	1.9	2	2.1
D	0.169		0.185	4.3		4.7
F	0.006		0.012	0.152		0.305
G	-		0.008	-		0.203
H	0.085	0.091	0.096	2.15	2.3	2.45
L	0.03		0.06	0.76		1.52
X		0.11			2.8	
Y		0.079			2	
Z		0.079			2	

»Ordering information

Part Number	ES3A	ES3B	ES3D	ES3G	ES3J	ES3K	ES3M
Marking	ES3A	ES3B	ES3D	ES3G	ES3J	ES3K	ES3M
Base qty	3K	3K	3K	3K	3K	3K	3K

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Rectifiers](#) category:*

*Click to view products by [Bourne](#) manufacturer:*

Other Similar products are found below :

[70HFR40](#) [FR105 R0](#) [RL252-TP](#) [1N5397](#) [1N4005-TR](#) [1N4007-BP](#) [UFS120Je3/TR13](#) [20ETS12S](#) [RRE02VS6SGTR](#) [MS306](#) [A1N5404G-G](#)  
[CRF02\(T5L,TEMQ\)](#) [ACGRB207-HF](#) [CLH07\(TE16L,Q\)](#) [CLH03\(TE16L,Q\)](#) [1N5395-TP](#) [UES1302](#) [ACGRC307-HF](#) [ACEFC304-HF](#) [DZ-](#)  
[1380](#) [85HFR60](#) [40HFR60](#) [70HF120](#) [85HFR80](#) [SCF7500](#) [SM100](#) [ACGRA4001-HF](#) [SKN70/08](#) [NTE5819](#) [NTE5827](#) [NTE5828](#) [NTE5911](#)  
[NTE5915](#) [NTE6104](#) [NTE6163](#) [NTE6164](#) [NTE6165](#) [NTE6364](#) [TSD3G](#) [SET130312](#) [NRVUS110VT3G](#) [UES1106](#) [UES1306](#)  
[NRVUS240VT3G](#) [D5FE60-5063](#) [R4000GPS-TP](#) [D4015L56TP](#) [UES1306HR2](#) [FX20K120](#) [D20XB60-7101](#)