

Features

- Compact
- Lightweight
- Long life
- Infinite resolution
- Free shaft rotation
- AC or DC
- Shaft options available

Flexible wire leads

Economical RoHS compliant*

3048 Linear Motion Potentiometer

Product Dimensions


<u>13.5</u> (.53) 11.18 ± 0.38 9.14 (.44 ± .015) (.36) 25.4 4.6 ± 0.25 (1.00) (.18 ± .010) #2-56 UNC-2A THREADED SHAFT (STANDARD). SHAFT SHOWN IN 2 PLCS. ŧ _____ ÷ Ĥ RETRACTED 3.18 ± 0.38 2.67 ± 0.25 $\frac{2.34}{(.092)}$ DIA. (.125 ± .015) (.11 ± .010) 2 MOUNTING HOLES 7.60 FULL THREAD 5.60 #2 SCREW CLEARANCE (.220) (.299) 56.39 (2.22) 2.13 +0.02/-0.50 (.084 +.001/-.020) DIA. (THIS DIMENSION APPLIES BEYOND THE THREADED AREA 2.36 +.025/-.013 TO THE FULL DIAMETER. (.093 +.001/-.005) SEE THE #2-56 THREAD NOTE ABOVE.) 1.52 MAXIMUM FILLET ¥. (.060) 31.75 CHAMFER: (1.250) $45^{\circ} \times \frac{0.25}{(0.10)}$ 6.99 ± 0.25 3 ELECTRICALLY INSULATED LEADWIRES (.275 ± .010) 152.40 (6.00) MINIMUM LENGTH (28 AWG INSULATED CONDUCTOR) 8.28 ± 0.38 2.36 (.093) DIA (.326 ± .015) Ø RED 2 WIPER .010 EXCEPT WHERE NOTED TOLERANCES: ± YELLOW GREEN (0.25)1)--3 SHAFT EXTENDED MM DIMENSIONS: (INCHES) WIRING DIAGRAM

Specifications[†]

opecifications
Standard Electrical Travel
0.2, 0.3, 0.4, 0.5 in.
(5.08, 7.62, 10.16, 12.70 mm)
Standard Resistances
1K ohms to 50K ohms (± 20 %)
Independent Linearity± 5 %
Resolution Infinite
Power Rating @ 70 °C (158 °F)
Range 2, 3 0.12 watt
Range 4, 5 0.25 watt
Operating Temperature Range
55 °C to +125 °C
Temperature Coefficient 1000 PPM/°C
Insulation Resistance 50 megohms
@ 500 VDC
BacklashNegligible
Shaft Actuating Force 4 oz. max.
@ 70 °F
Life500,000 cycles
Shock 50 G for 7 msec
Vibration20 G, 10-2 kHz
Marking Manufacturer's trademark,
resistance code, wiring diagram,
date code, manufacturer's model
number and style

Specifications are typical. Contact factory for special requirements.

† Specifications applicable from 5 % to 95 % of electrical travel.



Resistance Value

Stainless steel shaft is available upon request.

Standard Resistance Table

Resistance (Ohms)	Resistance Code
1,000	102
2,500	252
5,000	502
10,000	103
20,000	203
50,000	503

WARNING Cancer and Reproductive Harm www.P65Warnings.ca.gov

*RoHS Directive 2015/863, Mar 31, 2015 and Annex. Specifications are subject to change without notice. Users should verify actual device performance in their specific applications. The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf

Legal Disclaimer Notice

This legal disclaimer applies to purchasers and users of Bourns[®] products manufactured by or on behalf of Bourns, Inc. and its affiliates (collectively, "Bourns").

Unless otherwise expressly indicated in writing, Bourns[®] products and data sheets relating thereto are subject to change without notice. Users should check for and obtain the latest relevant information and verify that such information is current and complete before placing orders for Bourns[®] products.

The characteristics and parameters of a Bourns[®] product set forth in its data sheet are based on laboratory conditions, and statements regarding the suitability of products for certain types of applications are based on Bourns' knowledge of typical requirements in generic applications. The characteristics and parameters of a Bourns[®] product in a user application may vary from the data sheet characteristics and parameters due to (i) the combination of the Bourns[®] product with other components in the user's application, or (ii) the environment of the user application itself. The characteristics and parameters of a Bourns[®] product time. Users should always verify the actual performance of the Bourns[®] product in their specific devices and applications, and make their own independent judgments regarding the amount of additional test margin to design into their device or application to compensate for differences between laboratory and real world conditions.

Unless Bourns has explicitly designated an individual Bourns[®] product as meeting the requirements of a particular industry standard (e.g., ISO/TS 16949) or a particular qualification (e.g., UL listed or recognized), Bourns is not responsible for any failure of an individual Bourns[®] product to meet the requirements of such industry standard or particular qualification. Users of Bourns[®] products are responsible for ensuring compliance with safety-related requirements and standards applicable to their devices or applications.

Bourns[®] products are not recommended, authorized or intended for use in nuclear, lifesaving, life-critical or life-sustaining applications, nor in any other applications where failure or malfunction may result in personal injury, death, or severe property or environmental damage. Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any Bourns[®] products in such unauthorized applications might not be safe and thus is at the user's sole risk. Life-critical applications include devices identified by the U.S. Food and Drug Administration as Class III devices and generally equivalent classifications outside of the United States.

Bourns expressly identifies those Bourns[®] standard products that are suitable for use in automotive applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns[®] standard products in an automotive application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk. If Bourns expressly identifies a sub-category of automotive application in the data sheet for its standard products (such as infotainment or lighting), such identification means that Bourns has reviewed its standard product and has determined that if such Bourns[®] standard product is considered for potential use in automotive applications, it should only be used in such sub-category of automotive applications. Any reference to Bourns[®] standard product in the data sheet as compliant with the AEC-Q standard or "automotive grade" does not by itself mean that Bourns has approved such product for use in an automotive application.

Bourns[®] standard products are not tested to comply with United States Federal Aviation Administration standards generally or any other generally equivalent governmental organization standard applicable to products designed or manufactured for use in aircraft or space applications. Bourns expressly identifies Bourns[®] standard products that are suitable for use in aircraft or space applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns[®] standard product in an aircraft or space application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk.

The use and level of testing applicable to Bourns[®] custom products shall be negotiated on a case-by-case basis by Bourns and the user for which such Bourns[®] custom products are specially designed. Absent a written agreement between Bourns and the user regarding the use and level of such testing, the above provisions applicable to Bourns[®] standard products shall also apply to such Bourns[®] custom products.

Users shall not sell, transfer, export or re-export any Bourns[®] products or technology for use in activities which involve the design, development, production, use or stockpiling of nuclear, chemical or biological weapons or missiles, nor shall they use Bourns[®] products or technology in any facility which engages in activities relating to such devices. The foregoing restrictions apply to all uses and applications that violate national or international prohibitions, including embargos or international regulations. Further, Bourns[®] products and Bourns technology and technical data may not under any circumstance be exported or re-exported to countries subject to international sanctions or embargoes. Bourns[®] products may not, without prior authorization from Bourns and/or the U.S. Government, be resold, transferred, or re-exported to any party not eligible to receive U.S. commodities, software, and technical data.

To the maximum extent permitted by applicable law, Bourns disclaims (i) any and all liability for special, punitive, consequential, incidental or indirect damages or lost revenues or lost profits, and (ii) any and all implied warranties, including implied warranties of fitness for particular purpose, non-infringement and merchantability.

For your convenience, copies of this Legal Disclaimer Notice with German, Spanish, Japanese, Traditional Chinese and Simplified Chinese bilingual versions are available at:

Web Page: <u>http://www.bourns.com/legal/disclaimers-terms-and-policies</u> PDF: http://www.bourns.com/docs/Legal/disclaimer.pdf

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Slide Potentiometers category:

Click to view products by Bourns manufacturer:

Other Similar products are found below :

 M22
 SS-4928
 RSA0K11A901L
 RA6020F-10-20D1-B50K
 RA4520F-10-20D1-B50K
 X22205CAAF
 RSA0N11B9A03
 448XC2103BDN

 K22208EAAG
 PS15-10PC1BR10K
 PT1A-50-FR-10K-M6
 ASE1D
 ASE1E
 ASE2D
 MFP130
 MFP1323
 MFP1424
 MFP161D

 MFP220
 MFP231P
 MFP261N
 MMP1010DRA1
 MFP120
 MFP 130 R
 MFP1323R
 MFP140-R
 MFP201N
 MFP 211-N

 MFP230
 MFP2323R
 CDE23N-60-B10K
 CDE23N-60-B1K
 CDE23N-60-B50K
 MMP1010D-RA
 MMP121
 MMP421-R
 MMS224

 1825160-1
 1825257-1
 1825259-2
 1825289-6
 1825261-2
 MMS124
 MMP134-R
 MMP 1010 D-1
 1825265-2