

Features

- RoHS compliant*
- 2/4 isolated resistors in an 0404/0804 size package
- E24 series from 10 ohms to 1 megohm
- Convex termination style
- Resistance tolerance ±5 %
- Suitable for all types of soldering processes

■ Paper tape on reel for automatic placement

Model CAY10 - Chip Resistor Array

Specifications

Requirement	Characteristics	Test Method
Short Time Overload	±2 %	Rated Voltage X 2.5, 5 seconds
Soldering Heat	±1 %	260 °C ±5 °C, 10 seconds ±1 second
Temperature Cycling (5)	±1 %	125 °C (30 minutes) - normal (15 minutes) -30 °C (30 minutes) - normal (15 minutes)
Moisture Load Life	±3 %	1000 hours
Load Life	±3 %	1000 hours

Characteristics

Characteristics	CAY10-xxxJ2	CAY10-xxxJ4	
Number of Elements (Isolated)	2	4	
Power Rating @ 70 °C per Resistor	0.0625 W	0.0625 W	
Package Power Rating @ 70 °C	0.125 W	0.250 W	
Resistance Tolerance	±5 %		
Resistance Range (E24) plus Zero-ohm Jumper	3 ohms - 1 megohm		
T.C.R.	3 ohms ~ 9.1 ohms: ±500 ppm/°C 10 ohms ~ 1 megohm: ±250 ppm/°C		
Max. Overload Voltage	50 V		
Max. Working Voltage	25 V		
Operating Temp. Range	-55 °C to +125 °C		
Rating Temperature	+70 °C		
Packaging	10,000 pieces per reel		

Protective Glass Overcoat Thick Film Resistive Element Termination High Purity Alumina Substrate

100 70 °C 125 °C

Typical Part Marking

Derating Curve

None on part. Label on reel will include part number.

Ambient Temp. (°C)

How To Order

CA Y 10 - 103 J 4 L
Chip Arrays —
Type
• Y = Convex
Model —
• 10 = 04 Package Width
Resistance Code —
• <10 ohms: "R" represents decimal point (example: 4R7 = 4.7 ohms)
≥10 ohms: First two digits are significant, third digit represents number of zeros to follow (example: 474 = 470k ohms
• 000 = Zero-ohm Jumper
Resistance Tolerance • J = ±5 %
Resistors —
• 2 = 2 Resistors
• 4 = 4 Resistors

 \bullet LF = Tin-plated (RoHS compliant)


Terminations -

For Standard Values Used in Capacitors, Inductors, and Resistors, click here.

Environmental Characteristics

Moisture Sensitivity Level1	
ESD Classification (HBM)N/A	L

Isolated Circuit





WARNING Cancer and Reproductive Harm - www.P65Warnings.ca.gov


*RoHS Directive 2015/863, Mar 31, 2015 and Annex. Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.


Model CAY10 - Chip Resistor Array


BOURNS®


Soldering Profile for RoHS Compliant Chip Resistors and Arrays



Product Dimensions









Land Pattern

CAY10-xxxJ4




CAY10-xxxJ2




Model CAY10 - Chip Resistor Array

BOURNS®

Packaging Dimensions





DIMENSIONS: $\frac{MM}{(INCHES)}$

BOURNS®

Asia-Pacific: Tel: +886-2 2562-4117 • Email: asiacus@bourns.com

EMEA: Tel: +36 88 885 877 • Email: eurocus@bourns.com

The Americas: Tel: +1-951 781-5500 • Email: americus@bourns.com

www.bourns.com

REV. 09/19

Legal Disclaimer Notice

BOURNS

This legal disclaimer applies to purchasers and users of Bourns® products manufactured by or on behalf of Bourns, Inc. and its affiliates (collectively, "Bourns").

Unless otherwise expressly indicated in writing, Bourns® products and data sheets relating thereto are subject to change without notice. Users should check for and obtain the latest relevant information and verify that such information is current and complete before placing orders for Bourns® products.

The characteristics and parameters of a Bourns® product set forth in its data sheet are based on laboratory conditions, and statements regarding the suitability of products for certain types of applications are based on Bourns' knowledge of typical requirements in generic applications. The characteristics and parameters of a Bourns® product in a user application may vary from the data sheet characteristics and parameters due to (i) the combination of the Bourns® product with other components in the user's application, or (ii) the environment of the user application itself. The characteristics and parameters of a Bourns® product also can and do vary in different applications and actual performance may vary over time. Users should always verify the actual performance of the Bourns® product in their specific devices and applications, and make their own independent judgments regarding the amount of additional test margin to design into their device or application to compensate for differences between laboratory and real world conditions.

Unless Bourns has explicitly designated an individual Bourns® product as meeting the requirements of a particular industry standard (e.g., ISO/TS 16949) or a particular qualification (e.g., UL listed or recognized), Bourns is not responsible for any failure of an individual Bourns® product to meet the requirements of such industry standard or particular qualification. Users of Bourns® products are responsible for ensuring compliance with safety-related requirements and standards applicable to their devices or applications.

Bourns® products are not recommended, authorized or intended for use in nuclear, lifesaving, life-critical or life-sustaining applications, nor in any other applications where failure or malfunction may result in personal injury, death, or severe property or environmental damage. Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any Bourns® products in such unauthorized applications might not be safe and thus is at the user's sole risk. Life-critical applications include devices identified by the U.S. Food and Drug Administration as Class III devices and generally equivalent classifications outside of the United States.

Bourns expressly identifies those Bourns® standard products that are suitable for use in automotive applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard products in an automotive application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk. If Bourns expressly identifies a sub-category of automotive application in the data sheet for its standard products (such as infotainment or lighting), such identification means that Bourns has reviewed its standard product and has determined that if such Bourns® standard product is considered for potential use in automotive applications, it should only be used in such sub-category of automotive applications. Any reference to Bourns® standard product in the data sheet as compliant with the AEC-Q standard or "automotive grade" does not by itself mean that Bourns has approved such product for use in an automotive application.

Bourns® standard products are not tested to comply with United States Federal Aviation Administration standards generally or any other generally equivalent governmental organization standard applicable to products designed or manufactured for use in aircraft or space applications. Bourns expressly identifies Bourns® standard products that are suitable for use in aircraft or space applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard product in an aircraft or space application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk.

The use and level of testing applicable to Bourns® custom products shall be negotiated on a case-by-case basis by Bourns and the user for which such Bourns® custom products are specially designed. Absent a written agreement between Bourns and the user regarding the use and level of such testing, the above provisions applicable to Bourns® standard products shall also apply to such Bourns® custom products.

Users shall not sell, transfer, export or re-export any Bourns® products or technology for use in activities which involve the design, development, production, use or stockpiling of nuclear, chemical or biological weapons or missiles, nor shall they use Bourns® products or technology in any facility which engages in activities relating to such devices. The foregoing restrictions apply to all uses and applications that violate national or international prohibitions, including embargos or international regulations. Further, Bourns® products and Bourns technology and technical data may not under any circumstance be exported or re-exported to countries subject to international sanctions or embargoes. Bourns® products may not, without prior authorization from Bourns and/or the U.S. Government, be resold, transferred, or re-exported to any party not eligible to receive U.S. commodities, software, and technical data.

To the maximum extent permitted by applicable law, Bourns disclaims (i) any and all liability for special, punitive, consequential, incidental or indirect damages or lost revenues or lost profits, and (ii) any and all implied warranties, including implied warranties of fitness for particular purpose, non-infringement and merchantability.

For your convenience, copies of this Legal Disclaimer Notice with German, Spanish, Japanese, Traditional Chinese and Simplified Chinese bilingual versions are available at:

Web Page: http://www.bourns.com/legal/disclaimers-terms-and-policies

PDF: http://www.bourns.com/docs/Legal/disclaimer.pdf

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for bourns manufacturer:

Other Similar products are found below:

PWR4412-2SDR0050F SRP1040-3R3M PWR4412-2SDR1000F SF-FP-LAB1 SF-SP-LAB1 PV36Z502C01B00 3386F-FE1-202LF CMF-RLC50-10-0 SM51295PEL PTF01-082T-103B2 CMF-SD35A-2 3547H-582-103A 4118R-D48-103/104 CMF-RD50-0 4306H-BR4-000LF CRF0805-FX-R009ELF PT25012L 1061-005 5900-153-RC CRM2512-JW-222ELF 6324 6346 6359 CW201212-LAB1 70F122AI-RC 74F396AP-RC 83A1D-B28-J10 PCW1J-B24-KAB502 PWR221T-30-1R00F PWR263S-20-20R0F H-1060 1250-1S-480 RJ26FW101 RJR24FX104R 2017-15-SMH-RPLF 2200HT-821-V-RC RT22C2X502 RT26C2X501 91C1A-D24-A10L 9230-76-RC SDE0805A-221K SDR0503-122JL SRP1238A-1R8M SRP1265A-R82M SRR0908-102YL SRU5028A-101Y SRU60-LAB1 PEC11R-4225F-N0024 PWR263S-20-27R0F 3057L-1-102