









# US-324

**brain**boxes

# USB 1 Port RS422/485 1MBaud

## "SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"

#### **Features**

- 1 x RS422/485
- USB 2.0
- 128 Byte TX and 256 Byte RX FIFOs
- Up to 921,600 Baud
- DB9 Connector 9 Pin Male
- Includes 0.25mm USB Extender cable
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

### Product



US-324: USB 1 Port RS422/485 1MBaud



### Description

USB to Serial adapter providing one RS422/485 serial port. Data transfer rates up to 921,600 baud rates and the 128 byte deep transmit and 256 byte receive FIFOS, coupled with 1Mbit line drivers deliver uncompromising performance on your laptop/PC. Drivers for Windows 32 bit and 64 bit Operating Systems including Windows XP, Server 2003, Vista, Server 2008, Windows 7 and Windows 8 with additional drivers for Raspberry Pi, Mac OS X and Linux.

USB to serial is the quick low cost way to connect your computer to a serial comms enabled device. Boost software gives industry leading functionality and compatibility.

These products do away with traditional issues with USB technology so you can buy with confidence!

With Brainboxes industry renowned Lifetime Warranty and Lifetime Support!

#### Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows 8 32 bit 64 bit Editions
- Windows 7 32 bit 64 bit Editions
- Windows Vista 32 bit 64 bit editions
- Windows XP 32 bit 64 bit editions

As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.



Code US-324




















## US-324- USB 1 Port RS422/485 1MBaud

### US-324: Full Specification

Port	Ports	1 x RS422/485
Pin 1   TXD-   Pin 2   TXD+   Pin 3   RTS-   Pin 4   RTS+   Pin 5   GND     Pin 6   RXD-   Pin 7   RXD+   Pin 8   CTS     Pin 9   CTS+	Connector	DB9 Connector - 9 Pin Male
	FIFO Size	256 Rx FIFO + 128 Tx FIFO
	Operating Distance	RS422/485 Standard 4000 ft : 1200 metres
	Cable	USB extender cable 0.25 metre 1ft
Port Settings	Baud Rate	921,600
921,600 >>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>	Data Bits	7 or 8
	Parity	Odd, Even, None, Mark or Space
	Stop Bits	1 or 2
	Flow Control	
	Tx/Rx Modes	Full Duplex, Half Duplex Autogating
Interface	OS Compatibility	Microsoft Windows 8 32 bit 64 bit Editions
USD E		Raspberry Pi
		Microsoft Windows 7 32 bit 64 bit Editions
		Windows Server 2008 32 bit 64 bit Editions
		Windows Vista 32 bit 64 bit Editions
	BUS	USB 2.0
Approvals	Other Approvals	AEO C-TPAT C-Tick
Compatible Windows 7		Microsoft Certified Gold Partner WEEE
		RoHS METL UL
	Microsoft Approvals	Windows 7 32 bit 64 bit Editions
		Windows Vista 32 bit 64 bit editions
		Windows XP 32 bit 64 bit editions
General	PCB Layers	4
GB AEOF 00031/11	Power Consumption	80mA @ 5V
	Product Weight	0.023 kg, 0.81 ounces
	Product Size	89x35x20 mm, 3.5x1.4x0.8 inches
Box Content	Packaging	Cable, Installation CD (inc manual, Microsoft signed drivers & Utilities)
	Device	USB 1 Port RS422/485 1MBaud USB extender cable 0.25 metre 1ft
Product Support	Warranty	Lifetime (online registration required)
	Support	Lifetime Web, Email & Phone Support from fully qualified, friendly staff who work in and alomgside our Product Development Team
Additional	OEM Option	Available for bulk buy OEM
	Made In	Manufacturerd in the UK by Brainboxes Winner 2005 European Electronics Industry Awards "Manufacturer of the Year"
	Customisable	Brainboxes operate a "Perfect Fit Custom Design" policy for volume users. More info: sales@brainboxes.com

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Interface Modules category:

Click to view products by Brainboxes manufacturer:

Other Similar products are found below:

8500-003 IFD8520 422CON ATX6022/14GP7 ATX6022/8 AX93221-24/48 OPT8AP-AE 60006-016 96RMKVM-19V1C-A 60016-011 60016-014 60006-008 60016-015 60011-075 HPCI-14S12U cBP-3208 cBP-3062A FAB205-6P5 ATX6022/6 60016-012 96RMKVM-17V1C-A PCE-DP10-00A1E MOS-1120Y-0201E 96RMLCD-17V1-A 96RMKVM-17V8C-A 60004-005 60016-017 60006-019 60006-009 60016-035 60016-034 60016-031 60016-030 60016-026 60016-025 60016-024 60016-021 60016-018 60016-007 60016-006 60016-005 60016-004 60007-002 60006-018 60006-010 AXX10GBTWLHW3 382-BBEH 555-BDCL K6CMISZBI52 426451401-3