

## 1200V 18A N-Channel SiC MOSFET

### Features

- Low On-Resistance
- Low Capacitance
- Avalanche Ruggedness
- Halogen Free, RoHS Compliant


### BENEFITS

- Higher System Efficiency
- Parallel Device Convenience
- High Temperature Application
- High Frequency Operation

### Application

- Switch Mode Power Supply (SMPS)
- Power Factor Correction (PFC)
- Uninterruptible Power Supply (UPS)
- EV Charging station & Motor Drives
- Solar/ Wind Renewable Energy
- Power Inverters & DC/DC Converters

### SYMBOL



**TO-247**

### ASSEMBLY MESSAGE

Product Name	Package	Packaging
BXW18M1K2H	TO-247	Tube


### ABSOLUTE MAXIMUM RATINGS (T<sub>C</sub>=25°C unless otherwise noted)

Parameter		Symbol	Rating	Unit
			TO-247	
Drain-Source Voltage		V <sub>DSS</sub>	1200	V
Continuous Drain Current	T <sub>C</sub> = 25°C, V <sub>GS</sub> =20V	I <sub>D</sub>	18	A
Single Pulse Avalanche Energy	L=10mH	E <sub>AS</sub>	145	mJ
	L=10mH	I <sub>AS</sub>	5.4	A
Pulsed Drain Current		I <sub>DM</sub>	72	A
Recommend Gate Source Voltage(Static)		V <sub>GS,op</sub>	-3/+20	V
Maximum Gate Source Voltage(AC (f > 1Hz))		V <sub>GS,max</sub>	-5/+25	V
Power Dissipation	T <sub>C</sub> =25°C	P <sub>D</sub>	96.9	W
Soldering Temperature		T <sub>L</sub>	260	°C
Operating Junction and Storage Temperature Range		T <sub>J</sub> ,T <sub>STG</sub>	150,-55~150	°C
Thermal Resistance, Junction to Case		R <sub>θJC</sub>	1.29	°C / W


**ELECTRICAL CHARACTERISTICS** ( $T_J=25^{\circ}\text{C}$ , unless otherwise Noted)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
<b>OFF CHARACTERISTICS</b>						
Drain-Source Breakdown Voltage	$BV_{DSS}$	$V_{GS}=0V, I_D=250\mu A$	1200			V
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=1200V, V_{GS}=0V$			10	$\mu A$
Gate-Body Leakage Current, Forward	$I_{GSS}$	$V_{GS}=20V, V_{DS}=0V$			250	nA
<b>ON CHARACTERISTICS</b>						
Gate Threshold Voltage	$V_{GS(TH)}$	$V_{DS}=V_{GS}, I_D=5mA$	2.0		4.5	V
Drain-Source On-State Resistance	$R_{DS(ON)}$	$V_{GS}=20V, I_D=9A$		190	228	m $\Omega$
		$V_{GS}=18V, I_D=9A$		215	258	
		$V_{GS}=15V, I_D=9A$		295	355	
		$V_{GS}=20V, I_D=9A, T_J=150^{\circ}\text{C}$		345		
<b>DYNAMIC PARAMETERS</b>						
Input Capacitance	$C_{ISS}$	$V_{DS}=1000V, V_{GS}=0V,$ $f=1MHz, V_{AC}=25mV$		550		pF
Output Capacitance	$C_{OSS}$			39		pF
Reverse Transfer Capacitance	$C_{RSS}$			7		pF
<b>SWITCHING PARAMETERS</b>						
Total Gate Charge(Note2)	$Q_G$	$V_{DD}=800V,$ $V_{GS}=-3/+20V,$ $I_D=18A$		44		nC
Gate Source Charge	$Q_{GS}$			4		nC
Gate Drain Charge	$Q_{GD}$			19		nC
Gate plateau voltage	$V_{pl}$			5		V
Turn-ON Delay Time	$t_{D(ON)}$	$V_{DS}=400V, I_D=18A,$ $V_{GS}=-3/+20V, R_G=25\Omega$		38		ns
Turn-ON Rise Time	$t_R$			68		ns
Turn-OFF Delay Time	$t_{D(OFF)}$			70		ns
Turn-OFF Fall-Time	$t_F$			51		ns
Internal Gate Resistance	$R_{G(int.)}$	$f=1MHz, V_{AC}=25mV$		13		$\Omega$
<b>SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS</b>						
Drain-Source Diode Forward Voltage	$V_{SD}$	$I_S=9A, V_{GS}=-3V$		6.3		V
Continuous Diode Forward Current	$I_S$	$V_{GS}=-3V$		18		A
Reverse Recovery Time	$t_{rr}$	$V_{GS}=-3/+20V, I_F=18A,$ $V_{DS}=400V,$ $di/dt=250A/\mu s$		30		ns
Reverse Recovery Charge	$Q_{rr}$			55		nC
Peak Reverse Recovery Current	$I_{rrm}$			3.1		A


**TYPICAL CHARACTERISTICS**




**Figure1. Typical Output Characteristics**




**Figure2. Typical Transfer Characteristics**




**Figure3. On-Resistance versus Drain Current**



**Figure4. On-Resistance versus Temperature for Various Gate Voltage**




**Figure5. Typical Capacitance versus VDS**




**Figure6. Typical Gate Charge versus VGS**


**TYPICAL CHARACTERISTICS(Cont.)**




**Figure7. Maximum Power Dissipation Derating versus Case Temperature**



**Figure8. On-Resistance Variation with Temperature**



**Figure9. Maximum Safe Operating Area**



**Figure10. Maximum Continuous Drain Current versus Case Temperature**

**Revision history****Document revision history**

<b>Date</b>	<b>Revision</b>	<b>Changes</b>
7-Mar-2022	1.0	First release

**Disclaimers:**

Bridgelux WuXi has made reasonable commercial efforts to ensure that the information given in this data sheet is correct. However, it must clearly be understood that such information is for guidance only and does not constitute any representation or form part of any offer or contract.

For documents and material available from this data sheet, Bridgelux WuXi does not warrant or assume any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, product, technology or process disclosed hereunder.

Bridgelux WuXi reserves the rights to at its own discretion to make any changes or improvements to this data sheet. Unless said data sheet is incorporated into the formal contract, any customer should not rely on the information as any specification or product parameters duly committed by Bridgelux WuXi. Customers are hereby advised to verify that the information contained herein is current and complete before the entering of any contract or acknowledgement of any purchase order. Accordingly, all products specified hereunder shall be sold subject to Bridgelux WuXi's terms and conditions supplied at the time of order acknowledgement. Except where agreed upon by contractual agreement, testing of all parameters of each product is not necessarily performed.

Bridgelux WuXi does not warrant or convey any license either expressed or implied under its patent rights, nor the rights of others. Reproduction of information contained herein shall be only permissible if such reproduction is without any modification or alteration. Reproduction of this information with any alteration is an unfair and deceptive business practice. Bridgelux WuXi is not responsible or liable for such altered documentation.

Resale of Bridgelux WuXi's products with statements different from or beyond the parameters stated by Bridgelux WuXi for that product or service voids all express or implied warranties for the associated Bridgelux WuXi's product or service and is unfair and deceptive business practice. Bridgelux WuXi is not responsible or liable for any such statements.

Bridgelux WuXi's products are not authorized for use as critical components in life support devices or systems without the express written approval of Bridgelux WuXi. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [MOSFET](#) category:*

*Click to view products by [Bridgelux](#) manufacturer:*

Other Similar products are found below :

[614233C](#) [648584F](#) [FDPF9N50NZ](#) [IRFD120](#) [JANTX2N5237](#) [2N7000](#) [FCA20N60\\_F109](#) [FDZ595PZ](#) [2SK2545\(Q,T\)](#) [405094E](#) [423220D](#)  
[TPCC8103,L1Q\(CM](#) [MIC4420CM-TR](#) [VN1206L](#) [614234A](#) [715780A](#) [NTNS3166NZT5G](#) [SSM6J414TU,LF\(T](#) [751625C](#) [IPP110N20N3GXX](#)  
[IPS70R2K0CEAKMA1](#) [DMN3404LQ-7](#) [NTE6400](#) [2SK2614\(TE16L1,Q\)](#) [DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [ECH8691-TL-W](#)  
[FCAB21350L1](#) [P85W28HP2F-7071](#) [DMN1053UCP4-7](#) [NTE221](#) [NTE2384](#) [NTE2903](#) [NTE2941](#) [NTE2945](#) [NTE2946](#) [NTE2960](#) [NTE2969](#)  
[NTE2976](#) [NTE455](#) [NTE6400A](#) [NTE2910](#) [NTE2916](#) [NTE2956](#) [NTE2911](#) [TK10A80W,S4X\(S](#) [SSM6P69NU,LF](#) [DMP22D4UFO-7B](#)  
[DMN1006UCA6-7](#) [DMN16M9UCA6-7](#)