

# ASMT-UWA1, ASMT-UWA2, ASMT-UWB1, ASMT-UWB2

## OneWhite Surface Mount PLCC-2 LED Indicator

### Description

The following cumulative test results have been obtained from testing performed at Broadcom in accordance with JEDEC.

Broadcom tests parts at the absolute maximum rated conditions recommended for the device. The actual performance you obtain from Broadcom<sup>®</sup> parts depends on the electrical and environmental characteristics of your application but will probably be better than performance outlined in the following table.

**Table 1: Environmental Tests and Other Tests**

Test Name	Reference	Test Conditions	Units Tested <sup>a</sup>	Units Failed <sup>b</sup>
Temperature Cycle	JESD22-A104	-40°C/100°C, 30 minutes dwell, 5 minute transfer, 100 cycles	2632	0
Low Temperature Operating Life	JESD22-A108	T <sub>A</sub> = -40°C, I <sub>F</sub> = 30 mA for 1000 hours	84	0
High Temperature Operating Life	JESD22-A108	T <sub>A</sub> = 55°C, I <sub>F</sub> = 30 mA for 1000 hours	280	0
Temperature Humidity Operating Life	JESD22-A101	T <sub>A</sub> = 60°C/90% RH, I <sub>F</sub> = 23 mA for 1000 hours	728	0
Room Temperature Operating Life	JESD22-A108	T <sub>A</sub> = 25°C, I <sub>F</sub> = 30 mA for 1000 hours	84	0
Temperature Humidity Storage Life	JESD22-A101	T <sub>A</sub> = 60°C/90% RH for 1000 hours	392	0
Low Temperature Storage	JESD22-A103	T <sub>A</sub> = -40°C for 1000 hours	84	0
High Temperature Storage	JESD22-A103	T <sub>A</sub> = 100°C for 1000 hours	84	0
Solderability	JESD22-B102	245°C for 5 seconds	60	0
Mechanical Shock	JESD22-B104	5 shocks each X1, X2, Y1, Y2, Z1, Z2, 2900G, 0.3-ms pulse	30	0
Vibration	JESD22-B103	4 cycles, 4 minutes each X, Y, and Z at 0.06 in. at 20 Hz to 100 Hz, 50g at 100 Hz to 2000 Hz	30	0
Pulse Test	JESD22-A108	T <sub>A</sub> = 25°C, Frequency = 1 kHz, 1000 hours, Peak current = 100 mA, Duty factor = 10%	84	0

a. Each reliability sample was subjected to pretreatment of moisture soak followed by reflow accordance to JEDEC standard before stress under reliability test listed in the previous table.

b. A failure is any LED that is open, shorted, or fails to emit light (except the solderability test).

## Disclaimer

Broadcom's products and software are not specifically designed, manufactured, or authorized for sale as parts, components, or assemblies for the planning, construction, maintenance, or direct operation of a nuclear facility or for use in medical devices or applications. The customer is solely responsible, and waives all rights to make claims against Broadcom or its suppliers, for all loss, damage, expense, or liability in connection with such use.

Broadcom, the pulse logo, Connecting everything, Avago Technologies, Avago, and the A logo are among the trademarks of Broadcom and/or its affiliates in the United States, certain other countries, and/or the EU.

Copyright © 2017–2020 Broadcom. All Rights Reserved.

The term “Broadcom” refers to Broadcom Inc. and/or its subsidiaries. For more information, please visit [www.broadcom.com](http://www.broadcom.com).

Broadcom reserves the right to make changes without further notice to any products or data herein to improve reliability, function, or design. Information furnished by Broadcom is believed to be accurate and reliable. However, Broadcom does not assume any liability arising out of the application or use of this information, nor the application or use of any product or circuit described herein, neither does it convey any license under its patent rights nor the rights of others.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Standard LEDs - SMD category](#):*

*Click to view products by [Broadcom manufacturer](#):*

Other Similar products are found below :

[LTST-C19GD2WT](#) [LTST-N683GBEW](#) [LTW-170ZDC](#) [LTW-M140SZS40](#) [598-8110-100F](#) [598-8170-100F](#) [598-8610-202F](#) [67-22VRVGC/TR8](#) [AAAF5060QBFSEEZGS](#) [HLMP-6305-L0011](#) [ALMD-LB36-SV002](#) [APT1608QGW](#) [15-21UYC/S530-A3/TR8](#) [EASV1803BA0](#) [LG M67K-H1J2-24-0-2-R18-Z](#) [LS A676-P2S1-1](#) [SML-512VWT86A](#) [SML-LX0606SISUGC/A](#) [SML-LXL1307SRC-TR](#) [SML-LXR851SIUPGUBC](#) [LT1ED53A](#) [FAT801-S](#) [AM27ZGC03](#) [APB3025SGNC](#) [APFA3010SURKCGKQBDC](#) [APHK1608VGCA](#) [APT2012QGW](#) [CLX6D-FKB-CN1R1H1BB7D3D3](#) [LTST-C250KGKT](#) [LTW-020ZDCG](#) [LTW-21TS5](#) [LTW-220DS5](#) [JANTXM19500/521-02](#) [UYGT801-S](#) [42-21UYC/S530-A3/TR8](#) [LO T67F-V1AB-24-1](#) [YGFR411-H](#) [SML-LX0402IC-TR](#) [CMDA20AYAA7D1S](#) [CMDA16AYDR7A1X](#) [339-1SURYGW/S530-A2](#) [598-8040-100F](#) [598-8070-100F](#) [598-8140-100F](#) [598-8610-200F](#) [EAPL3527GA5](#) [67-11/BHC-M1N2B8Y/2A0](#) [SML-LXL1209SYC/ATR](#) [EASV3020YGA0](#) [EAST16086YA5](#)