

# HDSP-C5x1/C5x3

## 0.52" Single Digit PCB Based LED Display



### Data Sheet

#### Description

This is 0.52" height single digit display. It utilizes GaAsP/ GaP Red, Orange, Yellow, Green and AlGaAs/GaAs Red chips. This device is halogenated.

All devices are categorized for luminous intensity. The orange, yellow and green devices are categorized for color. Use of similar device categories will yield a uniform display.



#### Features

- High reliability
- Excellent characters appearance
- Available in CA and CC
- RoHS Compliant
- Gray top surface with white diffused segments.

#### Ordering Information

| Red       | Green     | Yellow    | Orange    | AlGaAs Red | Description                        |
|-----------|-----------|-----------|-----------|------------|------------------------------------|
| HDSP-C5E1 | HDSP-C5G1 | HDSP-C5Y1 | HDSP-C5L1 | HDSP-C5A1  | Common Anode, Right Hand Decimal   |
| HDSP-C5E3 | HDSP-C5G3 | HDSP-C5Y3 | HDSP-C5L3 | HDSP-C5A3  | Common Cathode, Right Hand Decimal |


#### Package Dimensions



#### Notes:

1. All dimensions are in millimeter.
2. Unless otherwise stated, the tolerance is  $\pm 0.25\text{mm}$ .

## Circuit Diagram



### Absolute Maximum Ratings at $T_A = 25^\circ\text{C}$

| Parameter   | Symbol | Red/Yellow/<br>Orange | Green                     | AlGaAs Red | Units |
|---|--------|-----------------------|---------------------------|------------|-------|
| Power Dissipation per segment or Dot Point (DP)                             | $P_D$  | 57.5                  | 62.5                      | 50         | mW    |
| Continuous Forward Current per segment                                      | $I_F$  | 25                    | 25                        | 25         | mA    |
| Peak Forward Current per segment<br>(1/10 Duty Cycle, 0.1m sec pulse width) |        | 80                    | 80                        | 80         | mA    |
| Derating Linearly from 25°C per segment                                     |        | 0.33                  | 0.33                      | 0.33       | mA/°C |
| Reverse Voltage per segment or DP   | $V_R$  |                       | 5                         |            | V     |
| Operating Temperature   | $T_O$  |                       | -40 to 85                 |            | °C    |
| Storage Temperature   | $T_S$  |                       | -40 to 85                 |            | °C    |
| Wave solder Condition 1.6mm below body                                      |        |                       | 260°C peak for 5 secs max |            |       |

**Electrical / Optical Characteristic at  $T_A = 25^\circ\text{C}$** **Red**

| Parameter  | Symbol      | Min | Typ | Max | Units         | Test Conditions     |
|--|-------------|-----|-----|-----|---------------|---------------------|
| Average Luminous Intensity (Digit Average)             | $I_V$       | –   | 4.0 | –   | mcd           | $I_F = 10\text{mA}$ |
| Peak Wavelength  | $\lambda_p$ | –   | 640 | –   | nm            | $I_F = 20\text{mA}$ |
| Dominant Wavelength                                    | $\lambda_d$ | –   | 626 | –   | nm            | $I_F = 20\text{mA}$ |
| Forward Voltage per segment or DP                      | $V_F$       | –   | 2.0 | 2.3 | V             | $I_F = 20\text{mA}$ |
| Reverse Current  | $I_R$       | –   | –   | 100 | $\mu\text{A}$ | $V_R = 5\text{V}$   |
| Luminous Intensity Matching Ratio (Segment to Segment) | $I_{V-M}$   |     | 2:1 |     |               | $I_F = 10\text{mA}$ |

**Green**

| Parameter  | Symbol      | Min | Typ  | Max | Units         | Test Conditions     |
|--|-------------|-----|------|-----|---------------|---------------------|
| Average Luminous Intensity (Digit Average)             | $I_V$       | –   | 6.0  | –   | mcd           | $I_F = 10\text{mA}$ |
| Peak Wavelength  | $\lambda_p$ | –   | 565  | –   | nm            | $I_F = 20\text{mA}$ |
| Dominant Wavelength                                    | $\lambda_d$ | –   | 569  | –   | nm            | $I_F = 20\text{mA}$ |
| Forward Voltage per segment or DP                      | $V_F$       | –   | 2.25 | 2.5 | V             | $I_F = 20\text{mA}$ |
| Reverse Current  | $I_R$       | –   | –    | 100 | $\mu\text{A}$ | $V_R = 5\text{V}$   |
| Luminous Intensity Matching Ratio (Segment to Segment) | $I_{V-M}$   |     | 2:1  |     |               | $I_F = 10\text{mA}$ |

**Yellow**

| Parameter  | Symbol      | Min | Typ  | Max | Units         | Test Conditions     |
|--|-------------|-----|------|-----|---------------|---------------------|
| Average Luminous Intensity (Digit Average)             | $I_V$       | –   | 3.0  | –   | mcd           | $I_F = 10\text{mA}$ |
| Peak Wavelength  | $\lambda_p$ | –   | 587  | –   | nm            | $I_F = 20\text{mA}$ |
| Dominant Wavelength                                    | $\lambda_d$ | –   | 589  | –   | nm            | $I_F = 20\text{mA}$ |
| Forward Voltage per segment or DP                      | $V_F$       | –   | 2.15 | 2.3 | V             | $I_F = 20\text{mA}$ |
| Reverse Current  | $I_R$       | –   | –    | 100 | $\mu\text{A}$ | $V_R = 5\text{V}$   |
| Luminous Intensity Matching Ratio (Segment to Segment) | $I_{V-M}$   |     | 2:1  |     |               | $I_F = 10\text{mA}$ |

## Orange

| Parameter  | Symbol      | Min | Typ  | Max | Units         | Test Conditions     |
|--|-------------|-----|------|-----|---------------|---------------------|
| Average Luminous Intensity (Digit Average)             | $I_V$       | –   | 4.0  | –   | mcd           | $I_F = 10\text{mA}$ |
| Peak Wavelength  | $\lambda_p$ | –   | 610  | –   | nm            | $I_F = 20\text{mA}$ |
| Dominant Wavelength                                    | $\lambda_d$ | –   | 605  | –   | nm            | $I_F = 20\text{mA}$ |
| Forward Voltage per segment or DP                      | $V_F$       | –   | 2.15 | 2.3 | V             | $I_F = 20\text{mA}$ |
| Reverse Current  | $I_R$       | –   | –    | 100 | $\mu\text{A}$ | $V_R = 5\text{V}$   |
| Luminous Intensity Matching Ratio (Segment to Segment) | $I_{V-M}$   |     | 2:1  |     |               | $I_F = 10\text{mA}$ |

## AlGaAs Red

| Parameter  | Symbol      | Min | Typ  | Max | Units         | Test Conditions     |
|--|-------------|-----|------|-----|---------------|---------------------|
| Average Luminous Intensity (Digit Average)             | $I_V$       | –   | 16   | –   | mcd           | $I_F = 10\text{mA}$ |
| Peak Wavelength  | $\lambda_p$ | –   | 660  | –   | nm            | $I_F = 20\text{mA}$ |
| Dominant Wavelength                                    | $\lambda_d$ | –   | 643  | –   | nm            | $I_F = 20\text{mA}$ |
| Forward Voltage per segment or DP                      | $V_F$       | –   | 1.85 | 2.0 | V             | $I_F = 20\text{mA}$ |
| Reverse Current  | $I_R$       | –   | –    | 100 | $\mu\text{A}$ | $V_R = 5\text{V}$   |
| Luminous Intensity Matching Ratio (Segment to Segment) | $I_{V-M}$   |     | 2:1  |     |               | $I_F = 10\text{mA}$ |

## Red




Figure 1. Relative Luminous Intensity Vs Forward Current




Figure 2. Forward Voltage Vs Current




Figure 3. Relative Luminous Intensity Vs Wavelength

## Green




Figure 4. Relative Luminous Intensity Vs Forward Current




Figure 5. Forward Voltage Vs Current




Figure 6. Relative Luminous Intensity Vs Wavelength

## Yellow




Figure 7. Relative Luminous Intensity Vs Forward Current




Figure 8. Forward Voltage Vs Current




Figure 9. Relative Luminous Intensity Vs Wavelength

## Orange




Figure 10. Relative Luminous Intensity Vs Forward Current




Figure 11. Forward Voltage Vs Current




Figure 12. Relative Luminous Intensity Vs Wavelength



## AlGaAs Red




Figure 13. Relative Luminous Intensity Vs Forward Current




Figure 14. Forward Voltage Vs Current






Figure 15. Relative Luminous Intensity Vs Wavelength

### Packing Tube Specifications:

25 PCS PRODUCTS PER IC TUBE



Tube Front View



Tube Top View

### Reference

For further information on soldering LEDs, please refer to Avago Technologies Application Note 1027.

For product information and a complete list of distributors, please go to our web site: [www.avagotech.com](http://www.avagotech.com)

Avago, Avago Technologies, and the A logo are trademarks of Avago Technologies in the United States and other countries. Data subject to change. Copyright © 2005-2011 Avago Technologies. All rights reserved. AV02-2493EN - April 4, 2011

**Avago**  
TECHNOLOGIES

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [LED Displays & Accessories](#) category:*

*Click to view products by [Broadcom](#) manufacturer:*

Other Similar products are found below :

[LTC-2721WC](#) [LTC-4624JD](#) [LTC-4627WC](#) [LTC-571P](#) [LTD-5021AWC](#) [LTM-8522G](#) [LTP-4323P](#) [LTP-747G](#) [LTS-3361JG-06](#) [ELS-316SYGWA/S530-E2](#) [1668](#) [HT-F196NB-5323](#) [IPD2131-27](#) [SA03-12EWA](#) [LDQ-N514RI](#) [LDS-A3506RD](#) [LDS-A3926RI](#) [SC03-12HDB](#) [SI-B9T151550WW](#) [SI-B9V171550WW](#) [SLC-3PF-WL](#) [SLDN-32M-G](#) [1624](#) [LTC-2623WC](#) [LTC-4627JD](#) [LTD-322G](#) [LTD-482PC](#) [LTP-1057AHR](#) [LTP-1457AKR](#) [LTP-3784G-01](#) [LTS-313AP](#) [LTS-4812SKR-P](#) [LTS-547AE](#) [LTS-6780P](#) [446010401-3](#) [DA43-11GWA](#) [LDD-A516RI-17](#) [LDD-E305RI](#) [LDQ-N3402RI](#) [LDQ-N3606RI](#) [LDT-M2804RI](#) [86004CB830](#) [LTP-3862JD](#) [LTP-2088AKD](#) [LTD-6740P](#) [LTS-6880Y](#) [LDS-SMC3002RISUGTR](#) [LTC-2623E](#) [CC25-12YWA](#) [LDM-6432-P3-UR-1](#)