

TECHNICAL DATA SHEET

ECO - Lead-free Solder Alloy

Description

ECO is a high-quality and ecological lead-free soft solder alloy.

Application: developed for general hand and automated soldering applications, component attach and touch-up for surface mount technology for the electronics assembly industries where a low melting point alloy has been specified.

Available formats: flux-cored wire, solid wire, wave bar and rod.

Type of Alloys

Product Name	Alloy N° EN ISO 9453	Alloy Designation	Melting Temp °C
ECO 1	401	S-Sn99,3Cu0,7	220 eutectic
ECO 2	702	S-Sn97Ag3	221 eutectic
ECO 3	402	S-Sn97Cu3	230 eutectic
ECO 4	711	S-Sn96,5Ag3Cu0,5	217-220
ECO 5	501	S-Sn99Cu0,7Ag0,3	217-227
ECO 6	713	S-Sn95,5Ag3,8Cu0,7	217-226

Alloys compliant with the current regulation EN-ISO 9453: 2006 and RoHS directive.

Other alloys are available upon request.

Type of flux cores

Flux core	Classification & Compliance	Flux description & Properties
B2.2	1.1.3.B (EN-ISO 29454-1) ROMO (J-STD-004)	<ul style="list-style-type: none"> Halide-free rosin for all electronic assembly applications. Fast wetting and good spreading. Minimal non-corrosive and clear post-soldering residues which can be safely left without the need to remove them.
B2.1	1.1.2.B (EN-ISO 29454-1) ROM1 (J-STD-004)	<ul style="list-style-type: none"> Activated rosin (contains halides) for quick-spreading and difficult to solder surfaces to join copper, nickel, brass and bronze. Also suitable on robotic soldering, rework and repair applications. Low post-soldering residues that are hard and which can be safely left without the need to remove them.
B1.2	1.2.3.B (EN-ISO 29454-1) REM0 (J-STD-004)	<ul style="list-style-type: none"> Halide-free resin. Good spread on copper, brass and nickel. Low spitting.
B1.1	1.2.2.B (EN-ISO 29454-1) REM1 (J-STD-004)	<ul style="list-style-type: none"> Activated resin (contains halides). Developed to cope with the higher process temperatures at lead-free soldering.

TECHNICAL DATA SHEET

ECO - Lead-free Solder Alloy

Nº of flux cores: 4

Flux content: standard 2,5 weight %

Delivery form

Available diameters: from 0,35 mm.

Delivered in plastic reel of: 100gr x 30 units/carton | 250gr x 50 | 500gr x 24 | 1kg x 16 | 4 Kg.

Other formats may be available upon request.

Health and Safety: Before using the product, please read the material safety data sheet carefully and follow the safety precautions described.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Solder](#) category:

Click to view products by [Broquetas](#) manufacturer:

Other Similar products are found below :

[701-2758](#) [707-1811](#) [707-1850](#) [13-217-3-01](#) [P10695](#) [SN63WRAP3-.022-1-LB](#) [599Z](#) [707-0441-26](#) [707-1810](#) [601Y](#) [24-9574-7619](#) [24-4060-2437](#) [T0051387299](#) [5760140](#) [1152](#) [EC2002M-1](#) [760-2028](#) [389289](#) [570027](#) [811035](#) [811036](#) [811018](#) [ALPHA VACULOY SNCX PLUS 07 1](#)
[KG](#) [15704](#) [15808](#) [0008752](#) [0401-08-000460](#) [04-6040-0050](#) [H560103-BULK](#) [H560106-BULK](#) [H562159-BULK](#) [TDS12AS](#) [BON-102F](#)
[BON-102K](#) [BON-102S](#) [BR-102F](#) [560006BA](#) [560048](#) [560069W-LF](#) [5601034](#) [5601053](#) [5601056](#) [5601058](#) [5601129](#) [5601157](#) [5601161](#)
[8001092](#) [5601243](#) [0401-08-000179](#) [5601247](#) [0401-08-000183](#) [5601275](#)