

Handy Electrical DMM + 3 Φ Rotation Meter!

System & Motor 3 Φ Rotation, Audible + Visible BeepLit™ Continuity, AutoV + Ghost Voltage Buster, VFD V & Hz Fundamentals, Hi & Lo EF-Detection, No Amps & 10 Amps Models, Records Min/Max/Average!



BM230R Series
Electrical Multimeter



BRIGHT PEOPLE'S CHOICE
<http://www.brymen.com>



● **BM239R**



● **BM237R**



● **BM236R**

239R	237R	236R	FUNCTIONS & FEATURES
●	●	●	3-5/6 Digits 6,000 Counts Large Easy To Read LCD Display
●	●	●	Fast Measurements, 5/Sec; Fully Auto-Ranging
●	●	●	Intelligent Auto Power Off
●	●	●	True RMS AC Conversion
●	●	●	Data Hold
●	●	●	Records Max/Min Readings & Calculates Avg Readings Over Time
●	●	●	VFD V & Hz Fundamental Readings Of Most Variable-Frequency-Drives
●	●	●	Paper white Back-Lighted LCD Display
●	●	●	BeepLit™ Continuity. Features Audible Beep & Visible Backlight Effects
●	●	●	Relative Zero Mode
●	●	●	Non-Contact EF-Detection (NCV) With Hi/Lo Selectable Sensitivities
●	●	●	Probe-Contact EF-Detection For More Precise Indication Of Live
●	●	●	Ⓡ 3Φ-Rotation-R (Regular-sensitivity mode) for Supply Systems (Probe-contact)
●	●	●	Ⓢ 3Φ-Rotation-M (Hi-sensitivity mode) for Motors (Probe-contact)
●	●	●	AutoV LoZ Feature. Automatic DC & AC 1000V Selection With Low Initial Impedance To Drain Ghost Voltages
●	●	●	DC/AC V Ranges 600.0mV To 1000V
●	●	●	Ohms Ranges 600.0Ω To 60.00MΩ
●	●	●	Cx Ranges 2000nF to 10.00mF For Start & Run Motor Capacitors
●	●	●	Line Level Frequency Ranges 99.99Hz To 50.00kHz
●	●	●	DC/AC A Ranges 6.000A To 10.00A (20A for 30s / 5 mins cool down)
●	●	●	DC/AC μA Ranges 200.0μA To 2000μA
●	●	●	Type-K Temperature Readings -40°C To 400°C or -40°F To 752°F
●	●	●	Beep-Jack™ Input Warning Against Improper A-Terminal Plug In
●	●	●	Diode Tester
●	●	●	Rugged Fire Retarded Housing
●	●	●	Replaceable Protective Holster With Probe-Holders & Tilt-Stand
●	●	●	Optional Purchase Magnetic Hanger
●	●	●	Batteries And Fuses Access Door
●	●	●	Transient Protection Up To 6kV 1.2/50μs Lightning Surge
●	●	●	LVD: EN61010-1/-2-030/-2-033 CAT-II 1kV, CAT-III 600V & CAT-IV 300V
●	●	●	EMC: EN61326-1:2013

An Electrical DMM Engineered For Professionals!

LoZ AutoV, VFD V/Hz, 3Wire RST, °C/°F, μ A/10A, BeepLit™ Continuity, Hi/Lo EF-Detection, BeepJack™ Warning



White Display Backlight
For Easy Viewing In The Dark

Auto & Manual-ranging
Auto-ranging With Manual-ranging Override

True Rms Measurements
For Non-sinusoidal Waveforms Of AC Voltages & AC Currents

Large 6000 Counts LCD Display
5/sec Fast Nominal Update Rate

Function Selection
Toggle Conveniently Between Primary & Secondary Functions

Max Min Avg Record
Record Max/Min And Calculates Average Readings Over Time

Hz Of Line Level Voltage
Measures Noisy High Voltage ACV Frequencies

Relative Zero Mode
For Convenient Readings Comparison & Offset

VFD V & Hz Feature
Measures Fundamental Voltage & Frequency Of Most Variable-Frequency-Drives

Data Hold
Freezes The Displaying Reading For Later View

High Impedance Voltage
1000VAC/DC Measuring Capabilities; High Input Impedance For Load Sensitive Circuits

Hi/Lo Senses EF-Detection
Both Non-contact (NCV) & Single-probe Voltage Detection For Identifying Live Lines

AutoV LoZ Feature
Automatic Selection Of LoZ DCV And LoZ ACV

RST Phase Rotation
Dual Sensitivity Modes For Both Motors And Supply Systems

Ghost-voltage-buster
AutoV Loz Drains Ghost/ Stray Voltages Leaving Only Hard Signals On Meter Readings

BeepLit™ Continuity
Quick Open-short Tests. Beep and Backlight Effects For Noisy Environments

Beep-jack™ Audible Warning
Beeps Against Improper A-terminal Plug In. Decreases Risks Of Damage

Type-k Temperature
Selectable °C & °F Readings

Protective Holster
With Holders For Probe Storage And "third Hand" Feature, Replaceable & Washable

Intelligent Auto-power-off
To Extend Battery Life

EMC
Meets EN61326-1:2013

LVD Safety
Meets EN61010-1/-2-030/-2-033
CAT II 1kV & CAT III 600V

Transient Protection
Up To 6kV 1.2/50 μ s Lightning Surge; Superb Protection For Serious Users

GENERAL SPECIFICATION

Display: 3-5/6 digits 6,000 counts

Update Rate: 5 per second nominal

Operating Temperature: -10°C to 45°C

Relative Humidity: Maximum relative humidity 80% for temperature up to 31°C decreasing linearly to 50% relative humidity at 45°C

Altitude: Operating below 2000m

Storage Temperature: -20°C ~ 60°C, < 80% R.H. (with battery removed)

Temperature Coefficient: Nominal 0.15 x (specified accuracy)/ °C @ (-10°C ~ 18°C or 28°C ~ 45°C), or otherwise specified

Sensing: True RMS sensing

Pollution Degree: 2

Safety: Double insulation per IEC/UL/EN61010-1 Ed. 3.0, IEC/UL/EN61010-2-030 Ed. 1.0, IEC/UL/EN61010-2-033 Ed. 1.0, IEC/UL/EN61010-031 Ed. 1.1 and the corresponding CAN/CSA-C22.2 regulations to Measurement CAT II 1000V, CAT III 600V and CAT IV

300V AC & DC

Transient Protection: 6.0kV (1.2/50µs surge)

Terminals (to COM) Measurement Category:

V / mAµA / A / L3: Category II 1000V, CAT III 600V and CAT IV 300V AC & DC.

E.M.C. : Meets EN61326-1:2013

In an RF field of 3V/m:

Temperature function is not specified

Ohm function:

Total Accuracy = Specified Accuracy + 15 digits

Other functions:

Total Accuracy = Specified Accuracy

Performance above 3V/m is not specified

Overload Protection:

A: 11A/1000V DC/AC rms, 1R 20kA, F Fuse; or better

V, Auto V & L3: 1100V DC/AC rms

mV, Ohm & others: 1000V DC/AC rms

Low Battery: Below approx. 2.5V

Power Supply: 1.5V AAA Size battery X 2

Power Consumption (typical): 3.2mA

APO Consumption (typical): 10µA

APO Timing: Idle for 30 minutes

Dimension: 161*80*50mm L*W*H (With Holster)

Weight: Approx. 334 gm (With Holster)

Special Features: AutoV (LoZ); 3-Phase Rotation detection; VFD; BeepLit™ Continuity Tester; Auto-ranging MAX/MIN/AVG Record; Backlighted LCD; Auto-ranging Relative Zero mode; Display Hold; EF-Detection (NCV) (BM237R & BM239R only); BeepJack™ on A terminal (BM237R & BM239R only)

Accessories: Test lead set; Alligator clip set; Batteries installed; User's manual; BKP60 banana plug type-K thermocouple (BM239R only)

Optional Purchase Accessories: BKB32 banana plug to type-K socket plug adaptor (BM239R only); BMH-01 magnetic hanger; BMP-25x soft carrying pouch

Electrical Specification

Accuracy is given as ±(% of reading digits + number of digits) or otherwise specified @ 23°C ± 5°C

ACV & ACA accuracies are specified from 1% to 100% of range or otherwise specified. Maximum Crest Factor <2:1 at full scale & <4:1 at half scale, and with frequency components fall within the meter specified frequency bandwidth for non-sinusoidal waveforms

AC Voltage

RANGE	Accuracy
50Hz ~ 60Hz	
6.000V, 60.00V, 600.0V, 1000V	0.7% + 3d
45Hz ~ 440Hz	
6.000V, 60.00V, 600.0V, 1000V	2.0% + 3d
10Hz ~ 500Hz	
60.00mV, 600.0mV	1.0% + 3d
500Hz ~ 800Hz	
60.00mV, 600.0mV	2.0% + 3d

Input Impedance: 10MΩ, 54pF nominal

VFD ACV (with Low Pass Filter)

RANGE	Accuracy ¹⁾
10Hz ~ 440Hz (fundamental)	
600.0V, 1000V	2.0%+3d

¹⁾Not specified for fundamental frequency > 440Hz

AutoV ACV

RANGE	Accuracy ¹⁾
45Hz ~ 440Hz	
600.0V, 1000V	2.0% + 3d

¹⁾Not specified at <1VAC

Threshold: > 1VAC nominal

Input Impedance:

Initially approx. 2.1kΩ, 164pF nominal; Impedance increases abruptly within a fraction of a second as display voltage is above 50V (typical). Ended up impedances vs display voltages typically are:

12kΩ @100V
100kΩ @300V
240kΩ @600V
580kΩ @1000V

DC Voltage

RANGE	Accuracy
60.00mV, 600.0mV, 6.000V, 60.00V, 600.0V, 1000V	0.3% + 2d

Input Impedance: 10MΩ, 54pF nominal

AutoV DCV

RANGE	Accuracy ¹⁾
600.0V, 1000V	2.0% + 3d

¹⁾Not specified at <1VDC

Threshold: > +1.0VDC or < -1.0VDC nominal

Input Impedance:

Initially approx. 2.1kΩ, 164pF nominal; Impedance increases abruptly within a fraction of a second as display voltage is above 50V (typical). Ended up impedances vs display voltages typically are:

12kΩ @100V
100kΩ @300V
240kΩ @600V
580kΩ @1000V

Ohm

RANGE ¹⁾	Accuracy
600.0Ω, 6.000KΩ	0.3% + 3d
60.00KΩ, 600.0KΩ	0.5% + 3d
6.000MΩ ²⁾ , 60.00MΩ ³⁾	0.9% + 3d ⁴⁾

¹⁾Open Circuit Voltage: 1.6VDC typical

²⁾Constant Test Current: 0.2µA Typical

³⁾Constant Test Current: 0.02µA Typical

⁴⁾5%+20d @ >30MΩ

BeepLit™ Continuity Tester

Continuity Threshold: Between 30Ω and 480Ω

Response time: 64ms

Latch time: 128ms

Audible Response: Beep sound

Visible Response: LCD Backlight

Capacitance (BM237R & BM239R only)

RANGE	Accuracy
2000nF, 20.00µF, 200.0µF, 2000µF	1.5% + 2d
10.00mF	4.5% + 10d

Accuracies with film capacitor or better

DCµA & ACµA (BM239R only)

RANGE	Accuracy	Burden Voltage
DCµA		
200.0µA, 2000µA	0.7% + 3d	2.5mV/µA
ACµA (50Hz ~ 400Hz)		
200.0µA, 2000µA	1.0% + 3d	2.5mV/µA

Overload protection type: PTC protective impedance combination

DCA & ACA (BM237R & BM239R only)

RANGE	Accuracy	Burden Voltage
DCA		
6.000A, 10.00A ¹⁾	0.7% + 3d	0.04V/A
ACA (50Hz ~ 400Hz)		
6.000A, 10.00A ¹⁾	1.0% + 3d	0.04V/A

¹⁾10A continuous, >10A to 20A for 30 seconds max with 5 minutes cool down interval

Overload protection type: HBC fuse

Temperature (BM239R only)

RANGE	Accuracy
-40.0 °C ~ 99.9°C	1% + 1 °C
100 °C ~ 400°C	
-40.0 °F ~ 99.9 °F	1% + 2 °F
100 °F ~ 752 °F	

Type-K thermocouple range & accuracy not included

Diode Tester

RANGE	Accuracy
3.000V	0.9% + 2d

Test Current: 0.3mA typical

Open Circuit Voltage: < 3.2VDC typical

Line Frequency (BM237R & BM239R only)

Function	Sensitivity (Sine RMS)	Range
60mV, 600mV	50mV	10Hz - 50kHz
6V	3V	10Hz - 50kHz
60V	5V	10Hz - 50kHz
600V	50V	10Hz - 1kHz
1000V	500V	10Hz - 1kHz
VFD 600V	50V	10Hz - 1kHz
VFD 1000V	500V	10Hz - 1kHz
200µA ¹⁾ , 2000µA ¹⁾	500µA	10Hz - 5kHz
6A, 10A	8A	50Hz - 1kHz

¹⁾Available for Model 239R only

Accuracy: 0.03% + 2d

Non-Contact EF-Detection (BM237R & BM239R only)

Bar-Graph Indication	EF-H (Hi Sensitivity)	EF-L (Lo Sensitivity)
	Typical Voltage (Tolerance)	
-	10V (3V~19V)	40V (16V~71V)
--	20V (10V~38V)	80V (32V~142V)
---	40V (21V~79V)	160V (63V~285V)
----	80V (40V~156V)	300V (105V~608V)
-----	160V (>80V)	500V (>300V)

Indication: Bar-graph segments & audible beep tones proportional to the field strength

Detection Frequency: 50/60Hz

Detection Antenna: Top left end of the meter
Probe-Contact EF-Detection: For more precise indication of live wires, such as distinguishing between live and ground connections, use direct contact testing with one single test-probe via the input terminal COM or V. The COM terminal (Black) has the best sensitivity.

(R) & (C) 3-Phase Rotation function

Hi-sensitivity mode (R)

Voltage range: 0.4V ~ 1000V

Frequency range: 3Hz ~ 400Hz

Regular-sensitivity mode (C)

Voltage range: 65V ~ 1000V

Frequency range: 35Hz ~ 400Hz



BRYMEN TECHNOLOGY CORPORATION

http://www.brymen.com

TEL: +886 2 2226 3396 (rep)

FAX: +886 2 2225 0025

Copyright © MMXV B.T.C. All rights reserved

Specifications subject to change without notice

Patents pending. Printed in Taiwan

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Digital Multimeters](#) category:

Click to view products by [Brymen](#) manufacturer:

Other Similar products are found below :

[6111-517](#) [FS881](#) [40705X](#) [P 3340](#) [SEFRAM7303](#) [F302+](#) [19290](#) [IBT6K](#) [1000-219](#) [1001-613](#) [1001-810](#) [1002-408](#) [1006-969](#) [1008-221](#) [1012-597](#) [1013-099](#) [30XR](#) [34XR](#) [35XP](#) [TESTO 745](#) [0590 7450](#) [TESTO 760-2](#) [0590 7602](#) [TESTO 760-3](#) [0590 7603](#) [440012](#) [AX-155](#) [AX-174](#) [AX-178](#) [AX-18B](#) [AX-190A](#) [AX-503](#) [AX-507B](#) [AX-594](#) [AX-LCR42A](#) [AX-MS8250](#) [AX-PDM01](#) [AX-T520](#) [AX-T901](#) [AX-T903](#) [BAT-250-EUR](#) [BM525S](#) [BM807S](#) [BM817S](#) [BM827S](#) [BM829S](#) [BM857S](#) [BM859S](#) [BM867S](#) [BM907S](#) [33XR](#) [UNITEST TESTFIX 9023](#) [37XR](#)