







## NOTE:

- 1.) MATERIAL: ABS THERMOPLASTIC

  (FLAMMABILITY RATING OF 94V-0 AT 0.070°

  THICKNESS & CONTINUOUS USE TEMPERATURE OF 70° C.)
- 2.) FINISH: DUTSIDE SURFACES ARE TEXTURED.
- 3.) COLOR: BLACK
- 4.) LENGTH & WIDTH DIMENSIONS ARE TAKEN FROM CLOSED END OF BOX. SLIGHT INCREASE AT OPEN END, DUE TO TAPER.

THIS IS A #PB-1576-TF MODIFIED WITH SPECIAL HOLES.

	ITEM	REQ'D.	PAR	T N□.		DESCRIF	PTION
TOLERANCES:	MAT:	AS	NOTED	SCALE:		NAME:	
±,005 BETWEEN HOLE CENTERS ±,015 FROM SHEARED EDGE ±,032 FROM A BENT SURFACE	FINIS	SH: AS	NOTED	BID		POTTING BOX (TOP FLANGE)	
	DR.	BT 6	5-19-08				
LOCO DETLIEFL ACCENDUED	CH.		<del>-</del>	BUD INDUS	STRIES, INC.		
QTY. USED ON UNLESS OTHERWISE SPECIFIED	APP,		-	WILLOUGH	HBY, OHIO	DWG, N□.	47805

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for bud industries manufacturer:

Other Similar products are found below:

CR-1727 LW-3213 CSA-11264 CU-247 MODIFIED CU-382-MB CU-5475 CU-7127-GT EXN-23371-FET FN-1280 FT-1979 PMR-9449-NF PS-11296-G PS-1250-MG PS-1258 H-9164-B AC-1610 RFV-20203 RL-7765 RM-14212 AN-1301-G AN-1308-AB AN-2813-A AN-2816-A ANX-91322 AS-5061 BAS-5101 BAS-5104 BAS-5108 BBC-1824 BC-14210 BP-681 BP-705 NBD-10462 NBF-32016 NBF-32228 NBF-32234 NBF-32320 NBF-32434 C-1588 PA-1101-LG PA-1105-BR PA-1109-MG PA-1131-MG PA-1138-WH JB-1654 PA-2402-MG JB-3953 JB-3960 PA-3105-HG LB-1662