

Distribution Units have combinations of four, five or six outlets together with neon indicator, fuse and switch options. The three sizes are available in various combinations and, other than the compact version, all have shuttered outlets. The larger enclosed versions are also available with EMI filtering.











- O Five Shuttered Outlets
- 5 x 20mm Fuseholder
- O Neon Indicator
- 00 Filtered or Non-filtered
- EN60320 Inlet
- O 10A, 250V AC



IEC Panel Mount Distribution Unit




- Five Shuttered Outlets
- 5 x 20mm Fuseholder
- Neon Indicator
- Screw Fit to Panel
- 0 10A, 250V AC



IEC Distribution Unit



- O Five Shuttered Outlets
- 5 x 20mm Fuseholder
- Neon Indicator
- O Filtered or Non-filtered
- 2 Metre Cable with BS1363 Plug
- O 10A, 250V AC



Part No.	Inlet	Outlet	EMI Filter	Neon Indicator	Fuse	Illuminated Switch
Panel Style:						
PXD100/050/01/1		5 Shuttered		1	1	
Box Style:						
PXD301/050/01/1	1	5 Shuttered		1	1	
PXD301/050/07/1	1	5 Shuttered				Red
PXD301/050/08/1	1	5 Shuttered	•			Green
PXD301/550/01/1	1	5 Shuttered	•	1	1	
PXD301/550/07/1	1	5 Shuttered	•			Red
PXD301/550/08/1	1	5 Shuttered				Green
PXD303/050/01/1	2m cable with BS1363 plug	5 Shuttered		1	1	
PXD303/050/07/1	2m cable with BS1363 plug	5 Shuttered				Red
PXD303/050/08/1	2m cable with BS1363 plug	5 Shuttered	•			Green
PXD303/550/01/1	2m cable with BS1363 plug	5 Shuttered	•	1	1	
PXD303/550/07/1	2m cable with BS1363 plug	5 Shuttered	•			Red
PXD303/550/08/1	2m cable with BS1363 plug	5 Shuttered				Green
PXD306/050/01/1	2m cable with CEE7 Sheet VII plug	5 Shuttered		1	1	


IEC Rectangular Distribution Units



IEC Distribution Unit




- O Five Shuttered Outlets
- Illuminated Switch
- Filtered or Non-Filtered
- EN60320 Inlet
- O 10A, 250V AC



IEC Distribution Unit



- Five Shuttered Outlets
- Illuminated Switch
- Filtered or Non-Filtered
- O 2m Cable and BS1363 plug
- O 10A, 250V AC



Specifications

Mouldings: Thermoplastic

Housing: ABS

Connectors: Nylon

Contacts: Outlets: Brass, Tin Plated

Inlets: Brass, Nickel Plated

Voltage Rating: 250V AC 50/60Hz

Current Rating: 10A
Proof Voltage: 2kV

Temp. Range: -5°C to +60°C

Mating Connectors: PX0686, PX0686/SE

RoHS Compliant

Filter

Max. Earth Leakage:

Current: <0.35mA (at 250V, 50Hz)

Capacitor 2 x 2.2nF (Y), 1 x 15nF (X)

Inductance: 2 x 0.35mH


Fuse: 5 x 20mm, 10A (ceramic HRC type, IEC 127)



Compact Distribution Unit




- Four Outlets
- 0 EN60320 Inlet
- O 10A, 250V AC
- cULus Approval



Compact Distribution Unit



- O Four Outlets
- 2m Cable with BS1363 connector, Schuko connector (CEE7) or NEMA 5/15 connector
- O 10A, 250V AC



Specifications

Mouldings: Thermoplastic

Housing: ABS, UL94V-0

BS1363, CEE7, NEMA 5/15 Connectors:

Outlets: Brass, Tin Plated Inlets: Brass, Nickel Plated Contacts:

250V AC 50/60Hz Voltage Rating:

10A Current Rating:

Proof Voltage: 2kV

Temp. Range: -5°C to +60°C

Approvals c us Listed (PXD200)

RoHS Compliant

Part No.	Inlet	Outlet
PXD200	1	4
PXD201	2m cable with BS 1363 plug	4
PXD201/1	2m cable with Schuko plug	4
PXD201/2	2m cable with NEMA 5/15	4




Compact Distribution Unit



PXD701/061/10/1

- Six Shuttered Outlets
- 5 x 20mm Fuseholder
- O Filtered or Non Filtered
- Switch, Fuse, Neon Indicator With IEC Inlet \bigcirc
- 0
- O 10A, 250V AC








PXD500/061/10/1


- O Six Shuttered Outlets
- 5 x 20mm Fuseholder
- O Switch, Fuse, Neon Indicator
- Screw Fit to Panel
- 10A, 250V



Compact Distribution Unit



- O Six Shuttered Outlets
- 5 x 20mm Fuseholder
- O Filtered or Non Filtered
- Switch, Fuse, Neon Indicator
- 2 Metre Cable with BS1363
- or CEE7 Plug O 10A, 250V



Specifications				
Mouldings:	Thermoplastic			
Housing:	ABS			
Connectors:	Nylon			
Contacts:	Outlets: Brass, Tin Plated Inlets: Brass, Nickel Plated			
Voltage Rating:	250V AC 50/60Hz			
Current Rating:	10A			
Proof Voltage:	2kV			
Temp. Range:	−5°C to +60°C			
RoHS	Compliant			

Part No.	Inlet	Outlet	EMI Filter	Switch	Fuse	Neon Indicator
Panel Style:						
PXD500/061/10/1		6 Shuttered		1	1	1
Box Style:						
PXD701/061/10/1	1	6 Shuttered		1	1	1
PXD701/561/10/1	1	6 Shuttered	•	1	1	1
PXD703/061/10/1	2m cable with BS 1363 plug	6 Shuttered		1	1	1
PXD703/561/10/1	2m cable with BS 1363 plug	6 Shuttered	•	1	1	1
PXD706/061/10/1	2m cable with CEE7 Sheet VII plug	6 Shuttered		1	1	1

Filter

Max. Earth Leakage:

<0.35mA (at 250V, 50Hz) Current: 2 x 2.2nF (Y), 1 x 15nF (X) Capacitor

Inductance: 2 x 0.35mH

5 x 20mm, 10A (ceramic HRC type, IEC 127) Fuse:

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for AC Power Entry Modules category:

Click to view products by Bulgin manufacturer:

Other Similar products are found below:

0098.0050 6167.0002 6609100-2 7-6609955-2 FKI2-50-6/M5 FN361-6-06 FN389-4-22 FN9226B-6-02 FN9233S1-10-06 FN9233S1-8-06 FN9233S1B-8-06 FN9233S1R-12-06 FN9233S1R-12-06 FN9233SB-12-06 FN9233SB-8-06 FN9233SR-10-06 FN9244B-15-06HI FN9244EB-3-06 FN9244EB-8-06 FN9244ER-15-06 FN9244ER-8-06 FN9244ES1-8-06 FN9244ESB-8-06 FN9244R-12-06 FN9244S1-12-06 FN9244S1R-3-06 FN9244SB-8-06 FN9244SR-6-06 FN9244U-3-06 FN9244U-8-06 8-6609940-2 PE00SSSXB Fuse-H-EUR-1 Fuse-H-USA-1 PM00XD000 A-0701-HT-H 15EJMS8 1-6609941-2 200JM6-2 CA121003-6 SK-1015(F1-5) 161-R3015-E 1-6609153-2 FN323-1-05 FN9233B-8-06 FN9233EB-1-06 FN9233ES1R-10-06 FN9233R-12-06 FN9233S-10-06