

Polarized flat cables



RoHS
Conformity

Applications:
Polarized flat cable.
Cable for electronics, loudspeakers, Home Theatre and Hi-Fi Car systems.

Characteristics:
Conductors: n. 1 O.F.C. red copper
n. 1 O.F.C. tinned copper
Special PVC
Insulation: Grey
Sheath colours: Black or White *on demand*

tasker® Code	Cond. number	Nominal section mm ²	Nominal section AWG	Elementary wire conductor Ø mm.	External Cable Dimension mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C100	2	2 x 0,35	22	0,20	1,9 x 3,9	100	B	1,1
		2 x 0,50	20	0,20	2,0 x 4,1	100	B	1,5
		2 x 0,75	18	0,20	2,2 x 4,5	100	B	2,1
		2 x 1,00	17	0,20	2,8 x 5,7	100	B	2,9
		2 x 2,00	14	0,20	3,7 x 7,1	100	B	5,5

RoHS
Conformity

Conductor Resistance Ω/Km ± 5%	Max rated Voltage AC - V	Operative Temperature °C
60	49	-15 / +70
45	49	-15 / +70
32	49	-15 / +70
21	49	-15 / +70
14	49	-15 / +70

RoHS
Conformity

Applications:
Red and black flat cable.
Cable for loudspeakers, Home Theatre and Hi-Fi Car systems.

Characteristics:
Conductors: O.F.C. red copper
Insulation: Special PVC
Sheath colour: Red-black

Red and Black flat cables



RoHS
Conformity

tasker® Code	Cond. number	Nominal section mm ²	Nominal section AWG	Elementary wire conductor Ø mm.	External Cable Dimension mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C101	2	2 x 0,35	22	0,20	1,9 x 3,9	100	B	1,1
		2 x 0,50	20	0,20	2,0 x 4,1	100	B	1,5
		2 x 0,75	18	0,20	2,2 x 4,5	100	B	2,1
		2 x 1,00	17	0,20	2,5 x 5,1	100	B	2,9
		2 x 1,50	16	0,25	3,1 x 6,2	100	B	4,0
C102	2	2 x 2,00	14	0,25	3,5 x 7,1	100	B	5,5
		2 x 2,50	13	0,25	3,7 x 7,4	100	B	6,4

RoHS
Conformity

Conductor Resistance Ω/Km ± 5%	Max rated Voltage AC - V	Operative Temperature °C
60	49	-15 / +70
45	49	-15 / +70
32	49	-15 / +70
21	49	-15 / +70
16	49	-15 / +70
14	49	-15 / +70
12	49	-15 / +70

Multicolour flat cable



RoHS
Conformity

Applications:
Multicolour flat cable.
Cable for electronics, loudspeakers, Home Theatre and Hi-Fi Car systems.

Characteristics:
Conductors: O.F.C. red copper
Cond. Insulation: PVC
Core colours: Blue, White, Black, Red
Sheath: Special PVC
Sheath colour: Transparent

tasker® Code	Cond. number	Nominal section mm ²	Nominal section AWG	Elementary wire conductor Ø mm.	External Cable Dimension mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C104	4	4 x 1,00	17	0,20	3,0 x 12,0	100	B	6,0

Conductor Resistance Ω/Km ± 5%	Max rated Voltage AC - V	Operative Temperature °C
21	49	-15 / +70

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Audio Cables](#) / [Video Cables](#) / [RCA Cables](#) category:

Click to view products by [Tasker](#) manufacturer:

Other Similar products are found below :

[59384500100E](#) [73-6310-10](#) [73-6311-10](#) [73-6313-3](#) [73-6313-6](#) [PCX-60-50](#) [RCA10RCA](#) [1-3737-600-3216](#) [15AK25X](#) [25FK25](#) [LF3BLX](#) [30-1511-10](#) [30AR30](#) [30AK30](#) [30AN30](#) [RCA05RCA](#) [RCA05RCAB](#) [RCA05TS](#) [RCA10RCAB](#) [420001400-3](#) [426058900-3](#) [TT6RX](#) [TT7BKX](#) [TT93602](#) [426058300-3](#) [LF1BKX](#) [LF3RX](#) [0887418300](#) [73-6312-6](#) [73-6314-3](#) [73-6352-3](#) [VMP3YX](#) [VMP2YX](#) [68767-0003](#) [TT746](#) [TT744](#) [CN13B](#) [LF4GNX](#) [LF2GYX](#) [426494200-3](#) [LF1RX](#) [VMPBNCF](#) [LF10GNX](#) [427492100-3](#) [LF4BLX](#) [TT747N2](#) [TT864](#) [LF2YX](#) [426491500-3](#) [426523700-3](#)