CT2151 Stacking Banana Plug Test Lead

Datasheet

4mm Stacking, Retractable Sleeve Banana Plug to Stacking, Retractable Sleeve...

Description

Added safety and protection when standard banana jack connections are encountered. With our largest gauge silicone jacketed wire, 2.50 mm2 (13 AWG). Clear covering sleeve retracts as you plug into the jack. Banana plug includes a Grey plastic insulation tip for added protection.

- Materials: Body: Polyamide; Contact: Brass, Nickel Plt.
- Banana Contact: BeCu, Nickel Plt.
- Meets IEC 61010-031 safety specifications
- Available in 6 standard lengths
- Available in 6 colors



Technical data subject to change. © Cal Test Electronics 2018.



caltestelectronics.com

All specifications apply to the unit after a temperature stabilization time of 20 minutes over an ambient temperature range of $25^{\circ}C \pm 5^{\circ}C$.

Specifications

IEC Rating	600 V CAT II
Current Max	36 A
Jacket Material	Silicone
Conductor Area	2.50 mm2
Wire Gauge	13 AWG
Stranding (# x dia.)	651 x 0.07 mm
Jacket OD	3.9 mm (0.154")
Temperature (degrees)	-20 to +80C
RoHS (2011/65/EU)	Compliant

Specifications are subject to change without notice. To ensure the most current version of this manual, please download the current version from our website: caltestelectronics.com



caltestelectronics.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Test Leads category:

Click to view products by Cal Test manufacturer:

Other Similar products are found below :

795-2384-10-25
1301430020
1510-24-105
15308
15408
15302
15409
BU-1149-A-36-0
BU-1481-E-12-0
BU-1481-E-24-0
1927617
2450

2524-A-60
LB1F-2R-RED
LB1F-2R-YLW
2500
2524-A-48
2977-J-48
R948131000
380200
BU-1449-E-12-2
BU-1480-E-24-0
BU-1481-E-24-0
<td