CT3810 Alligator Clip Test Lead

Datasheet

Pair, black & red, insulated alligator clip to insulated alligator...

Description

Black and red pair of standard insulated alligator clip to standard insulated alligator clip test leads. Alligator clips have insulated PVC boots. Test lead wire is 18 AWG with highly flexible silicone jackets.

Features:

- Materials:
- Body & spring: steel, nickel plated
- Insulator: PVC
- Wire: high stranded bare copper; silicone jacket
- Jaws open to 7.9 mm (0.31")
- Black & red pair
- Available in 3 lengths
- IEC 61010-031 rated

Available as individual colorsModel CT3809





All specifications apply to the unit after a temperature stabilization time of 20 minutes over an ambient temperature range of 25° C \pm 5° C.

Specifications

Voltage Rating	300 V CAT II
Current, Max	10 A
Jacket Material	Silicone
Wire Gauge	18 AWG (0.82 mm2)
Stranding (# x dia.)	168 x 0.07 mm
Jacket OD	3.7 mm (0.146")
Temperature (degrees)	-20 to +80C
RoHS (2011/65/EU)	Compliant

Specifications are subject to change without notice. To ensure the most current version of this manual, please download the current version from our website: caltestelectronics.com



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Test Leads category:

Click to view products by Cal Test manufacturer:

Other Similar products are found below:

795-2384-10-25 1301430020 1510-24-105 15308 15408 15302 15409 BU-1149-A-36-0 BU-1481-E-12-0 BU-1481-E-24-0 1927617 2450 2524-A-60 LB1F-2R-RED LB1F-2R-YLW 2500 2524-A-48 2977-J-48 R948131000 380200 BU-1449-E-12-2 BU-1480-E-24-0 BU-1481-E-12-2 BU-1481-E-24-2 LB1F-2R-BLK LB1F-2R-BLUE LB1F-2R-WHT 6345 6432 6416 EM3782-24-3# R948161002 R948160002 R948170002 R948171002 R948163002 973604100 934160101 934160100 R948174000 CT3269 CT3258 CT3158-100 HSPL 8568/AWG16/200/RT HSPL 8568/AWG16/200/SW 28.0119-10020 28.0127-05025 28.0127-20025 49.0079-20021 49.0079-20024