

CT3986

Datasheet

Pair, CAT IV DMM probes with silicone leads and right-angle

Pair, CAT IV DMM probes with silicone leads and right-angle...

Description

Pair of DMM probes with leads, black and red, with 2 mm (.080) diameter x 19 mm (0.75) probe tips. With safety caps installed, probes meet the 600 V CAT IV per IEC 61010-031. Remove the safety caps to access standard 2 mm tips and attach optional tip accessories that snap-lock to the probe body for secure connection. Set includes black and red pair of CT3947 spring hook probe adapter for enhanced utility.

Features:

- Pair of black and red probes
- Highly flexible silicone jacket lead wires
- 4 mm right-angle sheath banana plug connectors
- Tip: Brass, Nickel plated
- Tip fits North American power sockets

Kit Contains:

Probe Bodies, black & red - (CT3985)

Spring Hooks, black & red - (CT3947)

Optional tip accessory pairs that snap-lock to the probe tips:

- CT3941 Extended Tips
- CT3943 Alligator Clips
- CT3945 Spade Lugs



Technical data subject to change.

© Cal Test Electronics 2018.

caltestelectronics.com



All specifications apply to the unit after a temperature stabilization time of 20 minutes over an ambient temperature range of 25°C ± 5°C.

Specifications

Values	Probes w/Leads	Spring Hooks
IEC Rating	1,000 V CAT III/600 V CAT IV w/Cap(CAT III w/Cap)	300 V CAT I w/Cap
Current Max	10 A	3 A
Jacket Material	Silicone	-
Wire Gauge	18 AWG	-
Stranding	195 x 0.07 mm	-
OD	3.7 mm (0.146")	-
Temperature (degrees)	-20 to +80C	
RoHS (2011/65/EU)	Compliant	

Specifications are subject to change without notice. To ensure the most current version of this manual, please download the current version from our website: caltestelectronics.com

Technical data subject to change.

© Cal Test Electronics 2018.

caltestelectronics.com



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Test Probes](#) category:

Click to view products by [Cal Test](#) manufacturer:

Other Similar products are found below :

[6214](#) [6474](#) [815003](#) [923832-BK-B](#) [P-KIT-1](#) [KT-MS001](#) [925250-R](#) [973368101](#) [972318101](#) [972318100](#) [MXHQ87WJ3000](#) [PK106-3](#) [PK2-5MM-102](#) [TAS90](#) [VL1735/45](#) [973368100](#) [972327100](#) [972327101](#) [973995100](#) [973995101](#) [CT3982B-120](#) [MO50-PINS](#) [CT4386](#) [PP023-1](#) [PK1-5MM-127](#) [PP026-1](#) [PK103](#) [PK-ZS-013](#) [P6139B-PK10](#) [PQ215](#) [PQ218](#) [RT-ZI10C](#) [TT-SI 8071](#) [TT-SI 8050](#) [TT-SI 8010A](#) [TT-SI 7005](#) [GE.3421](#) [GE.2521](#) [GE.3121](#) [GE.1511](#) [GE.1521](#) [GE.2511](#) [GE.4511](#) [HVP15B](#) [TT-SI7002](#) [4005](#) [4011](#) [4012](#) [4013](#) [4014](#)