

**SPECIFICATIONS**

Current rating: 3A AC/DC  
 Voltage rating: 250V AC/DC  
 Contact resistance: 20mΩ max.  
 Withstand voltage: 1000V AC/min  
 Insulation resistance: 1000MΩ/min.  
 Temperature range: -25° C~+85° C


**Material:**

Part No: 2~15  
 Housing: Nylon66, UL 94V-0

Poles	Part No	Dimension mm	
		A	B
2	2503H-2P	2.50	6.0
3	2503H-3P	5.00	8.5
4	2503H-4P	7.50	11.0
5	2503H-5P	10.00	13.5
6	2503H-6P	12.50	16.0
7	2503H-7P	15.00	18.5
8	2503H-8P	17.50	21.0
9	2503H-9P	20.00	23.5
10	2503H-10P	22.50	26.0
11	2503H-11P	25.00	28.5
12	2503H-12P	27.50	31.0
13	2503H-13P	30.00	33.5
14	2503H-14P	32.50	36.0
15	2503H-15P	35.00	38.5

**TOLERANCE TABLE**

.0	±0.20
.00	±0.10
.000	±0.05

APPROVED:	DATE:	 深圳市灿科盟实业有限公司 CHANKEMENG INDUSTRYCO., LTD
CHECKED:	DATE:	
DRAWN:	DATE:	TITLE:
LYF	2008-04-07	2503H-XP
CLIENT P/N		SCALE
UNIT	mm	free
FILE NO.	Ckmtw-2503-0002	REV.
		A

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Cankemeng](#) manufacturer:*

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#)  
[63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#)  
[66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#) [M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#)  
[70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [FCN-367T-T012/H](#)  
[80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-014-20-001000](#)  
[803-43-024-10-001000](#)