



技术参数 (SPECIFICATIONS)

额定电压 250V AC/DC
 Voltage rating 250V AC/DC
 额定电流 7.0A AC/DC
 Current rating 7.0A AC/DC
 耐压: 1500V AC/minute
 Withstand voltage 1500V AC/minute
 绝缘电阻 1000MΩ/V/MIN
 Insulation resistance 1000MΩ/V/MIN
 接触电阻 0.015 Ω MAX(初始值)
 Contact resistance 0.015 Ω MAX(Initial)
 工作温度: -25°C~+85°C
 Working Temperature -25°C~+85°C
 适用线规: 24-20AWG
 Applicable Wire 24-20AWG
 间距 4.2 mm
 Pitch 4.2 mm
 材料 (MATERIAL)
 端子 磷青铜
 Terminal: Phosphor bronze

PRODUCT ID	PRODUCT NAME	MATERIALS	FINISH	AWG	Qty/reel
SS57-T	Phosphor Bronze	TIN	24~20	6500pcs	

深圳市灿科盟实业有限公司
 C kintw CHANKLEMENT INDUSTRYCO., LTD

TITLE:

5557TS 母端子 高脚 (MX4.2端子)

TOLERANCE TABLE		APPROVED:	DATE:	CLIENT P/N	UNIT	SCALE	Free	REV.
.0	±0.20			C2902704	mm			A
.00	±0.10	DRAWN:	DATE:					
.000	±0.05	LYF	2008-04-07	FILE NO.				

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Terminals](#) category:

Click to view products by [Cankemeng](#) manufacturer:

Other Similar products are found below :

[00-054007-01074-6](#) [00-054007-70206-1](#) [00-054007-70210-8](#) [00-054007-70217-7](#) [00-054007-70228-3](#) [00-054007-70256-6](#) [00-054007-70316-7](#) [00-054007-49560-4](#) [00-054007-70209-2](#) [00-054007-70231-3](#) [00-054007-70241-2](#) [00-054007-70242-9](#) [00-054007-70246-7](#) [00-054007-70263-4](#) [00-054007-70288-7](#) [00-054007-70290-0](#) [00-054007-70300-6](#) [00-054007-70304-4](#) [01-2900-1-04412](#) [00581P0075](#) [600TS-10](#) [605601-1](#) [60598-1-CUT-TAPE](#) [60617-1-C](#) [61314-6-C](#) [61810-3](#) [626-0194](#) [63-S](#) [M55155/079C01](#) [M55155/099B03](#) [M55155/099H02](#) [M55155/109H01](#) [M55155/12XH05](#) [M55155/29-5S](#) [M55155/29XJ08](#) [M55155/30-6S](#) [M55155/30-9S](#) [M55155/30XI09](#) [M6-14RSX](#) [696683-1](#) [696861-1](#) [696999-1](#) [M86700006](#) [D18-110B-C](#) [D18-110B-M](#) [701-1936](#) [701-1955](#) [701-2003](#) [701-2007](#) [701-2013](#)