

### Specification

Insulator Material: Polysetc, UL94V-0

Standard: Nylon-6T

Contact Material: Brass

Contact plated: Gold Over Nickel


Current Rating : 1Amp

Contact Resistance: 20 Milliohms Max

Insulation Resistance : 1000MΩ Min.

Dielectric withstanding Voltage: AC 500V

Operation Temperature : -40 °C -- +105 °C

APPROVED:	DATE:	 <b>深圳市灿科盟实业有限公司</b> Kintw CHANKUENG INDUSTRY CO., LTD			
CHECKED:	DATE:	TITLE: 210-1S-2*5P L=5.8MM (3.0/1.0/1.8)			
DRAWN:	DATE:	CLIENT P/N	SCALE	REV.	
LXF	2008-04-29	C2895038	free	⊕	A
TOLERANCE TABLE		UNIT	mm	SCALE	free
	.0				
	.00				
	.000				
	±0.20				
	±0.10				
	±0.05				

PCB LAYOUT

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Cankemeng](#) manufacturer:*

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)  
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)  
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [M90C108951C](#)  
[70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [80.063.4001.1](#)  
[800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-024-10-](#)  
[001000](#) [803-93-012-10-001000](#)