



SPECIFICATION:

Current Rating: 1.5AMP
 Contact Resistance: 20m Ω (max)
 Insulation Resistance: 1000M Ω Min at 500V DC
 Dielectric Strength: 500V AC Per 1 Minute
 Operating Temperature: -40°C TO +105°C

MATERIALS:

Insulator: Nylon-6T, UL94V-0
 Contact: Brass
 Contact plated: Gold Over Nickel

Poles	Part No.	Dimension mm		
		A	B	C
6	300-2SMT-6P	13.34	12.24	4.00
8	300-2SMT-8P	15.34	14.24	6.00
10	300-2SMT-10P	17.34	16.24	8.00
12	300-2SMT-12P	19.34	18.24	10.00
14	300-2SMT-14P	21.34	20.24	12.00
16	300-2SMT-16P	23.34	22.24	14.00
18	300-2SMT-18P	25.34	24.24	16.00
20	300-2SMT-20P	27.34	26.24	18.00
24	300-2SMT-24P	31.34	30.24	22.00
26	300-2SMT-26P	33.34	32.24	24.00
30	300-2SMT-30P	37.34	36.24	28.00
34	300-2SMT-34P	41.34	40.24	32.00
40	300-2SMT-40P	47.34	46.24	38.00
44	300-2SMT-44P	51.34	50.24	42.00
50	300-2SMT-50P	57.34	56.24	48.00

TOLERANCE TABLE

.0	± 0.20
.00	± 0.10
.000	± 0.05

APPROVED:	DATE:	C 深圳市矽科盟实业有限公司 CHANKLEMENT INDUSTRYCO., LTD	TITLE: 300-2SMT-XP (筒牛贴面)			
CHECKED:	DATE:		CLIENT P/N	/	SCALE	free
DRAWN: LYF	DATE: 2009-07-02	UNIT mm	SCALE free	REV. A	ZS00	
		FILE NO. Ckmtw-300-0005				

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Cankemeng](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#)
[63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#)
[66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#) [M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#)
[70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [FCN-367T-T012/H](#)
[80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-014-20-001000](#)
[803-43-024-10-001000](#)