



**SPECIFICATION:**

Current Rating: 3.0AMP  
 Contact Resistance: 20m Ω (max)  
 Insulation Resistance: 1000M Ω Min at 500V DC  
 Dielectric Strength: 500V AC Per 1 Minute  
 Operating Temperature: -40°C TO +105°C

**MATERIALS:**

Insulator: P.B.T.+30% Glass Fibre(UL 94V-0)  
 Contact: Brass  
 Contact plated: 0.8u" Gold Over Nickel

Poles	Part No.	Dimension mm		
		A	B	C
10	310R-10P	31.90	10.16	18.60
12	310R-12P	34.44	12.70	21.14
14	310R-14P	36.98	15.24	23.68
16	310R-16P	39.52	17.78	26.22
20	310R-20P	44.60	22.86	31.30
24	310R-24P	49.68	27.94	36.38
26	310R-26P	52.22	30.48	38.92
30	310R-30P	57.30	35.56	44.00
34	310R-34P	62.38	40.64	49.08
40	310R-40P	70.10	48.26	56.70
50	310R-50P	82.70	60.96	69.40
60	310R-60P	95.40	73.66	82.10
64	310R-64P	100.48	78.74	87.18

TOLERANCE TABLE	
.0	±0.30
.00	±0.20
.000	±0.05

APPROVED:	DATE:	深圳市灿科盟实业有限公司 CHANKEMENG INDUSTRYCO., LTD	TITLE: 310R-XP			
CHECKED:	DATE:		CLIENT P/N	/	SCALE	free
DRAWN: LYF	DATE: 2008-04-07	UNIT	mm	REV.	A	
		FILE NO.	Ckmtw-310-00003			

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Cankemeng](#) manufacturer:*

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [0009485154](#) [009176003701906](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#)  
[63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#) [65817-010LF](#)  
[65817-015LF](#) [66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#)  
[70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [FCN-367T-T012/H](#) [80.063.4001.1](#)  
[800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-014-20-](#)  
[001000](#)