


铆钉示意图



螺丝示意图

MATERIAL & FINISHES
 INSULATOR - PBT GLASS FILLED UL94V-0
 CONTACT - BRASS
 SHELL - STEEL
 PLATING - CONTACT
 - GOLD OVER NICKEL PLATED
 - SHELL
 NICKEL PLATED

ELECTRICAL CHARACTERISTICS
 RATING CURRENT : 3A
 CONTACT RESISTANCE : <15mΩ
 INSULATION RESISTANCE : >3000MΩ AT 500V
 DIELECTRIC VOLTAGE : 1000V AT 1 MINUTE
 OPERATING TEMPERATURE : -55° C TO+105° C

No. Of Contacts	Dim. A	Dim. B	Dim. C	Dim. D	Dim. E
9	16.33	24.99	30.81	19.28	4.5
15	24.66	33.32	39.14	27.51	
25	38.38	47.04	53.04	41.30	
37	54.84	63.50	69.32	57.71	

TOLERANCE TABLE

.0	±0.30
.00	±0.15
.000	±0.05

APPROVED:

DATE:

CHECKED:

DATE:

DRAWN:

DATE:

LYF

2013-9-12

Ckmtw 深圳市灿科盟实业有限公司
 CHANKLEMENT INDUSTRYCO., LTD

TITLE:

DMS-XP 母头 铆鱼叉锁螺丝

CLIENT P/N /

UNIT	mm	SCALE	free	REV.	A	XH00
FILE NO.	Ckmtw-DMS-0004					

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [D-Sub Standard Connectors](#) category:

Click to view products by [Cankemeng](#) manufacturer:

Other Similar products are found below :

[56F711-015](#) [LV242999-142T12](#) [015-0339-000](#) [015-0341-000](#) [015-0349-000](#) [015-0350-000](#) [015-0372-008](#) [015-8544-011](#) [015-8755-001](#)
[017041-0005](#) [020419-0104](#) [012-0467-000](#) [012-9507-114](#) [020745-0008](#) [609-25P](#) [609-9P](#) [M24308/2-23Z](#) [M24308/2-36Z](#) [CT0E22-14SC](#)
[CT0P14S-5SXS](#) [CT0P22-14PS](#) [CT0TA16-11SXCA232](#) [CT1E20-19SS](#) [CT2-10SL-3SC](#) [CT2-14S-2PCA34](#) [CT2-16S-17PS](#) [CT2-18-10PS-](#)
[FMLB-D](#) [CT2-18-11PCAU](#) [CT2-18-1PSAUA34](#) [CT2-22-19SC](#) [CT2-22-19SS-A206](#) [CT2-24-2PS](#) [CT2-28-12SC](#) [CT2-28-12SSA232](#) [CT6-](#)
[10SL-3SC](#) [CT6-10SL-4SC](#) [CT6-14S-2SC](#) [CT6-16-12SC](#) [CT6-18-10PSA206](#) [CT6-18-10PSA232](#) [CT6-18-10SSF127A206](#) [CT6-22-10PS](#)
[CT6-28-22SS](#) [CT6E14S-2S0](#) [CT6E14S-2SC-A206](#) [CT6E14S-5SC](#) [CT6E14SA7SC](#) [CT6E20-14SS](#) [CT6E22-10PS](#) [CT6E22-14PC](#)