



Specification
Insulator Material: Polyeser; UL94V-0
Standard: P.B.T
Contact Material: Brass
Contact plated: 0.8u"Gold Over 50u" Nickel

Poles: 2~40P
Current Rating : 3Amp
Contact Resistance: 20 Milliohms Max
Insulation Resistance : 5000MΩ Min.
Dielectric withstanding Voltage: AC 500V
Operation Temperature : -40℃ -- +105℃

APPROVED:		DATE:		TITLE:	
CHECKED:		DATE:		深圳市旭科盟实业有限公司 CHANKEMENG INDUSTRY CO., LTD	
DRAWN:		DATE:		CLIENT P/N	
LYF		2010-08-12		210S-1*XP (6.0/2.54/3.0) 蓝胶	
TOLERANCE TABLE				UNIT	
.0	±0.20			mm	
.00	±0.10			SCALE	
.000	±0.05			free	
				FILE NO.	
				REV.	
				A	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Cankemeng](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)