



PCB LAYOUT

TOLERANCE TABLE

.0	±0.20
.00	±0.10
.000	±0.05

Specification

Insulator Material: Polysacet, UL94V-0
Standard: Nylon-6T

Contact Material: Brass
Contact plated: Gold Over Nickel

Current Rating : 1Amp
Contact Resistance: 20 Milliohms Max
Insulation Resistance : 1000MΩ Min.
Dielectric withstanding Voltage: AC 500V
Operation Temperature : -40 °C -- +105 °C

APPROVED:	DATE:	<p>深圳市灿科盟实业有限公司 CHANKUENG INDUSTRY CO., LTD</p>
CHECKED:	DATE:	
DRAWN:	DATE:	TITLE:
LXF	2008-04-29	210-1S-2*XP 3.0/1.0/1.8

CLIENT P/N	SCALE	UNIT	FILE NO.
/	free	mm	Chantr-210-10002
REV.			
A			

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Cankemeng](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)