



**PCB Layout**

**SPECIFICATION**  
 Current Rate:3Amp  
 Contact Resistance:20mΩ MAX.at DC 1A  
 Insulation Resistance:1000MΩ MIN.atDC500V  
 Dielectric Strength:AC500V PER minute  
 Operation Temperature:-40°to +105°

**MATERIAL**

Insulator:Polyester ,UL94V-0  
 Standard:P.B.T  
 CONTACT:Brass  
 Contact plated: Gold Over Nickel  
 Poles:2~40P  
 Color:Black

TOLERANCE TABLE	
.0	±0.20
.00	±0.10
.000	±0.05

APPROVED:	DATE:	TITLE:			
CHECKED:	DATE:	220S-1*XP H=8.5MM			
DRAWN:	DATE:	CLIENT P/N	UNIT	SCALE	REV.
L.Y.F	2008-04-29	/	mm	free	⊕
		FILE NO.	Ckmtw-220-00001	REV.	A

深圳市灿科盟实业有限公司  
 Ckmtw CHANKEMENG INDUSTRYCO., LTD

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Cankemeng](#) manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)