



PCB Layout

**SPECIFICATION**

Current Rate: 3Amp  
 Contact Resistance: 20mΩ MAX.at DC 1A  
 Insulation Resistance: 1000MΩ MIN.at DC500V  
 Dielectric Strength: AC500V PER minute  
 Operation Temperature: -40°to +105°

**MATERIAL**

Insulator: Polyester, UL94V-0  
 Standard: PA6T  
 CONTACT: Brass  
 Contact plated: Gold Over Nickel  
 Poles: 2~40P (Double)  
 Color: Black

| TOLERANCE TABLE |       |
|-----------------|-------|
| .0              | ±0.20 |
| .00             | ±0.10 |
| .000            | ±0.05 |

|           |            |  |          |                   |  |
|-----------|------------|--|----------|-------------------|--|
| APPROVED: | DATE:      | <b>深圳市灿科盟实业有限公司</b><br>KIMT W CHANKEMENG INDUSTRY CO., LTD |          |                   |  |
| CHECKED:  | DATE:      | TITLE:<br>220S-2*XP H=8.5MM                                |          |                   |  |
| DRAWN:    | DATE:      | CLIENT P/N   | SCALE    | REV.              |  |
| LYP       | 2008-04-29 | /  | Free     | A                 |  |
|           |            | UNIT   | FILE NO. | ChamtW-220-000002 |  |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Cankemeng](#) manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)