



SPECIFICATIONS

Voltage rating: AC, DC 250V
 Current rating: AC, DC 2A
 Withstand voltage: 800V AC/min
 Insulation resistance: 1000MΩ/min.
 Temperature range: -25° C +85° C
 Applicable PC board thickness: 0.031"~0.063" (0.8~1.6)
 Contact resistance: Initial value/10mΩ max.
 After environmental testing/20mΩ max.
 Material: Post: Brass, Tin plated
 Base: Nylon66, UL94V-0

| Poles | Part No | Dimension mm | |
|-------|-----------|--------------|------|
| | | A | B |
| 2 | 2001S-2P | 2.0 | 6.0 |
| 3 | 2001S-3P | 4.0 | 8.0 |
| 4 | 2001S-4P | 6.0 | 10.0 |
| 5 | 2001S-5P | 8.0 | 12.0 |
| 6 | 2001S-6P | 10.0 | 14.0 |
| 7 | 2001S-7P | 12.0 | 16.0 |
| 8 | 2001S-8P | 14.0 | 18.0 |
| 9 | 2001S-9P | 16.0 | 20.0 |
| 10 | 2001S-10P | 18.0 | 22.0 |
| 11 | 2001S-11P | 20.0 | 24.0 |
| 12 | 2001S-12P | 22.0 | 26.0 |
| 13 | 2001S-13P | 24.0 | 28.0 |
| 14 | 2001S-14P | 26.0 | 30.0 |
| 15 | 2001S-15P | 28.0 | 32.0 |
| 16 | 2001S-16P | 30.0 | 34.0 |
| 17 | 2001S-17P | 32.0 | 36.0 |
| 18 | 2001S-18P | 34.0 | 38.0 |
| 19 | 2001S-19P | 36.0 | 40.0 |
| 20 | 2001S-20P | 38.0 | 42.0 |

TOLERANCE TABLE

| | |
|------|-------|
| .0 | ±0.20 |
| .00 | ±0.10 |
| .000 | ±0.05 |

APPROVED: DATE: **CHECKED:** DATE: **DRAWN:** LYF 2008-04-07

TITLE: 2001S-XP (不打孔)

CLIENT P/N / UNIT mm SCALE free REV. A

CKM 深圳市灿科盟实业有限公司
 CHANKLEMENT INDUSTRYCO., LTD

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Cankemeng](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)