



SPECIFICATIONS

Current rating: 3A AC/DC
 Voltage rating: 250V AC/DC
 Contact resistance: 20mΩ max.
 Withstand voltage: 1000V AC/min
 Insulation resistance: 1000MΩ/min.
 Temperature range: -25°C~+85°C
 Applicable PC board thickness: 0.063"(1.6)

Material:

Part No: 2~20
 Post: Brass, Tin/plated
 Base: Nylon66 UL94V-2

Poles	Part No.	Dimension mm	
		A	B
2	2501SB-2P	2.50	7.50
3	2501SB-3P	5.00	10.00
4	2501SB-4P	7.50	12.50
5	2501SB-5P	10.00	15.00
6	2501SB-6P	12.50	17.50
7	2501SB-7P	15.00	20.00
8	2501SB-8P	17.50	22.50
9	2501SB-9P	20.00	25.00
10	2501SB-10P	22.50	27.50
11	2501SB-11P	25.00	30.00
12	2501SB-12P	27.50	32.50
13	2501SB-13P	30.00	35.00
14	2501SB-14P	32.50	37.50
15	2501SB-15P	35.00	40.00
16	2501SB-16P	37.50	42.50
17	2501SB-17P	40.00	45.00
18	2501SB-18P	42.50	47.50
19	2501SB-19P	45.00	50.00
20	2501SB-20P	47.50	52.50

TOLERANCE TABLE	
.0	±0.20
.00	±0.10
.000	±0.05

APPROVED:	DATE:	TITLE: 2501SB-XP 带扣			
CHECKED:	DATE:	CLIENT P/N /			
DRAM: LYF	DATE: 2008-04-07	UNIT: mm	SCALE: Free	REV. A	KL00
		FILE NO. Chantw-2501-0007			

深圳市灿科盟实业有限公司
 CHANKLEMENT INDUSTRY CO., LTD

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Cankemeng](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)