

MATERIAL & FINISHES

INSULATOR - PBT GLASS FILLED UL94V-0

CONTACT- BRASS

SHELL - STEEL

PLATING - GOLD FLASH

ELECTRICAL CHARACTERISTICS

RATING CURRENT : 3A

CONTACT RESISTANCE : $\langle 20m\Omega \rangle$

INSULATION RESISTANCE : $>1000M\Omega$ at 500V

DIELECTRIC VOLTAGE: 1000V /MIN

OPERATING TEMPERATURE : -50° C TO+105° C

ĊΠ	69.40	55. 42 63. 50 69. 40 57. 5	55.42	DMS-37P	37
	53.04	47. 04 53. 04 41. 20	38. 96	DMS-25P	25
	39. 14	33. 32 39. 14 27. 51	25. 25	DMS-15P	15
	30.81	16. 92 24. 99 30. 81 19. 25	16.92	DMS-9P	9
	Dim. C	Dim. B	Dim. A	PART No.	POLES

			_		,		
	.000	.00	.0	TOLER,			
	±0.05	±0.10	±0.20	TOLERANCE TABLE			
	LYF	DRAWN:			CHECKED:	APPROVED:	
	2010-11-02	DATE:			DATE:	DATE:	
CKM-QR-GC-07/M	2010-11-02 FILE NO. Ckmtw-DMS-0001 REV. A HX00	UNIT mm SCALE free	P/N /	DMS-XP 公头 光孔	TITLE:	CkmtwCHANKLEMENT INDUSTRYCO.,LTD	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Standard Connectors category:

Click to view products by Cankemeng manufacturer:

Other Similar products are found below:

DCM37S732N DAM15P500 DEV09S364GTLF DEM09P032N DDM50P732N DAM15S332N 173109-2218 173109-2466 173109-2436 173109-2435 56F706-005-LI 56F711-015 015-0341-000 015-0372-008 015-8544-011 017041-0005 012-0515-000 012-9507-034 012-9507-114 012-9534-001 020745-0008 609-25P M24308/2-23Z M243082310F M243082410F M243082411F M24308/4-21 CT1A18-11PSA206 CT1N36-5SC CT2-16S-17PS CT2-20-15PCAU CT2-24-12PS CT2-24-28PSF127A206 CT2-32-9PC CT6F9767-14-4-14S-5PC CT6FA10SL-4PS CT7-18-10SCAU CT7-18-12SCAU CT7-18-1PC CT7-18-1PCAU CT7-18-21SCAU M83513/01-FC M83723/76W24619 L/C M85049/48-3-2F 69001-865 6STD09PCM99B70X 6STD09SCT99S40X 6STD15PCT99S40X 6STD15SCM99B30X