



SUGGESTED PCB LAYOUT

NOTE:  
 Rating  
 Voltage rating:30V AC (Rms)  
 Current rating: 1.5A MAX  
 Electrical characteristics  
 Contact resistance:30mΩ MAX  
 Insulation resistance:1000MΩ MIN  
 Dielectrc withstanding voltage: 500V AC AT 1minute  
 Mechanical characteristics  
 Contact insertion force:3.0kg MAX  
 Contact withdrawal force:1.5kg MIN  
 Materials  
 Contact:Phosphor Bronze Gold Plating Over Nickel  
 Housing:PB1  
 Shell: Spec Plating Nickel  
 Contacts:Tin or Gold flashed

APPROVED:	DATE:	TITLE: USB-B/F-2*2P 90度 DIP 白胶有后盖			
CHECKED:	DATE:	CLIENT P/N /			
DRAWN: LYF	DATE: 2008-04-06	UNIT mm	SCALE free	REV. A	HF00
TOLERANCE TABLE					
.0	±0.30				
.00	±0.15				
.000	±0.05				

深圳市灿科盟实业有限公司  
 CHANKLEMENT INDUSTRYCO., LTD

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [USB Connectors](#) category:*

*Click to view products by [Cankemeng](#) manufacturer:*

Other Similar products are found below :

[10033527-N3112MLF](#) [17-210561](#) [GMCB05B11124H1EU](#) [17-200931](#) [65-647-8-BK-BU](#) [690-010-295-484](#) [73725-1191BLF](#) [950](#) [E8144-B01021-L](#) [A-USB A-LP-SMT-C](#) [A-USB B-TOP-C](#) [MUSBA511N5](#) [MUSBB15131](#) [MUSBC111M5](#) [MUSBD11135](#) [217450-1](#) [CA 6 W LD](#)  
[896-30-004-00-000000](#) [KUSBVX-BS1N-W30](#) [KUSBX-AP-KIT-SCBLK](#) [KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W](#) [KUSBX-SMTAS1NBTR](#) [KUSBX-SMTBS1NBTR](#) [30-498-6](#) [SK-60A-2](#) [17-200261](#) [17-210051](#) [1734082-1](#) [FK-37-32SL](#) [30-1574](#) [30-470](#) [30-489](#) [30-541](#) [30-572-3](#) [30-9503](#) [M9177/2-1](#) [MAB 5 S](#) [MIKROE-1451](#) [33UBBR-04SW11R](#) [USBFTV2PEM2G](#) [USBFTVC6ZN](#) [USBFTVSCCG](#)  
[KUSBX-AS2N-W30](#) [KUSBX-SLAS1N-W](#) [KUSBX-SLAS1N-W30](#) [1-1734084-2](#) [E8110-001-01](#) [MUSBC11135](#) [NK-27-32SL](#)