


.000	.00	.0	TOLER,					
±0.05	±0.20	±0.30	TOLERANCE TABLE					
LYF	DRAWN:			CHECKED:	APPROVED:			
DATE: 2009-11-28			DATE:		DATE:			
2009-11-28 FILE NO. Ckmtw-DB-0002 REV. A HX00	UNIT mm SCALE free \oplus	P/N /	DB-XP 公头 焊线 传统式	TITLE:	CkmtwcHANKLEMENT INDUSTRYCO., LTD			

37	25	15	9	POLES
DB-37P	DB-25P	DB-15P	DB-9P	PART No.
69.40	53.04	39.14	30.81	Dim. A
63.50	53.04 47.04	39.14 33.32	24.99	Dim. B
69.40 63.50 55.42 57.71	38.96 41.20	25.25 27.51	16.92 19.25	Dim. C
57.71	41.20	27.51	19.25	Dim. D







MATERIAL & FINISHES INSULATOR - PBT GLASS FILLED UL94V-0 CONTACT- BRASS OR PHOSPHOR BRONZE SHELL - STEEL PLATING - CONTACT SELECTIVE GOLD OVER NICKEL PLATED(CONTACT AREA) TIN/LEAD OVER NICKEL PLATED(TAIL AREA) - SHELL TIN OR ZINC OVER COPPER PLATED

ELECTRICAL CHARACTERISTICS CURRENT RATING : 3A CONTACT RESISTANCE : 20mΩ MAX INSULATION RESISTANCE : 1000MΩ AC 500V DIELECTRIC VOLTAGE : 500V /MIN OPERATING TEMPERATURE : -55°C TO+105°C

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Standard Connectors category:

Click to view products by Cankemeng manufacturer:

Other Similar products are found below :

DCM37S732N DAM15P500 DEV09S364GTLF DEM09P032N DDM50P732N DAM15S332N 173109-2218 173109-2466 173109-2436 173109-2435 56F706-005-LI 56F711-015 015-0341-000 015-0372-008 015-8544-011 017041-0005 020419-0104 012-0515-000 012-9507-034 012-9507-114 012-9534-001 020745-0008 609-25P M24308/2-23Z M243082310F M243082410F M243082411F M24308/4-21 CT1A18-11PSA206 CT1N36-5SC CT2-16S-17PS CT2-20-15PCAU CT2-24-12PS CT2-24-28PSF127A206 CT2-32-9PC CT6F9767-14-4-14S-5PC CT6FA10SL-4PS CT7-18-10SC CT7-18-10SCAU CT7-18-12SCAU CT7-18-1PC CT7-18-1PCAU CT7-18-21SCAU M83513/01-FC M83723/76W24619 L/C M85049/48-3-2F 69001-865 6STD09PCM99B70X 6STD09SCM99B30X 6STD09SCT99S40X