



适用线路板  
RECOMMENDED PCB LAYOUT

Pin 位	Type	A	B	C	Pin 位	Type	A	B	C
4	0.5-15-4PBX	1.5	2.6	6.4	34	0.5-15-33PBX	16.5	17.6	21.4
5	0.5-15-5PBX	2	3.1	6.9	35	0.5-15-34PBX	17	18.1	21.9
6	0.5-15-6PBX	2.5	3.6	7.4	36	0.5-15-35PBX	17.5	18.6	22.4
7	0.5-15-7PBX	3	4.1	7.9	37	0.5-15-36PBX	18	19.1	22.9
8	0.5-15-8PBX	3.5	4.6	8.4	38	0.5-15-37PBX	18.5	19.6	23.4
9	0.5-15-9PBX	4	5.1	8.9	39	0.5-15-38PBX	19	20.1	23.9
10	0.5-15-10PBX	4.5	5.6	9.4	40	0.5-15-39PBX	19.5	20.6	24.4
11	0.5-15-11PBX	5	6.1	9.9	41	0.5-15-40PBX	20	21.1	24.9
12	0.5-15-12PBX	5.5	6.6	10.4	42	0.5-15-41PBX	20.5	21.6	25.4
13	0.5-15-13PBX	6	7.1	10.9	43	0.5-15-42PBX	21	22.1	25.9
14	0.5-15-14PBX	6.5	7.6	11.4	44	0.5-15-43PBX	21.5	22.6	26.4
15	0.5-15-15PBX	7	8.1	11.9	45	0.5-15-44PBX	22	23.1	26.9
16	0.5-15-16PBX	7.5	8.6	12.4	46	0.5-15-45PBX	22.5	23.6	27.4
17	0.5-15-17PBX	8	9.1	12.9	47	0.5-15-46PBX	23	24.1	27.9
18	0.5-15-18PBX	8.5	9.6	13.4	48	0.5-15-47PBX	23.5	24.6	28.4
19	0.5-15-19PBX	9	10.1	13.9	49	0.5-15-48PBX	24	25.1	28.9
20	0.5-15-20PBX	9.5	10.6	14.4	50	0.5-15-49PBX	24.5	25.6	29.4
21	0.5-15-21PBX	10	11.1	14.9	51	0.5-15-50PBX	25	26.1	29.9
22	0.5-15-22PBX	10.5	11.6	15.4	52	0.5-15-51PBX	25.5	26.6	30.4
23	0.5-15-23PBX	11	12.1	15.9	53	0.5-15-52PBX	26	27.1	30.9
24	0.5-15-24PBX	11.5	12.6	16.4	54	0.5-15-53PBX	26.5	27.6	31.4
25	0.5-15-25PBX	12	13.1	16.9	55	0.5-15-54PBX	27	28.1	31.9
26	0.5-15-26PBX	12.5	13.6	17.4	56	0.5-15-55PBX	27.5	28.6	32.4
27	0.5-15-27PBX	13	14.1	17.9	57	0.5-15-56PBX	28	29.1	32.9
28	0.5-15-28PBX	13.5	14.6	18.4	58	0.5-15-57PBX	28.5	29.6	33.4
29	0.5-15-29PBX	14	15.1	18.9	60	0.5-15-58PBX	29.5	30.6	34.4
30	0.5-15-30PBX	14.5	15.6	19.4	64	0.5-15-60PBX	31.5	32.6	36.4
31	0.5-15-31PBX	15	16.1	19.9	68	0.5-15-64PBX	33.5	34.6	38.4
32	0.5-15-32PBX	15.5	16.6	20.4	80	0.5-15-80PBX	39.5	40.6	44.4
33	0.5-15-33PBX	16	17.1	20.9					

技术指标:

- 1、塑件表面应光洁、无毛刺、明显收缩、缺陷、裂纹等现象;
- 2、温度范围: -25°C~85°C;
- 3、额定电压: 50V, AC, DC(等效);
- 4、接触电阻:  $\leq 0.03\Omega$ ;
- 5、绝缘电阻:  $\geq 500M\Omega$ ;
- 6、耐压: 500V, AC/minute.

4	191-0200-004	弹片 Fitting Nail	磷青铜 Phosphor Bronze	2	电蚀制: 单个表面粗糙度30u"MIN, 膜厚 80u"MIN.
3	184-0400-003	铆 Actuator	PPS(U94V-0)	1	热/热
2	184-0100-002	端子 Contact	磷青铜 Phosphor Bronze	n×1	电蚀制: 单个表面粗糙度30u"MIN, 膜厚 80u"MIN.
1	184-0300-001	壳体 Housing	LCP/PA46(U94V-4)	1	热

TOLERANCE TABLE

.0	±0.30
.00	±0.20
.000	±0.05

APPROVED:	DATE:	Ckmtw 深圳市灿科盟实业有限公司 CHANKLEMENT INDUSTRYCO., LTD					
CHECKED:	DATE:	TITLE: FPC0.5-XP 下接 掀盖式					
DRAWN: LYF	DATE: 2012-09-21	PROD. P/N		/			
		UNIT	mm	SCALE	free	⊕	
		FILE NO.	Ckmtw-FPC-0061	REV.	A	XFRO	

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [FFC & FPC Connectors](#) category:*

*Click to view products by [Cankemeng](#) manufacturer:*

Other Similar products are found below :

[00-6200-227-022-800](#) [006205250500825+](#) [006205280500825+](#) [FPH-1602G](#) [086222026001800](#) [52610-0675](#) [62674-201121DLF](#) [52746-1671-TR250](#) [10051922-1610EHLF](#) [10051922-2810EHLF](#) [686322124422](#) [XF3M-2915-1B-R100](#) [AYF353125A](#) [AYF530665TA](#) [AYF534065TA](#) [20FLH-RSM1-TB](#) [207356-1](#) [SFW12R-5STE9LF](#) [SFW18R-1STAE9LF](#) [SFW4R-5STE9LF](#) [52807-0430](#) [046283021002868+](#) [FFC05011-10SBB114W5M](#) [502250-8027](#) [67000-008LF](#) [200528-0260](#) [FH28K-10S-0.5SH](#) [FH52K-6S-0.5SH](#) [0.5K-DX-30PWB](#) [DS1020-08-10VBT12](#) [THD0515-34CL-GF](#) [X05A10L28G](#) [ECC2841061EU](#) [1.0K-DHQX-16PWB](#) [1.0K-DHQX-30PWB](#) [1775333-6](#) [10054365-202110ELF](#) [10054365-242110ELF](#) [10054365-282110ELF](#) [10064555-392220HLF](#) [59453-041110EBHLF](#) [59453-091110EDHLF](#) [62674-241141ALF](#) [62684-432100ALF](#) [62684-451100AHLF](#) [62684-5721N0ALF](#) [HFW11R-1STE1MTLF](#) [HFW12R-1STE9LF](#) [HFW14R-1STE9MTLF](#) [HFW18S-2STE9LF](#)