



Material
 Insulator : PA6T Glass Fiber(U194-0)
 Terminal : Brass plated Tin
 Spring plate: SUS 301 plated Gold
 Cover : SPCC plated Ni

Specification
 Current Rating: 50mA DC 5V
 Insulation Resistance: 100MΩ Min. at 100V DC
 Dielectric Withstanding Voltage: AC 250V/ Min
 Operating Temperature: -20° C~+70° C
 Contact Resistance: 50mΩ Mix.

NO.	NAME	MATERIAL	NATIONALITY	QTY.	FINISHING
1	TERMINAL	Brass	China	1	Silver plating
2	CASE	PA66	China	1	Black
3	CONT ACT	Phosphor bronze	Korea	1	Contact side silver plating
4	BRACKET	SPCC-SD	China	1	CuSn plating
5	STEM	PA66 Chiro		1	H± 9.5mm
		PC JAF	AN	1	H>9.5mm

APPROVED: DATE: **CK** 深圳市灿科盟实业有限公司
 CHANKLEMENT INDUSTRYCO., LTD

CHECKED: DATE: **CK** 轻触开关 646#5 带支架 侧按

DRAWN: DATE: 2008-11-24
 LYF
 CLIENT P/N: C3025482
 UNIT: mm SCALE: free SHEET: 4/1
 FILE NO. K-KM02S01P-C000 REV. A GT01

TOLERANCE TABLE	
.0	±0.20
.00	±0.10
.000	±0.05

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Tactile Switches](#) category:

Click to view products by [Cankemeng](#) manufacturer:

Other Similar products are found below :

[5GTH92001](#) [5GTH9202242](#) [6407-250V-25273P](#) [ADTSA62NV](#) [ADTSA62RV](#) [B3F-3123](#) [1977177-8](#) [1977266-1](#) [ADTSA63NV](#)
[ADTSM21NSVTR](#) [ADTSM25RVTR](#) [ADTSM32NVTR](#) [ADTSMW64RV](#) [FSMRA4JHA04](#) [GS4.70F300QP](#) [KSC241J SP DELTA LFS](#)
[3FTL600RAS](#) [3FTL640RAS](#) [Y96K132V0FPLFS](#) [5GTH9658222](#) [6407-250V-25343P](#) [ADTSM31NVTR](#) [2-1977120-7](#) [TSJW-5.2-260-TR](#)
[KMT011MNGJLHS](#) [B3WN6002S](#) [70-201.0](#) [ADTSG648NV](#) [ADTSM62KSVTR](#) [ADTSM648NV](#) [95C06E3RAT](#) [5GTH96561](#) [3ATH9Q](#)
[FSMRA8JHA04](#) [HARS0073](#) [Y33R411N9FPLFT](#) [Y31C01402FPLFS](#) [PTS645SK50SMTR92](#) [ADTSM32NVB](#) [KMS233GPWTLFG](#)
[Y78B64124FP](#) [Y96D113G0FP LFS](#) [Y33A812C5FP LFT](#) [Y56B2D120FP LFS](#) [PTS645 DVM83-BN125-2 LFS](#) [B3W 1000G](#) [KSC621G OL](#)
[LFS](#) [B3F 1002C](#) [B3F 0047H](#) [B3F 1000G](#)